



- Termofijadora abierta.
- Thermoadhesive open.



- Palanca de presión.
- Pressure lever.



- Palanca de apertura y cierre.
- Opening & closing lever.



- Mesa para termofijadora con pieza antideslizante.
- Table for fusing machines PLT with non-slip part.



PL/T900 90x40	90x40 cm	230V Monofase	2.250W	0-230 °C	0-90 Segundos	79 Kg Neto 100 Kg Bruto	100x100x64cm
MESA TERMOFIJADORA			BAB001			16,5 Kg Neto 18 Kg Bruto	81x46x15cm

MANUAL FUSING AND TRANSFER PL/T900 90x40

OB4102



The thermoadhesive PL/T press, with its steel framework, is tough, safe, reliable and easy to be operated. A manual control makes possible to set the pressure of the top and the pressing time, whereas the temperature of the top is set through a digital thermostat. A safety device prevents the top from closing accidentally. The work surface is 90x40 cm. Pressure = 3 kg/cm².

TABLE FOR COMEL FUSING MACHINES BAB001



Table for with non-slip part that prevents the slip of the fusing machine. Measurements: Height 78.7x51.1x71.7 cm.

TERMOFIJADORA DE PLATO PL/T900 90x40

OB4102



Termofijadora manual de plato PL/T con estructura de acero: es resistente, segura, fiable y fácil de utilizar. Un control manual permite ajustar la presión de la parte superior y el tiempo de prensado, mientras que la temperatura de la parte superior se ajusta a través de un termostato digital. Un dispositivo de seguridad impide que la tapa se cierre accidentalmente. El área de trabajo es de 90x40cm. Presión = 3 kg/cm².

MESA PARA TERMOFIJADORAS COMEL BAB001



Mesa para termofijadoras Comel con pieza antideslizante que impide el deslizamiento de la termofijadora de acero. Medidas: altura 78,7x51,1x71,7 cm.