



www.reymatex.net

												Optional Device
UHF-9304-243-M14	2	4	2.2 mm	4 mm	6 mm	3.8	0.8 ~ 1.8	0.5 ~ 6	8 mm	#11 mm	6.500 S.P.M	• US038 Chainstitch cutter

### UHF-9304-243-M14

OA7626J



Top feed high speed overlock machine cylinder bed, 2 needles 4 threads. For thin and medium materials. Maximum sewing speed 6.500 SPM.

### UHF-9304-243-M14

OA7626J



Klein Zylinder Hoch-Geschwindigkeit Obertransport Overlockmaschine: 2 Nadeln 4 Fädig für Normal Säumen.

### UHF-9304-243-M14

OA7626J



Surjeteuse 2 aiguilles 4 fils à petit canon à grande vitesse à entraînement supérieur.

### UHF-9304-243-M14

OA7626J



Máquina overlock de arrastre superior de base cilíndrica de 2 agujas 4 hilos para géneros medios y finos. Velocidad 6.500 PPM.

#### A

- Front top feed dog.
- Diente superior.
- Ober Transporteur.
- Griffe supérieure.

#### B

- Fabric tension controlling device (tension roller).
- Mecanismo tensor para colocar los cuellos de las camisetas.
- Spannmechanismus, um die Hälse der Hemden zu platzieren (Spannrolle).
- Mécanisme de tension pour faire les cols des t-shirt.