



2/3"	1.6/25mm C	2/3"	1/1.8"	1/2"
FOCAL LENGTH		f=25mm		
MAX. DIAMETER (RATIO)		F=1:1.6~16		
ELEMENT		7 GROUPS 9 ELEMENTS		
PICTURE SIZE		6.6x8.8mm	5.4x7.2mm	4.8x6.4mm
ANGLE	VER. ANGLE	15.0°	12.3°	10.9°
	HOR. ANGLE	19.9°	16.4°	14.6°
	DIA. ANGLE	24.8°	20.4°	18.0°
DISTORTION (TV)		0.01%		
SHOOTING RANGE AT VER.		26.3mm	21.5mm	19.1mm
MINIMUM FOCUS HOR.		35.1mm	28.7mm	25.5mm
DISTANCE DIA.		43.9mm	35.9mm	31.9mm
MINIMUM FOCUS DISTANCE		0.1m		
FLANGE BACK		17.526mm in air		
BACK FOCUS		11.2mm in air		
FILTER SCREW SIZE		M30.5x0.5		
FRONT/REAR EFFECTIVE DIA.		FRONT ϕ 20.0mm	REAR ϕ 13.8mm	
MOUNT		C-MOUNT		
EXIT PUPIL		-46.6mm		
TEMPERATURE RANGE		-10~+50°C		
STORAGE TEMPERATURE RANGE		-20~+60°C		
RESOLUTION CENTER/CORNER		CENTER 160本/mm	CORNER 100本/mm	
WEIGHT		115 g		

NOTE: Specifications and availability are subject to change without notice

注) 本仕様については、予告なしに変更する場合があります。

		尺度	1/1	工場番号	CH1054
		機種名	2/3" F1.6 f=25mm		
2017.04.28	更新 (彫刻誤記訂正)	機種番	LM25JC5M2 外観図		
2014.12.25	更新				
2013.4.15	作成年月日				