



|   |           |                                 |             |             |
|---|-----------|---------------------------------|-------------|-------------|
| 2/3" 2.8/25mm C                           |           | 2/3"                            | 1/1.8"      | 1/2"        |
| FOCAL LENGTH                              |           | f=25mm                          |             |             |
| F-NUMBER                                  |           | F=2.8-16                        |             |             |
| PICTURE SIZE                              |           | 6.6 × 8.8mm                     | 5.4 × 7.2mm | 4.8 × 6.4mm |
| ANGLE OF VIEW<br>(∞)                      | VER.ANGLE | 15.0°                           | 12.4°       | 11.0°       |
|   | HOR.ANGLE | 20.0°                           | 16.4°       | 14.6°       |
|   | DIA.ANGLE | 24.8°                           | 20.4°       | 18.2°       |
| DISTORSION (TV)                           |           | 0.06%                           | 0.02%       | 0.02%       |
| FIELD OF VIEW<br>(MINIMUM FOCUS DISTANCE) | VER.      | 56mm                            | 46mm        | 41mm        |
|   | HOR.      | 75mm                            | 62mm        | 55mm        |
|   | DIA.      | 95mm                            | 77mm        | 69mm        |
| MINIMUM FOCUS DISTANCE                    |           | 0.2m                            |             |             |
| FLANGE BACK                               |           | 17.526mm in air                 |             |             |
| BACK FOCUS                                |           | 11.7mm in air                   |             |             |
| FILTER SCREW SIZE                         |           | None                            |             |             |
| FRONT/REAR EFFECTIVE DIA.                 |           | FRONT φ 18.9mm REAR φ 13.7mm    |             |             |
| MOUNT                                     |           | C-MOUNT                         |             |             |
| EXIT PUPIL                                |           | -58.8mm                         |             |             |
| TEMPERATURE RANGE                         |           | -10~+50°C                       |             |             |
| STORAGE TEMPERATURE RANGE                 |           | -20~+60°C                       |             |             |
| RESOLUTION CENTER/CORNER                  |           | CENTER 160lp/mm CORNER 100lp/mm |             |             |
| WEIGHT                                    |           | 55g                             |             |             |

NOTE: Specifications and availability are subject to change without notice

注) 本仕様については、予告なしに変更する場合があります。

|            |      |     |                      |      |         |
|------------|------|-----|----------------------|------|---------|
|            |      | 尺度  | 1:1                  | 工場番号 | S10-635 |
| 2020/10/22 | 誤記訂正 | 機種名 | 2/3" f=25mm F2.8 5MP |      |         |
| 2019/09/26 | 誤記訂正 |     |                      |      |         |
| 2019/02/22 | 作成   | 機種番 | LM25JC5MC 外観図        |      |         |
| 日付         | 内容   |     |                      |      |         |