

SP-100/200/300/200T Multi-Position Magnetic Stirrer

Magnetic Series

Introduction

Multi-position Magnetic Stirrer is designed for the high-efficiency experiments and has 4/8/12 stirring bar configurations to choose. It can use laboratory space efficiently. DC brushless motor makes the model, low speed but stable, high speed but powerful with low noise. Stainless steel is coated by silicone resin film disk. Non-slip and anti-corrosion.

Features

1. Digital display stirring speed at real-time, stirring bars operate synchronously and provide uniform agitation reaction conditions.
2. Efficient multi-position magnetic stirrers configure 4/8/12 stirring positions to use lab space efficiently.
3. DC brushless motor. Low speed but stable, high speed but powerful. Low noise and free maintenance.
4. Stainless steel is coated by silicone resin film pad. Non-slip and anti-corrosion.



SP-100



SP-200



SP-300

Parameters

Model	SP-100	SP-200	SP-300
Stirring Point Quantity	4	8	12
Size of Stirring Bars	Φ8x46mm	Φ8x46mm	Φ8x46mm
Max. Stir Capacity	400mlx4	400mlx8	400mlx12
Digital Display	Speed Display	Speed Display	Speed Display
Speed Range	200~1200rpm	200~1200rpm	200~1200rpm
Temp. Control Range (surface)	/	/	/
Platform Material	stainless steel with silicon pad	stainless steel with silicon pad	stainless steel with silicon pad
Motor	DC brushless motor	DC brushless motor	DC brushless motor
Voltage	AC100~230V, 50/60Hz	AC100~230V, 50/60Hz	AC100~230V, 50/60Hz
Power	20W	20W	20W
Fuse	250V,1A, Φ5x20	250V,1A, Φ5x20	250V,1A, Φ5x20
Dimension	W.115xD.480xH.50mm	W.205xD.480xH.50mm	W.295xD.480xH.50mm
Net Weight	3kgs	4kgs	5kgs