ACF-2125 LOW-PROFILE ADAPTER



This adapter allows 1%" eyepieces, Barlows and accessories to be used in 2" focusers, housings, extension tubes, diagonals, etc. The brass clamp ring assures tight, non-marring locking. Use of Tele Vue 1%" eyepieces (with their matching undercuts on the barrels) will minimize the possibility of accidental eyepiece fall-out.



IMPORTANT WARNING

IF YOU ARE USING THIS ADAPTER IN A 2" DIAGONAL, BE SURE THAT THE 11/4" COMPONENTS (SUCH AS BARLOWS) DO NOT CONTACT THE DIAGONAL MIRROR. IF THERE IS A DANGER OF CONTACT, CONSIDER USING TELE VUE'S "HIGH HAT" ADAPTER INSTEAD (ASF-8125).

Rev: 11/20/2017

ACF-2125 LOW-PROFILE ADAPTER



This adapter allows $1\frac{1}{4}$ " eyepieces, Barlows and accessories to be used in 2" focusers, housings, extension tubes, diagonals, etc. The brass clamp ring assures tight, non-marring locking. Use of Tele Vue $1\frac{1}{4}$ " eyepieces (with their matching undercuts on the barrels) will minimize the possibility of accidental eyepiece fall-out.



IMPORTANT WARNING

IF YOU ARE USING THIS ADAPTER IN A 2" DIAGONAL, BE SURE THAT THE 1¼" COMPONENTS (SUCH AS BARLOWS) DO NOT CONTACT THE DIAGONAL MIRROR. IF THERE IS A DANGER OF CONTACT, CONSIDER USING TELE VUE'S "HIGH HAT" ADAPTER INSTEAD (ASF-8125).

Rev: 11/20/2017

ACF-2125 LOW-PROFILE ADAPTER



This adapter allows $1\frac{1}{4}$ " eyepieces, Barlows and accessories to be used in 2" focusers, housings, extension tubes, diagonals, etc. The brass clamp ring assures tight, non-marring locking. Use of Tele Vue $1\frac{1}{4}$ " eyepieces (with their matching undercuts on the barrels) will minimize the possibility of accidental eyepiece fall-out.



IMPORTANT WARNING

IF YOU ARE USING THIS ADAPTER IN A 2" DIAGONAL, BE SURE THAT THE 1¼" COMPONENTS (SUCH AS BARLOWS) DO NOT CONTACT THE DIAGONAL MIRROR. IF THERE IS A DANGER OF CONTACT, CONSIDER USING TELE VUE'S "HIGH HAT" ADAPTER INSTEAD (ASF-8125).

Rev: 11/20/2017

ACF-2125 LOW-PROFILE ADAPTER



This adapter allows $1\frac{1}{4}$ " eyepieces, Barlows and accessories to be used in 2" focusers, housings, extension tubes, diagonals, etc. The brass clamp ring assures tight, non-marring locking. Use of Tele Vue $1\frac{1}{4}$ " eyepieces (with their matching undercuts on the barrels) will minimize the possibility of accidental eyepiece fall-out.



IMPORTANT WARNING

IF YOU ARE USING THIS ADAPTER IN A 2" DIAGONAL, BE SURE THAT THE 1¼" COMPONENTS (SUCH AS BARLOWS) DO NOT CONTACT THE DIAGONAL MIRROR. IF THERE IS A DANGER OF CONTACT, CONSIDER USING TELE VUE'S "HIGH HAT" ADAPTER INSTEAD (ASF-8125).

Rev: 11/20/2017