







Hi-Vol® is a tough supply hose that maintains excellent water flow. It is the premium extruded-through-the-weave, large-diameter, nitrile-rubber hose with the ability to deliver more water. This supply hose is compact and durable with a high resistance to oil, chemicals, UV and ozone. A tough, high-tensile cover and lining, permanently interlocked with the synthetic reinforcement, provides greater abrasion and puncture resistance, along with unmatched kink resistance. Hi-Vol is guaranteed to meet specified burst pressure and exceeds the NFPA 1961 standard. Hi-Vol will never mildew or rot.

# **UNIQUE DESIGN FEATURES:**

- · Achieves maximum water flow
- Compact and durable
- · High resistance to oil, chemicals, UV and ozone
- · Greater abrasion and puncture resistance
- · Unmatched kink resistance
- · Eliminates mildew and rot

Backed by BullDog's Municipal Fire Hose Ten-Year Warranty. bulldoghose.com/resources



Step up your water delivery!
Contact us today: 833.655.9201 · bulldoghose.com



## **FEATURES:**

#### **Lowest Friction Loss**

Superior efficiency on the fireground, delivering more GPM with lowest friction loss. Smooth inner liner keeps friction loss to a minimum.

## **Best-in-Class Adhesion**

Provides enhanced hose performance and increased hose life.

# **Improved Packability** Compact and flexible.

## **Anti-Burst Technology**

Hose is protected from catastrophic bursts, even with a 1/2" diameter hole through both the jacket and liner.

## **Superior Abrasion Performance**

Nitrile-rubber cover eliminates additional weight issues caused by water pick up during use and greatly increases abrasion resistance, providing a long service life.

## **Exceeds Standards**

Hi-Vol® is manufactured to meet or exceed the NFPA 1961 standard.

#### Standard Colors are Yellow and Red

#### ULC

Available on 4" and 5".

# **TECHNICAL SPECIFICATIONS:**

			Pressure			Weight	Coil Diameter
Size	Standard color	Service	Proof	Burst	<b>Bowl Size</b>	(100'/30M)	(100'/30M)
inch mm		psi kpa	psi kpa	psi kpa	inch	lbs kg	inch mm
3 75	Yellow/Red	300 2100	600 4200	900 6300	3-5/16	60 27.2	25 635
4 100 UC	Yellow/Red	225 1575	450 3150	675 4725	4-5/32	84 38.1	24 610
5 125 (ມູເ	Yellow/Red	200 1400	400 2800	600 4200	5-3/8	104 47.2	27 686
6 150	Yellow	200 1400	400 2800	600 4200	6-15/32	148 67.1	32 813

BullDog Hose Company maintains ongoing product improvement and development programs. Therefore BullDog reserves the right to modify any product or specification without prior notice. If necessary, please contact BullDog Hose Company customer service to ensure that all claims and technical data are current.





