

REDSKIN/BLUESKIN®

General Industrial Hose

Respond to fires quickly with BullDog Redskin/Blueskin®. The hose is a lay-flat, lightweight, flexible firehose specifically designed for industrial fire protection. Bringing tough, versatile firefighting power to departments in industrial situations. Redskin/Blueskin is UL approved and features a unique through-the-weave, one-piece construction that will not delaminate. The synthetic reinforcement is totally encased in a nitrile-rubber cover and lining which is resistant to fuels, oils and chemicals. Dependable, lay-flat and flexible, BullDog Redskin/Blueskin firehose is specifically engineered for industrial fire protection.

UNIQUE DESIGN FEATURES:

- · Lower friction loss
- · Reduces pumping costs
- · Higher flow rates and further pumping distance
- · Fast deployment and retrieval





Step up your fuel/water delivery!
Contact us today: 833.655.9201 · bulldoghose.com

REDSKIN/BLUESKIN®



FEATURES:

Extreme Durability

Hose meets or exceeds specifications for heat and kink resistance.

Durable Construction

Lay-flat, lightweight and flexible design is really suited for industrial fire protection and in-plant apparatus.

Less Maintenance

No drying time required just wash and store.

Long Service Life

Nitrile-rubber cover eliminates additional weight issues caused by water pick up during use and greatly increases abrasion resistance, providing a long service life. The hose is designed to resist cracking mildew and rot, which translates to a long service life.

Chemical-Resistant

Resists fuels, oils and a wide range of chemicals and bases.

Best in Class Adhesion

Best in class adhesion provides enhanced hose performance and increased hose life.

Exceeds Standards

Redskin/Blueskin® is manufactured to meet or exceed NFPA 1961 standard.

Listing Options

Agency approvals by UL, ULC, or FM are available on select sizes and colors, inquire for details.

TECHNICAL SPECIFICATIONS:

	Pressure				Weight	Coil Diameter
Size	Service	Proof	Burst	Bowl Size	(50'/15M)	(50'/15M)
inch mm	psi kpa	psi kpa	psi kpa	inch	lbs kg	inch mm
1-1/2 38 WD (!)	300 2100	600 4200	900 6300	1-3/4	11 5	13 330
1-3/4 45 WC	300 2100	600 4200	900 6300	2	14 6.4	13-3/4 349
2 50	300 2100	600 4200	900 6300	2-5/16	18 8.2	14-1/2 368
2-1/2 65 (LL) (N)	300 2100	600 4200	900 6300	2-3/4	22 10	14-1/2 368
3 75	300 2100	600 4200	900 6300	3-13/32	30 13.6	16-1/2 419

BullDog Hose Company maintains ongoing product improvement and development programs. Therefore BullDog reserves the right to modify any product or specification without prior notice. If necessary, please contact BullDog Hose Company customer service to ensure that all claims and technical data are current.





NITRILE-RUBBER COVER ELIMINATES WATER PICK UP AND INCREASES ABRASION RESISTANCE FOR A LONG SERVICE LIFE

