


CONCRETE CHIC by AMERICAN OLEAN




Color Availability




***Current Cream**



***Elegant Gray**



***Stylish Charcoal**




Trendy Tan






Vogue Brown

SPECIFICATIONS

SIZES

			THICKNESS	SQ.FT/ CARTON	PIECES/ CARTON
	*12 x 24 Floor Tile	11-13/16" x 23-13/16" (30.00 cm x 60.48 cm)	5/16"	15.60	8

TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose	3 x 12	P-43C9	30
	Cove Base <input type="checkbox"/>	6 x 12	P-36C9TB	22
	Cove Base Outcorner <input type="checkbox"/>	6 x 1	PC-36C9TB	15

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position. Cove base and cove corner trim are suitable for non-freezing climates only.

Ceramic body

APPLICATIONS


	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level to interior spaces expected be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

USAGE

FLOORS	WALLS	COUNTERTOPS
F	W	C

INSTALLATION & PRICING

RECOMMENDED GROUT JOINT:	SHADE VARIATION
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)	 HIGH (V3)
RELATIVE PRICING: Medium	




PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	3 (CC68, CC69) 4 (CC65, CC66, CC67)

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

FEATURES:

-  PRE-CONSUMER RECYCLED CONTENT
-  MADE IN THE U.S.A.
-  REVEAL IMAGING®

