

DANYA by AMERICAN OLEAN



Color Availability



***Basin**







***Cove**







***Stream**

SPECIFICATIONS

SIZES

			THICKNESS	SQ.FT/ CARTON	PIECES/ CARTON
	18 x 18 Floor Tile	17-3/4" x 17-3/4" (45.20 cm x 45.20 cm)	5/16"	17.60	8
	12 x 24 Floor Tile Q	11-13/16" x 23-13/16" (30.00 cm x 60.48 cm)	5/16"	15.60	8
	12 x 12 Floor Tile Q	11-13/16" x 11-13/16" (30.00 cm x 30.00 cm)	5/16"	14.55	15
	3 x 3 Mosaic p n	12" x 24" Sheet (30.48 cm x 60.96 cm)	1/4"	24.00	12

TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose p	3 x 12	P-43C9	22
	Cove Base p	6 x 12	S-36C9T	22
	Cove Base Outcorner p	6 x 1	SC-36C9T	15
	Wall Bullnose Corner p	3 x 3	SN-4310	32

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position. Cove base and cove corner trim are suitable for non-freezing climates only.
 Q Modular sizes p Ceramic body n Dot-mounted

APPLICATIONS


	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	● *
Wet & Level – Interior Floor	≥ 0.42	● *
Shower Floors (Residential or Light Commercial)	≥ 0.42	● **
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	● *
Pool Linings	N/A	● **

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

USAGE

FLOORS	WALLS	COUNTERTOPS
F	W	C

INSTALLATION & PRICING

RECOMMENDED GROUT JOINT:	SHADE VARIATION
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern. When multiple sizes are installed in a modular pattern, please specify same size caliber at time of order.) Wall: 1/16" Mosaic: 1/8" RELATIVE PRICING: Medium to Low	 HIGH (V3)




PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT	WALL RESULT	MOSAIC RESULT
Water Absorption	C373	< 0.5%	< 20.0%	< 3.0%
Breaking Strength	C648	> 275 lbs.	120 - 230 lbs.	> 250 lbs.
Scratch Hardness	MOHS	8.0	4.0 - 6.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant
Abrasion Resistance	C1027	3 (DY03, DY04) 4 (DY01, DY02)	N/A	3 (DY03, DY04) 4 (DY01, DY02)

APPLICATION NOTES:

Floor tile suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed. Wall and mosaic tile suitable for exterior applications in non-freezing climates, when proper installation methods are followed.
 * Wall tile not suitable for this application
 ** Mosaic tile only

FEATURES:

-  PRE-CONSUMER RECYCLED CONTENT
-  MADE IN THE U.S.A.
-  REVEAL IMAGING®

