HAWTHORNE by MARAZZI

Color Availability

English Taupe Flat

***Refined White Flat**

Scholarly Gray Flat

English Taupe Bevel

***Refined White Bevel**

Scholarly Gray Bevel

THE MASONRY CENTER
SURFACES AND SERVICE REINVENTED

Website: masonrycenter.com Phone Number: 800.284.9398

SPECIFICATIONS

SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
	***8 x 24 Flat** Wall Tile (8" x 24") (20.34 cm x 61.03 cm)	3/8"	13.3	10
	***8 x 24 Bevel** Wall Tile (8" x 24") (20.34 cm x 61.03 cm)	3/8"	13.3	10
	10 x 14 Flat Wall Tile (9-13/16" x 13-15/16") (24.99 cm x 35.40 cm)	5/16"	14.25	15
	10 x 14 Bevel Wall Tile (9-13/16" x 13-15/16") (24.99 cm x 35.40 cm)	3/8"	12.38	13
	***4 x 12 Flat** Wall Tile (4-1/4" x 12-7/8") (10.91 cm x 32.77 cm)	5/16"	10.64	28
	***4 x 12 Bevel** Wall Tile (4-1/4" x 12-7/8") (10.91 cm x 32.77 cm)	3/8"	7.98	21

TRIM

Description	Number	Size	Shape
Jolly	S-1/212J	1/2 x 12	

INSTALLATION

Grout Joint Recommendation	Shade Variation
8 x 24: 1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%) 10 x 14: 1/16" 4 x 12: 1/16" (when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%)	V1 Low Variation

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of Ó0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTestÊ , visit marazzitile.com/DCOF.

PERFORMANCE CHARACTERISTICS

	ASTM#	Wall Result
Water Absorption	C373	< 20%
Breaking Strength	C648	120-230 lbs
Scratch Hardness	MOHS	4.0 - 6.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

USAGE

Floors	Walls	Countertops
	W	

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

FEATURES

POST-CONSUMER RECYCLED MATERIALS

PRE-CONSUMER RECYCLED MATERIALS

MADE IN THE U.S.A.

REVEAL IMAGINGÈ

CERTIFIED PORCELAIN TILE

All or select items within this series meet the requirements for these qualifications.
Vist: marazzitile.com for more information