

IMPRESA by AMERICAN OLEAN



Color Availability




***Charcoal**



***Light Grey**

SPECIFICATIONS

SIZES

			THICKNESS	SQ.FT/ CARTON	PIECES/ CARTON
	12 x 24 Floor Tile	11-9/16" x 23-3/8" (29.40 cm x 59.30 cm)	3/8"	15.04	8
	4 x 12 Wall Tile	4-1/4" x 12-7/8" (10.91 cm x 32.77 cm)	5/16"	10.64	28
	2 x 2 Mosaic n	12" x 24" Sheet (30.48 cm x 60.96 cm Sheet)	1/4"	24.00	12

n Dot-mounted

TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose	3 x 12	P-43C9	22
	12" Jolly	1/2 x 12	S1/212J	6 Cards

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	● *
Wet & Level – Interior Floor	≥ 0.42	● **
Shower Floors (Residential or Light Commercial)	≥ 0.42	● **
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	● *
Pool Linings	N/A	● **

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

USAGE

FLOORS	WALLS	COUNTERTOPS
F	W	C

INSTALLATION & PRICING

RECOMMENDED GROUT JOINT:	SHADE VARIATION
<p>Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)</p> <p>Wall: 1/16" (When rectangular size is installed in a staggered brick-joint pattern, overlap should not exceed 33%.)</p> <p>Mosaic: 1/8"</p> <p>RELATIVE PRICING: Low to Medium</p>	 <p>HIGH (V3)</p>

PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT	WALL RESULT	MOSAIC RESULT
Water Absorption	C373	< 7.0%	< 20.0%	< 3.0%
Breaking Strength	C648	> 250 lbs.	120-230 lbs.	> 250 lbs.
Scratch Hardness	MOHS	7.0	4.0-6.0	7.0
Chemical Resistance	C650	Resistant	Resistant	Resistant
Abrasion Resistance	C1027	3	N/A	3

APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.. * Wall tile not suitable for this application.

* Wall tile not suitable for this application

** Mosaic tile only

FEATURES:

 PRE-CONSUMER RECYCLED CONTENT

 MADE IN THE U.S.A.

 REVEAL IMAGING®



CERTIFIED
PORCELAIN
TILE
0.5% or less water absorption

ZEROTOX
Healthy Homes | Healthy Planet

