


# **Kitchen Faucet Installation**

#### INSTALLATION MANUAL Tools You Will Need:







Adjustable Wrench

**Parts List** 

Hexagon wrench


Philips Screwdriver

#### **Before the Installation**

- 1. Check the package and confirm all parts are included. If any part is missing or damaged, please contact us.
- 2. Do not disassemble the main body, as it has been installed & commissioned correctly & precisely before leaving the factory.
- 3. Shut off the main water supply prior to beginning installation.
- 4. Do flush the water supply lines to remove any dirt and debris before installation (IMPORTANT).
- 5. Make sure to connect the hot/cold inlet pipe correctly. If standing in front, connect hot water pipe to the left and cold water pipe to the right.
- 6. After the installation, check for leaks and make sure every joint is safely sealed.


#### Cleaning and Maintenance

- 1. Rinse with clean water and dry with a soft cloth.
- 2. Do not use any detergent, acid, polisher, abrasives, or harsh cleaners.
- 3. Do not use cloth with a coarse surface.




Part	Name	Quantity
Α	faucet body	1
В	decor washer	1
С	O-ring	1
D	rubber washer	1
E	metal washer	1
F	mounting nut	1
G	cold/hot waterline	2
Н	spacer	2


### **Installation Guide**




Remove the rubber washer (D), metal washer (E) and mounting nut (F) from the threaded pipe (B) and fit the decor washer (B) and O-ring (C) to the bottom of the faucet body (A).




2. Screw up the cold/hot waterlines (G) to the corresponding holes under the bottom of the faucet body (A). Insert the spacers (H) to the other ends of the cold/hot waterlines (G).



Insert the faucet body (A) and the waterlines (G) into the hole on the countertop.



Secure back the rubber washer (D),
metal washer (E) and mounting nut (F).
Adjust the position of the faucet body
(A) to make sure it level and straight.
Tighten the mounting nut (G).



 Screw up the waterlines (G) to the corresponding water supply outlets with adjustable wrench (not included).

## **Troubleshooting**

	Problem	Possible Cause	Corrective Action
	Water does not shut off completely.	O-ring is not seated correctly or worn.     Cartridge may be defective.	Reseat or replace O-ring.     Replace cartridge.
	Leaks at waterline connection.	Worn or broken washer.     Faucet body may be defective.	Replace washer.     Replace faucet (contact us for the replacement).
	Leaks from handle.	Cartridge may come loose.     Cartridge may be defective.	Reseat cartridge tight.     Replace cartridge.
	Leaks at hose connection.	Hose connection is loose.	Tighten hose.     Replace hose.
3	Leaks at shower valve	Connection may come loose or not sealed completely.	Check connections.
	connection.	Defective shower valve inlet or outlet connector.	2. Replace valve body.
	Diverter knob does not work.	Diverter cartridge may be defective.	Replace cartridge.
	LED light does not Light or noisy LED showerhead.	Defective LED generator.	<ol> <li>Replace LED spray head (for kitchen faucet).</li> <li>Replace LED threaded pipe (for seperate faucet spout).</li> <li>Replace LED generator (for others).</li> </ol>
	Low flow.	Check for water pressure problems.     Aerator may be dirty or clogged.	<ol> <li>Clean or replace the aerator.</li> <li>Remove waterflow restrictor if available.</li> <li>Install booster or pump (if applicable).</li> </ol>