VAR TECH®
Quality • Reliability • Economy

D.C. POWER SUPPLY, S.M.P.S. BASED

MODEL : 3003 S U

VERY COMPACT
& LIGHT WEIGHT.
WITH 2A USB OUTPUT.

SPECIFICATIONS

O/P VOLTAGE = 0 ~ 30 V
O/P CURRENT = 0 ~ 3 A
USB = 2 A
TWO 4 Digits L.E.D. DPMs, FOR 'V' & 'I'
Display Accuracy : ± (0.5% + 5 Digits)
LOAD REGULATION : CV : ≤ 0.05% + 3 mV
CC : ≤ 0.5% + 10 mA
LINE REGULATION : CV : ≤ 0.1% + 3 mV
CC : ≤ 0.2% + 3 mA
Ripple & Noise : CV ; ≤ 10 mV rms
CC ; ≤ 20 mA rms
ENVIRONMENTAL : 0 ~ + 40 ^{0}C, R.H. < 90%.
OPERATING VOLTAGE : 220 ~ 240 V AC, 50 Hz
PROTECTION : C.C. & Short Circuit With Current Limit
Dimension & Weight : 78 (W) x 161 (H) x 255 (D) mm,
About 1.1 Kgs.

* * *

MODEL : 3005 S

VERY COMPACT & LIGHT WEIGHT.
WITH NEW ERA DESIGN OF
FINE & COARSE
COMBINED CONTROL.
CONTROLS LOCKING FACILITY.

SPECIFICATIONS

O/P VOLTAGE = 0 ~ 30 V
O/P CURRENT = 0 ~ 5 A
TWO 4 Digits L.E.D. DPMs, FOR 'V' & 'I'
Display Accuracy : ± (0.5% + 5 Digits)
LOAD REGULATION : CV : ≤ 0.01% + 5 mV
CC : ≤ 0.2% + 5 mA
LINE REGULATION : CV : ≤ 0.1% + 1 mV
CC : ≤ 0.2% + 1 mA
Ripple & Noise : CV ; ≤ 3 mV rms
CC ; ≤ 3 mA rms
ENVIRONMENTAL : 0 ~ + 40 ^{0}C, R.H. < 90%.
OPERATING VOLTAGE : 220 ~ 240 V AC, 50 Hz
PROTECTION : C.C. & Short Circuit With Current Limit
Dimension & Weight : 78 (W) x 161 (H) x 255 (D) mm,
About 1.4 Kgs.

* * *

** All Specifications & appearances are subject to change without prior notice.*