

Model : PPS - 3606 S

Single Output High Precision
Programmable D.C. Power Supply –
Switching type - having High Accuracy.
High Resolution : 10 mV / 1 mA
High Stability, Low Ripple & Noise
Cooling Fan ensures Low Heat & Noise

- ★ Over Voltage, Over Current & Over Temperature Protections
- ★ Five 4 Digits L.E.D., Displays for Vset, Iset, Vout, Iout & W.
 - ★ High speed Rotary Dial
 - ★ Front Panel Lock Facility
 - ★ Output ON/OFF function
 - ★ 6 Memories (M1 to M6)
 - ★ List Mode Operation
 - ★ Beeper & Delay Time
 - ★ USB Interface (Optional)



SPECIFICATIONS

Output	0 ~ 36 V / 0 ~ 6 A
Line & Load Regulation	≤ 0.2% FS
Ripple & Noise	≤ 0.5% FS Vrms
Setting & Display Accuracy	± (0.1% + 2 digits) : 25 (±5) °C
Power Display	0.001 W - 0.01 W – 0.1 W Auto Resolution
Other Features	High speed Rotary Dial, Front Panel Lock Facility, Beeper, Output On/Off function, Delay Time (9999 Sec.) & 6
Protection	Over Voltage, Over Current. & Over Temperature.
Power Source	220 V (±10%), 50 Hz
Weight & Dimensions	125 mm (W) × 160 mm (H) × 260 mm (D). Approx. 2 Kg.
Accessories	Power Cord, Operation Manual & USB Cable (Optional).

* All Specifications & appearances are subject to change without prior notice.