

DIGITAL CLAMP MULTIMETER

Model : V 2101+

3 5/6 DIGITS (6000 Counts)

**60 / 600 A / 1000 A AC/DC
1500 VDC & 1000 VAC**

**True RMS, Auto Ranging
Cap., Freq., & Temp.
Measurements
In Rush Current & V.F.C.
Data Hold, B/L & Torch
Continuity & Diode Test
A.P.O., NCV & Live Wire Test
Low Imp. ACV Meas. (TRMS)**



SPECIFICATIONS

| | | |
|---------------------------------------|----------------|--|
| DC Voltage | Range | 600 mV, 6 V, 60 V, 600 V, 1500 V |
| | Basic Accuracy | ± (0.5 % reading + 7 digits) |
| AC Voltage (True RMS) | Range | 6 V, 60 V, 600 V, 1000 V |
| | Basic Accuracy | ± (1 % rdg. + 10 digits) |
| AC Current & DC Current | Range | 60 A / 600 A / 1000 A (True RMS ACA) |
| | Accuracy | ± (4 % rdg. + 10 digits) |
| Low impedance AC V Measurement (TRMS) | Range | 6 V, 60 V, 300 V |
| | Basic Accuracy | ± (1% rdg. + 10 digits) Input impedance : ≤3 KΩ. |
| Resistance | Range | 600 Ω, 6 K Ω, 60 K Ω, 600 K Ω, 6 M Ω, 60 M Ω |
| | Basic Accuracy | ± (1% rdg. + 5 digits) |
| Capacitance Test (Auto Ranging) | | 1 nF, 10 nF, 100 nF, 1 μF, 10 μF, 100 μF, 1 mF & 10 mF. |
| Frequency / D. Cycle (Auto Ranging) | | 10 Hz ~ 10 MHz. Protection Upto 250 V ONLY. |
| Temperature Measurement | | -20 ~ 1000 °C (-4 ~ 1832 °F). |
| Other Facilities / Features | | NCV & Live Wire Test, Diode Test, Continuity Test, Back Light, Torch, Auto Power Off, Low Batt. Indication, Data Hold, REL, In Rush Current & V.F.C. |
| Accessories Supplied | | Test Leads - Pair, Temp., Probe, Carrying Pouch, User Manual & Battery (Installed / Kept Aside) - OPTIONAL. |
| Dimension & Weight | | 230 x 75 x 40 mm & Approx. 315 gms. (Incl. Batt.). |