

EXIDE[®]

Pushing the boundaries.

Battery Solutions for
Motorbike & Sport.



**ENERGIZING
A NEW
WORLD**

Creating the future – the Exide way:



Innovation



Reliability



Sustainability



High Performance

exidegroup.com

EXIDE[®]
TECHNOLOGIES

The world is changing. That's why we are energizing a new world.

For Exide, now is the time to release new energies to move even more into the future. Our new alignment “**Energizing a new world**” is designed to convey this aspiration. We want to bring change to life, face challenges together with our partners, and develop solutions for today and tomorrow. **Let's create the future – the Exide way:**



Innovation is the engine of technology leadership. That's why we are constantly evolving, remaining self-critical, and continue to inspire our customers.



Sustainability is an important part of our responsibility. That's why we rely on renewable energies and intelligent recycling concepts.



Reliability defines our business. This applies to our products as well as our innovative development, services, and partnerships. Our responsibility does not end with our products, but starts right there.



High Performance is the standard we set for our products and services. All our solutions are best of class. This means our customers are optimally equipped for any task.

Longing is always a good engine. Supported by our batteries, anything is possible.



Enjoying the freedom on the roads, the horizon in front of you and knowing that the only goal is to have a good time. Now that's even easier with Exide's high-performance batteries. The most advanced components and materials ensure long reliability and durability. Best of all, they're perfect for motorcycles, scooters, jet skis, and a host of other vehicles.

Before you start – a few important battery tips from our experts.



Shelf storage

- Store in a cool (0–25°C), dry, and well-ventilated environment free from sparks and frost.
- For our GEL and AGM Ready ranges, manage stock rotation and check voltage regularly.



Regular maintenance during use

- Check the voltage regularly.
- Check cables, clamps, and the rest of the battery for obvious signs of damage or loose connections.
- Clean terminals and connectors and apply pole grease as necessary.
- For Conventional, check the electrolyte level and refill water when necessary. And make sure the exhaust outlet is free of kinks and clogs.



Long resting period between uses

- Disconnect electrical equipment and fully charge the battery.
- Check the voltage every month for Conventional and every 3 months for AGM, AGM Ready, and GEL batteries.

There are many challenges.

We have the right battery for each.



Feature	Li-Ion	GEL	AGM Ready	AGM	Conventional
Performance	Ultra lightweight, extreme cycle life, highly vibration resistant, very low self-discharge	Superior capacity, maximum safety, maximum cycle life, highly vibration resistant, deep-discharge protection	Superior power, ultra safe features, extended cycle life, highly vibration resistant	Superior power, great safety features, extended cycle life, vibration resistance	Good power, good cycle life
Recommended vehicle parc	Ultimate choice for sport bikes	Ideal for premium vehicles with built-in or add-on electrical equipment	Ideal for high-class motorcycles, powersport, and off-road vehicles	Fits most applications	Suitable for standard power needs
Recommended applications					
Maintenance					Could require water refilling
Inclination level					Upright mounting only
Hermetic seal					
Ready to use				Initial filling required	Initial filling required
Acid pack included	No acid	No initial filling	No initial filling	+	+
Technology	Lithium-ion	Gel	AGM charged	AGM dry charged	Flooded dry charged

* Becomes sealed after initial filling

Exide Li-Ion

Exide is speeding up your passion. The Li-Ion Motorbike & Sport battery range is for those who demand the ultimate riding experience. The battery's ultra lightweight design reduces the overall weight of your bike, enabling faster acceleration and better performance. It has very low self-discharge, ideal for starting your engine after long periods off the road. Exide Li-Ion can be installed in multiple positions and comes with first-class safety features.



Powerful benefits:

- Ultra lightweight – up to 80% lighter than lead-acid batteries
- Very low self-discharge – long shelf life and perfect for seasonal use
- Super-fast recharging
- State-of-charge indicator for regular checks at one glance
- Extreme cycle life – more than 2.000 cycles
- Covers the majority of parc – spacers included for more fitment options
- Ready to use and maintenance free – just install and forget
- First-class safety features
- Multi-position mounting – even upside down



Good to know!

Li-Ion batteries require special chargers with charging profiles adapted for this technology. Don't use a lead-acid battery charger, it will damage the battery. Exide 12/2 Li-Ion charger is created specifically for Exide Li-Ion Motorbike & Sport batteries, bringing extended battery service life and maximum safety.

Exide GEL

Exide GEL is the ultimate choice for any premium motorcycle, scooter, or power-sports vehicle. It is designed to give you maximum comfort on the road and easily handles power-hungry devices such as audio, GPS, additional lighting, and heating systems. GEL is completely leak-proof, spill-proof, and highly resistant to vibration. Deep-discharge protection and very low self-discharge make it perfect for long storage periods and seasonal use. **Gel technology was originally invented by Exide, and is now the gold standard in motorcycle batteries.**



Impressive features:



- Brilliant performance even when partially discharged, prolonging cycle life



- Maximum safety and highly vibration resistant – easily handles rough road conditions



- Ready to use, no initial acid filling



- Maintenance free – no water refilling



- Very low self-discharge – perfect for seasonal use
- Deep-discharge protection – store for up to 24 months without loss in cycle life



- Latest original equipment technology
- Made in Europe



High performance components and materials.

Superior valves

cell sealing and ultra pure battery materials for low self-discharge and extra security

The original Gel technology

invented by Exide. The acid is fixed in a gel form with higher electrolyte reserve. Thus the battery is more heat tolerant, less prone to irreversible sulphation, and has a longer cycle life

Positive plate


Framed grid with high-tech and high-purity alloy for superior robustness

Negative plate

Framed grid with high-tech and high purity alloy for superior robustness

Extremely robust premium separator

with exceptional porosity, oxidation resistance, and mechanical stability to ensure maximum conductivity and battery life



Good to know!










As the original inventor of gel technology back in 1958, Exide supplies original equipment gel batteries for BMW motorcycles. Exide GEL is the perfect upgrade choice for vehicles with demanding electrical equipment such as audio, GPS, heating systems, and additional lights.

Exide AGM Ready

Exide AGM Ready provides maximum power and is entirely “install and forget”, just like you always wanted. No initial acid filling or water topping required! The battery is leak-proof, spill-proof, and highly vibration-resistant, ideal for powersport, all-terrain, and extreme uses. Exide AGM Ready offers incredible performance and exceptional starting power in all weather conditions, making it also ideal for jet skis.

Spare
ORIGINAL
Part

Impressive features:

-  • Ready to use, no initial acid filling
-  • Maximum power
-  • Extended cycle life
-  • Ideal for cold weather
-  • Ultra safe and highly vibration resistant – ideal for rough road conditions
-  • Maintenance free – no water refilling
-  • Low self-discharge – suitable for seasonal use
-  • Original equipment experience inside
-  • Largest range in the market – covering 80% of the parc



Exide AGM

Exide AGM offers impressive reliability and lifespan, easily withstanding cold winters and other harsh conditions. The battery is completely maintenance free, only requiring initial acid filling to get you started. It features AGM technology, and is ideal for the majority of applications, including high-end scooters.


Features:

-  • Extended cycle life
-  • Ideal for seasonal use and cold weather
-  • Great safety features and vibration resistant
-  • Maintenance free – no water refilling
-  • 6-bottle acid pack included for initial filling
-  • Easy stock handling – no recharge required before acid filling
-  • Wide range covering 90% of the parc

Exide Conventional

Exide Conventional batteries are designed for entry-level and older vehicles with basic power needs. They are also ideal for small lawn mowers and garden machines.

Features:

-  • Acid pack included for initial filling
- Easy stocking and handling – no recharge required before initial acid filling
- A great variety of battery types, including 6V



For detailed filling instructions please scan QR code!

Be sure to fully respect the filling instructions given in the manual or accessible via the QR to ensure product performance and quality. Batteries not properly filled will invalidate the warranty.




New European legislation prohibiting sale of battery electrolyte to end users.

Since February 2, 2021, a new European Regulation (Regulation EU 2019/1148) bans the sale of battery electrolyte to end users since it contains sulphuric acid. Retailers are no longer allowed to supply end users with separate sulphuric acid packs or bottles for the activation of dry, pre-charged batteries. Motorcycle batteries already factory filled, like Exide GEL and Exide AGM Ready, are not affected by the Regulation.

Exide AGM (Dry) and Conventional batteries therefore must be filled and prepared by retailers before being given to the end user.

Trust in our experience.

To experience the world on your own.



Smart tools and accessories.

Motorcycles and powersport vehicles often go extended periods without being used, but this does not have to be a problem. Follow the tips below and your engine will start just fine, even after a long winter stored away. Exide has a range of chargers and other added-value tools designed for the home or workshop. With the right maintenance, your battery will last even longer.

Battery Charger

Exide chargers can be used for a wide range of vehicle and lead-acid battery types. They are fully automatic and have a built-in temperature compensator, which is especially useful in colder climates. The chargers ensure optimum charging, can be used for batteries from 1 Ah up to 300 Ah, and have integrated safety functions to identify if anything is wrong with the battery.



Charging Tips

- Batteries should be charged off-vehicle if the voltage drops below 12.45 volts (or 6.2 volts for 6V batteries)
- Use the specially developed Exide motorcycle charger for best results
- Avoid fire or flare and ensure good ventilation during and after charging
- Allow the battery to rest for at least 12 hours after charging

QR Code

Scan the QR code on any Exide Motorbike & Sport battery packaging to access more information such as product features, battery tips and tricks, fun biking links, Exide Battery Finder app, and much more.




Battery Finder App

Search by bike model to quickly find the right battery on the go.



Battery Finder Online

The new online battery finder features a modern interface and all-new user experience. It supports battery selection and fitting for the most comprehensive range of vehicle types such as cars, buses, trucks, and motorcycles – plus, for the first time, construction and agricultural vehicles, ATVs, snow mobiles, and jet skis. exidegroup.com/eu/en/battery-finder



Exide motorcycle batteries type list

Exide	Performance		Dimensions & weight					Technical characteristics				
	Code	Energy (Wh)	Current (A)	L (mm)	W (mm)	H (mm)	Weight (kg)	Fits	Spacer quantity & size (LxWxH) (mm)	Polarity	Terminal type	
Li-Ion												
ELTZ5S	24	120	113	70	85	0.5	YTZ5S, YTX4L-BS, YTX5L-BS	2 spacers of 50x20x20				
ELTZ7S	28.8	150	113	70	85	0.6	YTZ7S, YTX7L-BS	4 spacers of 50x20x20				
ELTX9	36	180	150	87	105	0.7	YTX7A-BS, YTX9-BS, YTR9-BS	No spacer				
ELT9B	36	190	150	65	92	0.7	YT7B-BS, YT9B-BS	4 spacers of 50x20x7				
ELTX12	42	210	150	87	93	0.8	YTX12-BS, YTX12A-BS, YB12B-B2	2 spacers of 86x20x25. 2 spacers of 86x20x12				
ELTZ10S	48	230	150	87	93	0.8	YTZ10S	No spacer				
ELTX14H	48	240	150	87	93	0.9	YTX14H-BS, KMX14-BS, YTX14-BS	4 spacers of 86x20x25				
ELT12B	60	260	150	65	130	0.9	YT12B-BS, YT14B-BS, YB16AL-A2	10 spacers of 50x20x7, 2 spacers of 50x20x35				
ELTZ14S	60	290	150	87	93	1	YTZ12S, YTZ14S	2 spacers of 86x20x17				
ELTX20H	84	380	175	87	130	1.3	GYZ20H, YTX20H-BS, YTX20HLBS, YTX20-BS, YB16-B-CX, YB16-B, YB16C-B, YB18-A, Y50-N18A-A	4 spacers of 86x20x12. 2 spacers of 86x20x17				

Exide	Performance		Dimensions			Technical characteristics				
	Code	Capacity (10h) Ah	CCA A (EN)	L (mm)	W (mm)	H (mm)	Polarity	Terminal type		
GEL 12V										
GEL12-14	14 (20h)	150	150	87	145					
GEL12-16	16 (20h)	100	180	75	165					
GEL12-19	19 (20h)	170	185	80	170					
GEL12-30	30 (20h)	180	197	132	186					
AGM Ready 12V										
AGM12-4	3	50	113	70	85					
AGM12-5	4	70	113	70	105					
AGM12-6	6	90	150	87	93					
AGM12-7	6	100	113	70	105					
AGM12-7F	7	85	150	65	100			4.8		
AGM12-7.5	8	120	150	87	105					
AGM12-8	8.6	145	150	87	93					
AGM12-9	9	120	135	75	139					
AGM12-10	10	150	150	87	130					
AGM12-11	11.2	205	150	88	110					
AGM12-12	12	200	150	90	145					
AGM12-12F	12	150	150	100	100			4.8		
AGM12-12M	12	200	150	90	145					
AGM12-14	12	210	134	89	164					
AGM12-16	16	170	150	90	160					
AGM12-19	18	270	175	87	155					
AGM12-19.1	18	270	175	87	155					
AGM12-18	18	250	181	77	167					
AGM12-23	21	350	205	86	162					
AGM12-31	30	430	166	126	175					
AGM 12V										
ET4B-BS	2.3	35	113	38	85					
ETR4A-BS	2.3	35	113	48	85					
ETX4L-BS	3	50	113	70	85					
ETX5L-BS	4	70	113	70	105					
ETX7A-BS	6	90	150	87	93					
ETX7L-BS	6	100	113	70	130					
ETZ7-BS	6	100	113	70	105					
ET7B-BS	6.5	85	150	65	93					
ET9B-BS	8	110	150	70	105					
ETX9-BS	8	120	150	87	105					
ETZ10-BS	8.6	145	150	87	93					
ETX9C-BS	9	120	135	75	139					
ET12A-BS	9.5	130	150	87	105					
ET12B-BS	10	160	150	70	130					
ETX12-BS	10	150	150	87	130					
ETZ14-BS	11.2	205	150	87	110					
ET14B-BS	12	190	150	70	145					
ETX14-BS	12	200	150	87	145					
ETX14L-BS	12	200	150	87	145					
ETX14AH-BS	12	210	134	89	164					
ETX14AHL-BS	12	210	134	89	164					
ETX16-BS	14	215	150	87	161					
ETX20H-BS	18	270	175	87	155					
ETX20HL-BS	18	270	175	87	155					
ETX20CH-BS	18	230	150	87	161					
ETX24HL-BS	21	350	205	87	162					

Exide	Performance		Dimensions			Technical characteristics				
	Code	Capacity (10h) Ah	CCA A (EN)	L (mm)	W (mm)	H (mm)	Polarity	Terminal type		
Conventional 6V										
6N4B-2A	4	35	101	47	95			Leads		
6N6-3B-1	6	40	98	56	110					
6N11A-1B	11	95	121	59	131					
6N12A-2D	12	100	155	56	115					
Conventional 12V										
EB4L-B	4	50	120	70	92					
12N5-3B	5	40	120	60	130					
EB5L-B	5	65	120	60	130					
12N5,5-3B	5.5	45	135	60	130					
12N7-3B	7	75	135	75	133					
EB7C-A	8	90	130	90	114					
EB7-A	8	85	135	75	133					
EB7L-B	8	85	135	75	133					
12N9-3B	9	85	135	75	139					
12N9-4B-1	9	85	135	75	139					
EB9-B	9	100	135	75	139					
EB10L-A2	11	130	135	90	145					
EB10L-B	11	130	135	90	145					
EB10L-B2	11	130	135	90	145					
12N12A-4A-1	12	115	134	80	160					
EB12A-A	12	165	134	80	160					
EB12AL-A	12	165	134	80	160					
EB12AL-A2	12	165	134	80	160					
12N14-3A	14	130	134	89	166					
EB14-A2	14	145	134	89	166					
EB14-B2	14	145	134	89	166					
EB14L-A2	14	145	134	89	166					
EB14L-B2	14	145	134	89	166					
EB16AL-A2	16	175	205	70	162					
EB18L-A	18	190	180	90	162					
EB16-B	19	190	175	100	155					
EB16CL-B	19	190	175	100	175					
EB16L-B	19	190	175	100	155					
12Y16A-3A	20	210	185	81	170					
E50-N18L-A	20	260	205	90	162					
E50-N18L-A3	20	260	205	90	162					
12N24-3										

Energy that goes beyond.



- Transportation plant
- Industrial plant
- R&D facility
- Recycling
- Global HQ
- Principle sales offices
+ sales offices and distribution centers across the world



Subject to alteration

XXXXXXXXXXXXXXXXXX

<p>All manufacturing plants ISO 9001 certified</p>	<p>All automotive plants IATF 16949 certified</p>	<p>All manufacturing plants ISO 14001 certified</p>	<p>All manufacturing plants ISO 50001 certified</p>	<p>Most manufacturing plants ISO 45001 certified</p>
---	--	--	--	---

**ENERGIZING
A NEW
WORLD**

EXIDE[®]
TECHNOLOGIES