
SUPERIOR DEEP CYCLE AGM BATTERY


LDC8-180-GC8 (8V182Ah)

















Note: Terminal Torque Values in-lb(Nm):176-203(20-23)

CHARACTERISTICS

Item		Specifications
Voltage		8V
Dimension	Length	260mm (10.2inches)
	Width	180mm (7.09inches)
	Container Height	252mm (9.92inches)
	Total Height	274mm (10.8inches)
Approx Weight		30.8kg (67.9lbs)
Terminal		DT(5/16")
Container Material		ABS
Reserve Capacity	25A	365min
	56A	155min
Capacity	20HR	182Ah
	10HR	170Ah
	5HR	153Ah
Operating Temp. Range	Discharge	-20~55°C (-4~131°F)
	Charge	0~40°C (32~104°F)
	Storage	-15~40°C (5~104°F)

APPLICATIONS

- · Electric vehicle
- · Golf cart
- · Sightseeing
- · Cleaning equipment
- AWP
- Mobility

















SUPERIOR DEEP CYCLE AGM BATTERY

LDC8-180-GC8 (8V182Ah)



GENERAL FEATURES

Stable initial capacity

- · PAM/NAM amount optimization
- · 4BS crystal paste mixing & curing technology
- · Double layer separator technology
- · Improved design electrolyte S.G.

Less water loss

- · PAM/NAM amount optimization
- · New PAM/NAM recipe introduced
- · Rare earth alloy

Solve NAM sulphation

- · Carbon boost technology
- · Pre-sulfate technology

Improved PSoC cycling

- · Carbon boost technology
- · Mix carbon boost technology
- Targeting for higher level through carbon technology

Delay PAM softening and shedding


- · Plate assembly pressure re-engineering
- · 4BS crystal paste mixing & curing technology
- · Higher paste density


Optimize electrolyte stratification


· Introduce AGM-GEL technology


Excellent deep cycle performance

- · Plate assembly pressure re-engineering
- · New PAM/NAM recipe introduced
- · Gel electrolyte technology
- · Rare earth alloy
- · Double layer separator technology
- · Lower acid filling temperature









Leoch International Technology Ltd.

www.leoch.com

Leoch Batteries Pte Ltd

m www.leoch.sg

www.leochamericas.com

Leoch Battery Corporation

Leoch Europe S.A.

www.leoch.eu