

# ParkSafe - Product Specification Sheet



## Front Sensor Kit with Angled Collars

Set of four front parking sensors with LED Display to alert driver of obstacles that may be in their blind spots when maneuvering. Set includes angled collars to fit varying angles of installation.

Kits available in Gloss or Matt Black, Silver or White

### Key Specification:

18.5mm Paintable Sensors  
Angled heads; 6° 10° & 13°  
LED Display  
Sensor height adjustable by Control port  
Power: 12/24 V DC, 20-200mA  
Power Cable: 0.8m  
Sensor Cable: 2.5m  
LED Display cable: 6m  
Detection Range 0.2 - 1.5m

### Additional Specification:

Tow bar Ignore Function  
Frequency: 40KHz  
Working Temp. -30°C ~ +70°C



PS746



Date Created:

08/11/2022

Specification Sheet  
Number:

JAY10010118

Version:

V1.0

Box Dimensions (WxDxH):

250mm x 180mm x 60mm

### Approvals & Certifications:

E Mark, CE, UKCA

E13 10R-03-13369

### Box Contents:

4 x parking sensor heads, 4 x angled collars- 6° 10° & 13° (4 of each), 4 x parking sensor cables, 1 x control box, 1 x power lead, 1 x LED Display, Velcro pad, Tact switch, cable ties, user manual.