

SupaSoft insulation offers a safe, sustainable and cost-effective way to insulate your loft.

SupaSoft insulation contains 100% recycled polyester and is made almost entirely from recycled plastic bottles.

SupaSoft insulation contains no harmful chemicals or binders and is completely safe to handle

SupaSoft insulation is long-lasting and safe to handle. What's more, energy savings mean the insulation pays for itself in a just a few years

SupaSoft insulation can be used to insulate between and over rafters or simply laid on top of existing insulation to improve overall insulation performance.

#### **Key Facts**

- Width (mm) 390, 590
- ① Thickness (mm) 50 & 100
- M Thermal conductivity 0.040 W/mK
- Wapour open
- Made in the UK
- 8 >95% recycled content
- Manufactured to ISO 9001 & 14001
- (8) Can be recycled

#### Standards

Manufactured to ISO 9001

#### Environmental

GWP (A1-A3) total: 1.27 kgCO<sub>2</sub>e R1

• Recycled Content: >95%

Recyclable: Yes

EPD registration no. S-P-04469

• EPD valid to 31/10/26

#### **Applications**

- Roofs Loft
- Floors All levels
- Other can be used in walls and between rafters

#### Why Insulate with SupaSoft insulation?

Insulating a property will significantly reduce the amount of energy lost from the building envelope, reducing energy consumption and carbon dioxide released to the atmosphere.

#### Affordable

Insulating with SupaSoft insulation is a very cost-effective alternative to glass or other mineral insulation. What's more, the energy it saves means SupaSoft insulation quickly pays for itself.

#### Long Lasting

SupaSoft insulation contains a lofting agent to maintain durability and is designed to last the life of the building in which it is installed.

#### **Quality Assured**

SupaSoft insulation is manufactured and supplied in accordance with ISO 9001 quality management systems.

#### Sustainable

SupaSoft insulation can reduce CO<sub>2</sub> emissions by many tonnes over the lifetime of use. What's more, SupaSoft insulation is made from recycled plastic bottles and has a recycled content of more than 95%.

#### Vapour Open

SupaSoft insulation is an open non-woven material that allows water vapour to pass through the insulation.

#### Safe

SupaSoft insulation is safe to handle and can be recycled or safely disposed of at the end of its life.



#### **Specifications**

#### Performance

- Thermal Conductivity: 0.040 Wm<sup>-1</sup>K<sup>-1</sup>
- Water Absorption (@100% RH): 0% w/w
- Specific Heat Capacity: 1000 Jkg<sup>-1</sup>K<sup>-1</sup>
- Vapour Resistivity: 5 MN·s·g<sup>-1</sup>m<sup>-1</sup>
- EN11925-2 Reaction to Fire: Pass
- Fire Classification: EuroClass E
- Flammability to BS 5803-4: Pass
- Smoulder resistance to BS 5803-4: Pass
- Dimensional stability to EN 1604: Pass
- Can be used to achieve airborne sound reduction of  $R_w$  40dB.

#### Sizes

- Thickness 50 & 100 mm
- Width 390 & 590 mm
- Roll Lengths 10.00m (50mm), 5.00m (100mm)

#### R-Values

Thickness mm (tolerance +/- 5mm)	Thermal Resistance Km²W
50	1.25
100	2.5
150	3.75
200	5
250	6.25
300	7.5

### Installation and Handling

SupaSoft insulation is harmless and can be installed without gloves or protective clothing, although we recommend you wear a dust mask in enclosed spaces such as lofts.

SupaSoft insulation can be used in conjunction with a vapour permeable membrane to retain the benefits of vapour permeability

#### **Technical Support**

We offer a comprehensive support to meet all your technical requirements including:

- For technical advice call **01768 486285**
- On-site and off-site support throughout the design and build process
- Advice on meeting current regulations including Building Regulations
- U-value and condensation risk analysis
- Advice on environmental impact
- Application guidance notes, comprehensive product data







