

PU FEST Turbo

Two-component polyurethane sealer for resin, cement and microcement floors for both, indoor and outdoor use.

DESCRIPTION

A two-component polyurethane sealer with very high surface hardness and excellent flexibility. It does not turn yellow, it is resistant to UV rays providing very high durability.

APPLICATION

PU FEST TURBO can be used in many ways:

- as concrete and stone sealer for indoor and outdoor use;
- to protect heavy traffic industrial floors exposed to high mechanical loads;
- to protect the surface of epoxy resin coatings, polyurethane resin, cement coatings on floors and walls;
- for the protection of microcement and cement coatings with high and low porosity.

The product is for professional use only.

HOW TO USE

The surface must be perfectly hardened, bearing, dry, clean and free of dust, waxes and oils.

The container with **PU FEST TURBO** sealer should be well shaken. Add hardener as indicated on the package.

The hardener in a ratio of 2: 1 (2 parts by weight of component A: 1 part by weight of component B) is poured into the container with the sealer and mixed thoroughly. Leave the container open for about 10 minutes, then mix again. Apply with a high-quality roller with length of min. 6 mm. After 24 hours from application and after sanding the surface with 220 grit sandpaper, the second layer of **PU FEST Turbo** can be applied.



SPECIFICATIONS

- Mixture ratio:
2 parts by weight of component A:
1 part by weight of component B
- Color: transparent
- Application temperature:
+15°C ÷ +25°C
- Dry on touch after 2 hours.
- Light pedestrian traffic is possible after 24 hours, full traffic after 7 days.
- Consumption: 0,1-0,15 kg / m²
- Gloss level: satin, mat, gloss
- Pot life: 45 minutes
- Shelf life: 6 months.

PACKAGING

PU FEST Turbo is available in packages:

- 5 kg component A + 2,5 kg component B
- 0,8 kg component A + 0,4 kg component B
- 0,4 kg component A + 0,2 kg component B

Do not use **PU FEST TURBO** during the hottest hours of the day, when weather conditions are not favorable, as well as on damp grounds.

SAFETY AND HEALTH



COMPONENT A:

- Highly flammable liquid and vapor.
- Causes serious eye irritation.
- May cause drowsiness or dizziness.
- Frequent contact may cause dryness and cracking of the skin.
- If you need medical attention, have a container or product label on hand.
- Keep out of the reach of children.
- Keep away from heat / sparks / open flames / hot surfaces. No smoking.
- Keep container tightly closed.
- Use only outdoors or in a well-ventilated room.
- Wear protective gloves / protective clothing / eye protection / face protection.
- Call a POISON CENTER or doctor / physician if you feel unwell.
- Dispose your waste in dedicated collection points.

COMPONENT B:

- Highly flammable liquid and vapour.
- Harmful if inhaled.
- May cause an allergic skin reaction.
- Contains isocyanates. May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Keep away from heat / sparks / open flames / hot surfaces. No smoking.
- Keep container tightly closed.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves / protective clothing / eye protection / face protection.
- Call a POISON CENTER or doctor / physician if you feel unwell.
- Dispose your waste in dedicated collection points.

Disclaimer

Microcement Hub products should be used according to the information provided here. Each user should carefully review and consider this information in the context of how the products will be managed and used, including in combination with other products. While this information is accurate to the best of our knowledge at the time of publication, Microcement Hub makes no guarantees regarding its accuracy. If you require further clarification or additional information, please contact Microcement Hub directly.

Microcement Hub products are sold without any express or implied warranties, except as required by law, and are subject to our standard terms and conditions (available to customers upon request). Subject to these terms and any statutory provisions, Microcement Hub accepts no liability (including for negligence) for any loss or damage arising from the use of Microcement Hub products or reliance on the information provided here.