



FIBER COAT

IDEAL FOR PARAPETS, CONCRETE & STEEL ROOFS

SAFETY DATA SHEET

1. PRODUCT IDENTIFICATION AND COMPANY NAME

Rhinoluxe FibreCoat Product Name

Product Identification Fibre Filled Water Proofing

Rhinoluxe Supplier/Manufacturer

Pretoria, South Africa Address

www.rhinoluxe.co.za Website

2. COMPOSITION / INFORMATION ON INGREDIENTS

Resin Base Acrylic resin emulsion

Acrylic resin and small amounts of organic solvents-this product is not classed as hazardous but should Hazardous Components

carry the following S Phrases

S2, S24/25

3. HAZARDS IDENTIFICATION

This paint is NOT flammable. Physical/Chemical Hazards

Human Health Hazards Respiration May cause irritation. Eves May cause slight irritation.

May cause gastro-intestinal irritation. Ingestion

In general no irritation. Skin

Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. **Environmental Hazards**

4. FIRST AID MEASURES

General In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to

an unconscious person.

Move to a safe area with fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular Inhalation

or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by

mouth. If unconscious, place in recovery position and seek medical advice.





IDEAL FOR PARAPETS, CONCRETE & STEEL ROOFS

4. FIRST AID MEASURES

Eye Contact Rinse thoroughly with water for at least 10 minutes. Seek medical attention.

Ingestion Do not induce vomiting. Keep person warm and at rest. Seek medical advice immediately and show the

container or label.

Skin Contact Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use a recognized

skin cleanser. Do not use solvents or thinners.

5. FIRE-FIGHTING MEASURES

This paint is NOT flammable but the dry residue is combustible Expect no direct explosion hazard Use CO2, dry powder or foam

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Ventilate the area. Avoid breathing in vapours. Remove all sources of ignition e.g. flames, sparks, static

electricity and heat.

Spill Contain and collect spillage with absorbent material. Dispose of according to local regulations. Do not

allow spillage to enter sewerage drains or watercourses.

7. HANDLING AND STORAGE

Handling Keep container tightly closed. Eating, drinking and smoking should be prohibited in area where this

material is handled, stored and processed. After handling the material, workers should wash hands and face before eating, drinking and smoking. Always comply with health and safety regulations.

Storage Store in original container. Observe label precautions. Store in a cool, well-ventilated area away from

incompatible materials and ignition sources.

Keep away from oxidizing agents, strong alkaline and acids.

Containers which have been opened must be carefully resealed and kept upright to prevent leakage.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

Engineering Measures Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local

exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal Protective Equipment

Respiration Should ventilation be inadequate or if workers are exposed to concentrations above the exposure limit,

 $appropriate\ certified\ respirators\ must\ be\ used.$

Eyes Use safety eyewear designed to protect against splash of liquids. Never touch eyes with dirty hands or

gloves.

Ingestion Observe the rules of hygiene. Wash hands and face before eating, drinking or smoking.

Skin Use protective gloves. Wash in case of contact.

Environmental Exposure Control Do not allow product to enter sewerage drains or watercourses.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Thick Liquid

Flash Point (°C) Not flammable

Dilution/Wash up Water





IDEAL FOR PARAPETS, CONCRETE & STEEL ROOFS

10. STABLILTY AND REACTIVITY

Stability Stable under recommended storage and handling conditions.

Conditions to Avoid Excessive heat – store below 30 degrees Celsius.

Materials to Avoid Oxidizing agents, strong alkaline or acidic materials.

11. TOXICOLOGICAL INFORMATION

- Frequent and prolonged skin contact may cause irritation and skin inflammation.
- · Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea.
- In some cases contact with product may cause irritation of the skin/mucous membranes.

12. ECOLOGICAL INFORMATION

- There is no data available on the preparation itself.
- Product is considered a water pollutant. Do not allow to enter drains or watercourses.

13. DISPOSAL CONSIDERATIONS

- Do not allow to enter drains or watercourses.
- Dispose according to national and local applicable regulations.
- · Empty containers are suitable for recycling, but caution must be exercised in the disposal of used containers.

14. TRANSPORT INFORMATION

Not classified as dangerous for transport.

15. REGULATORY INFORMATION

Classification Not classified as hazardous

S2 Keep out of reach of Children

S24/25 Avoid contact with eyes and skin

16. OTHER INFORMATION

Date of Printing September 2022

Date of Issue September 2022

Version 2

Notice The information in this MSDS is based on the present state of our knowledge and on current national laws.

The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps in order to fulfill the demand laid down in the local rules and legislation. The information in this MSDS is meant as a description of the safety requirements of our product – it is not to be considered as a guarantee of the

product's properties.