









ABIDE BY ROHS

Silver shaft




SWITCH FUNCTION



Specification :

- 1. Rating : 12V AC/DC max. 2V DC min. 10mA AC/DC max. 10µA DC min.
- 2. Contact Resistance : 100mΩ Max
- 3. Insulation Resistance : 100MΩ Min (DC500V)
- 4. Withstand Voltage : AC100V (50-60Hz) for 1 minute
- 5. Bounce Time : ≤5msec (at 16 in/sec. actuation speed)
- 6. Operation Force : 40±10gf
- 7. Pre travel : 1.1±0.4mm
- 8. Total travel : 3.5±0.4mm
- 9. Operating Life : 70,000,000 Cycles(min).

⑦	Base	—	1	PA66	White	—
⑥	contact	—	2	Composite gold	—	—
⑤	Spring	—	1	Stainless Steel	—	—
④	Cover	—	1	PC	—	—
③	Keystroke	—	1	POM	Silver	—
②	static plate	—	1	Brass	sn plating	—
①	movable plate	—	1	Copper Alloy	—	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS			DATE		Kailh KAIHUA ELECTRONICS CO., LTD		
DRAWN		YI JIN PING	2017.04.13				
CHECKED				TITLE:		PG1511 Keystroke Switch(Golden shaft)	
APPROVALS				PART NO.		CPG151101D212	
TOLERANCES ARE		30<L	±0.30	ANGLE	UNIT: mm	SCALE: 1:1	PROJ: 
		10<=30	±0.20				
		5<=10	±0.15				
		L<=5	±0.10				
				±2°	DRAWING NO.	KHA-PG1511-166	SHEET 1 OF 1

ECN NO.	A	DATE.	NEW DESCRIPTION.	CHANGE.	CHECK.	APPRO.
---------	---	-------	------------------	---------	--------	--------


**Kailh**

**KAIHUA ELECTRONICS**

Document Number:

**KH-PS1705-22**

# Product Specification



P/N: \_\_\_\_\_

**CPG151101D212**

Title :

**PG1511 Keyboard Switch**

Content

1. Scope .....	3
2. Product Application .....	3
3. Technology Parameters .....	3
4. Ratings .....	3
5. Profile Dimensions .....	3
6. Electrical Performance .....	4
7. Mechanical Performance .....	5~6
8. Environmental Performance .....	7~9
9. Recommended PCB Layout .....	10
10. Loading Parameter Specification .....	11
11. Precaution .....	11

### 1. Scope:

This Product Specification covers the requirement of Mechanical Keyboard switch on product performance, test methods and quality assurance provisions.

### 2. Product Application:

Mainly applied on computer keyboards, cash registers, industrial equipment and Man-Machine interface.

### 3. Technology Parameters:

Ambient Humidity: 45 ~ 85% RH

Operating Temperature Range: -10°C ~ +70°C

Storage Temperature Range: -20°C ~ +70°C

Suggested storage period: about 6 months

Require the tin part on the switch terminals should keep good after storage guarantee date

Normal Condition:

Ambient temperature: 20±2°C

Relative humidity: 65%±5%RH

Air pressure: 86~101KPa

### 4. Ratings

Rating: 12V AC/DC max. 2V DC min


10mA AC/DC max. 10μA DC min

Insulation Resistance: ≥100MΩ/DC 500V


Withstand Voltage: 100 AC 1 Minute

Mechanical Life: 70,000,000 Cycles



### 5. Profile Dimensions





## 6. Electrical Performance

Item	Description	Test Condition	Requirement
6.1	Contact Resistance	<p>Static load: (Operation force)x2, which is applied on the center of Switch stem.</p> <p>Measurement tool: Contact resistance Meter. (1KHz,20mV,5~50mA)</p> <p>Measured at low current (100mA or less).</p>	100mΩ Max
6.2	Insulation Resistance	<p>Apply a Voltage of DC 500 V for 1 minute, according to the below method.</p> <p>(1) Between terminals.</p> <p>(2) Between terminal and Body.</p>	100mΩ Min
6.3	Dielectric withstanding voltage	<p>Apply a Voltage of AC100 V (50~60Hz) for 1 minute, according to the below method.</p> <p>(1) Between terminals.</p> <p>(2) Between terminal and Body.</p>	No evidence of breakdown
6.4	Bouncing	<p>Operation speed: 3~4 times/s</p> <p>Oscillo scope</p> <p>Switch Bouncing Test Circuit</p>  <p>Switch Bouncing Test Circuit</p> <p>"ON" "OFF"</p>	<p>Before Life cycle: On: 5ms MAX Off: 5ms MAX</p> <p>After Life cycle: On: 10ms MAX Off: 10ms MAX</p>

## 7. Mechanical Performance

Item	Description	Test Condition	Requirement
7.1	Load Curve	<p>Place the vertical direction of switch operation and gradually increase the load applied to the center of the stem until it stop.</p> 	See page 11
7.2	Loading parameter	<p>Place the vertical direction of switch operation and gradually increase the load applied to the center of the stem until it stop.</p> 	See page 11


<div>Kailh</div> <div>KAIHUA ELECTRONICS</div>		Product Specification			
		P/N:	DOC. No.:	Rev.:	Page:
		CPG151101D212	KH-PS1705-22	C	6/11
7.3	Static Strength	A static load of 3kgf shall be applied in the direction of button operation for a period of 60 seconds. <div>  </div>			No damage (Electrical) And mechanical
7.4	Stem Pull Strength	Break by a pull force applied opposite to the direction of stem operation.			5kgf Min
7.5	Shock	Measured by according to the below condition: (1) Acceleration: 80g (2) Cycles of test: 3 cycles each in 6 directions, for a total of 18 cycles. <div>  </div>			Shall meet No.6, 7.1, 7.2.
7.6	Life Test	1) D.C.12V 10mA resistance load 2) Operation speed: 5-6 times / s 3) Push force: 150gf 4) Push travel: 3.5mm 5) Operation number: 70,000,000 cycles			Contact resistance: 1000mΩ Max Bouncing: 10ms Max Operation force: Variation rate within ±30%

<div>Kailh</div> <div>KAIHUA ELECTRONICS</div>	Product Specification			
	P/N: CPG151101D212	DOC. No.: KH-PS1705-22	Rev.: C	Page: 7/11

8. Environmental Performance

Item	Description	Test Condition	Requirement												
8.1	Cold test	(1) Temperature: -20±2°C (2) Duration of test: 48h (3) Take off a drop water (4) Standard conditions after test: 1h	Contact resistance: 200mΩ Max Shall meet: No. 6.2 to 6.4 No. 7.1 to 7.2												
8.2	Heat test	(1) Temperature: 70±2°C (2) Duration of test: 48h (3) Take off a drop water (4) Standard conditions after test: 1h	Contact resistance: 200mΩ Max Shall meet: No. 6.2 to 6.4 No. 7.1 to 7.2												
8.3	Temperature cycle	(1) Test cycles: 5 cycles (2) Standard condition after test: 1h <table><tr><td></td><td>Temperature</td><td>Duration of test</td></tr><tr><td rowspan="4">1 cycle</td><td>20±5°C</td><td>1h</td></tr><tr><td>-20±2°C</td><td>1h</td></tr><tr><td>20±5°C</td><td>1h</td></tr><tr><td>70±5°C</td><td>1h</td></tr></table>		Temperature	Duration of test	1 cycle	20±5°C	1h	-20±2°C	1h	20±5°C	1h	70±5°C	1h	Contact resistance: 200mΩ Max Shall meet: No. 6.2 to 6.4 No. 7.1 to 7.2
	Temperature	Duration of test													
1 cycle	20±5°C	1h													
	-20±2°C	1h													
	20±5°C	1h													
	70±5°C	1h													




<div>Kailh</div> <div>KAIHUA ELECTRONICS</div>		Product Specification			
		P/N:	DOC. No.:	Rev.:	Page:
		CPG151101D212	KH-PS1705-22	C	8/11
8.4	Soldering heat test	<p>Soldering area: T/2 of PWB thickness. (PWB: T=1.6mm) Soldering temperature: 260±5°C Soldering time: 5±0.5s</p>			Appearance: No abnormality.
8.5	Solder ability	<p>1. Hand soldering: Please practice according to below condition: (1) Soldering Temperature: 350±5°C (2) Continual soldering time: 3±0.5s (3) Capacity of soldering iron: ≤20w</p> <p>2. Automatic PIP soldering: For the product of T/H according to below condition:</p> <p>Wave Soldering Temperature Curve (Single Wave Peak)</p> 			At least 95% of surface area of immersed portion shall be covered by solder.

<div>Kailh</div> <div>KAIHUA ELECTRONICS</div>		Product Specification			
		P/N:	DOC. No.:	Rev.:	Page:
		CPG151101D212	KH-PS1705-22	C	9/11
8.6	Humidity test	(1) Temperature: 60±2°C (2) relative humidity: 90~95% R.H. (3) Duration of test: 48h (4) Take off a drop water (5) Standard conditions after test: 1h		Contact resistance: 200mΩ Max Shall meet : No. 6.2 to 6.4 No. 7.1 to 7.2	
8.7	Salt Spray	Apply the following environment to test (1) Temperature: 35±5°C (2) Salt water density: 5±1% (3) Duration: 12hours (4) After test, the salt deposit shall be removed by running water.		Appearance: No corrosion spot, no crack, no base plate naked. Contact Resistance: 200 mΩ Max	
8.8	Withstand K <sub>2</sub> S	Apply the following environment to test: (1) Temperature: 35±5°C (2) K <sub>2</sub> S Density: 2% (3) Duration: 2 minute.		Appearance: No corrosion spot, no crack, no base plate naked. Contact Resistance: 1000 mΩ Max	

## 9. Recommended PCB Layout


### Mounting Options




### Circuit Board Layouts

Grid line spacing = 1.27mm


Keyswitch without fixation pins



Keyswitch with fixation pins



### Metal Frame Cutout Dimensions



## 10. Loading Parameter (FP/OP/PT/ OF /OT) Specification

Parameter	Unit	Specification	Remark
FP	mm	15.25 ± 0.2	
OP	mm	14.15 ± 0.6	
PT	mm	1.1 <sup>+0.4</sup> <sub>-0.2</sub>	
OF	gf	40 ± 10	
OT	mm	2.0	Min
TT	mm	3.5 ± 0.4	

## 11.Precaution

### 11.1 Immersion Soldering condition

ITEM	CONDITION
Preheat temperature	110°C Max (Ambient temperature of soldering surface of P.W.B)
Preheat time	60s, Max
Area of flux	1/2 Max of PWB Thickness
Temperature of solder	260±5°C
Time of immersion	Within 5s
Number of soldering	2time Max (But should down heat of the first soldering)
Printed wiring board	Single side copper-clad laminates

- (1) After switches were soldered, please be careful not to clean switches with solvent
- (2) Under the condition of using soldering iron, soldering temperature shall be 350°C max within 3 sec.

### 11.2 Notes

- (1) Please be cautious not to give excessive static load or shock to switches.
- (2) Please be careful not to stack up P. W. B. after switches were soldered.
- (3) Preservation under high temperature and high humidity or corrosive gas should be avoided Especially.  
When you need to preserve for a long period, do not open the carton.
- (4) Products meet the ROHS & REACH environmental management substances control standards.