




ABIDE BY ROHS




Rose pink shaft






Specification :

- 1. Rating : 12V AC/DC max. 2V DC min. 10mA AC/DC max. 10μA DC min.
- 2. Contact Resistance : 100mΩ Max
- 3. Insulation Resistance : 100MΩ Min (DC500V)
- 4. Withstand Voltage : AC100V (50-60Hz) for 1 minute
- 5. Bounce Time : ≤5msec (at 16 in/sec. actuation speed)
- 6. Resilience Force ≥12gf
- 7. Operation Force : 50±10gf
- 8. Pre travel : 1.1±0.4mm
- 9. Total travel : 3.5±0.4mm
- 10. Operating Life : 70,000,000 Cycles (min).

SWITCH FUNCTION



The Tilt Angle Of The Switch



<Feel is allowed to have difference before and after life test>

| ITEM | PART NAME | TER'NO. | QTY. | MATERIAL | FINISHING | REMARK |
|------|---------------|---------|------|-----------------|------------|--------|
| ⑧ | Spring | --- | 1 | SUS | Nature | --- |
| ⑦ | Base | --- | 1 | PA66 | White | --- |
| ⑥ | contact | --- | 2 | Composite gold | --- | --- |
| ⑤ | Spring | --- | 1 | Stainless Steel | --- | --- |
| ④ | Cover | --- | 1 | PC | Nature | --- |
| ③ | Keystroke | --- | 1 | POM | Rose Pink | 2044U |
| ② | static plate | --- | 1 | Brass | Plating Sn | --- |
| ① | movable plate | --- | 1 | Copper Alloy | --- | --- |

| APPROVALS | | DATE | Kailh KAIHUA ELECTRONICS CO., LTD | | |
|-----------|-----------|------------|-----------------------------------|--|---|
| DRAWN | YIJINPING | 2017.04.13 | TITLE: | PG1511 Keystroke Switch(Rose pink shaft) | |
| CHECKED | | | PART NO. | CPG151101D215 | |
| APPROVALS | | | TOLERANCES ARE | ANGLE | UNIT: mm SCALE: 1:1 PROJ: |
| | | | 30<L ±0.30 | ±2' | DRAWING NO. KHA-PG1511-169EN SHEET 1 OF 1 |
| | | | 10<L ≤30 ±0.20 | | |
| | | | 5<L ≤10 ±0.15 | | |
| | | | L ≤5 ±0.10 | | |

| ECN NO. | REV. | DATE. | DESCRIPTION. | CHANGE. | CHECK. | APPRO. |
|---------|------|-------|---------------------------------------|---------|-------------|--------|
| | B | | Static plate coating add tin over Ni. | | He De Qiang | |
| | A | | NEW | | | |


Kailh

KAIHUA ELECTRONICS

Document Number:

KH-PS1705-25

Product Specification



P/N:

CPG151101D215

Title :

PG1511 Keyboard Switch

| | | | |
|------------------------------|----------------------------------|-------------------|----------------------|
| P/N: CPG151101D215 | DOC. No.: KH-PS1705-25 | Rev.: A | Page: 2/11 |
|------------------------------|----------------------------------|-------------------|----------------------|

Content

| | |
|---|-----|
| 1. Scope | 3 |
| 2. Product Application | 3 |
| 3. Technology Parameters | 3 |
| 4. Ratings | 3 |
| 5. Profile Dimensions | 3 |
| 6. Electrical Performance | 4 |
| 7. Mechanical Performance | 5~6 |
| 8. Environmental Performance | 7~9 |
| 9. Recommended PCB Layout | 10 |
| 10. Loading Parameter Specification | 11 |
| 11. Precaution | 11 |

| | | | |
|------------------------------|----------------------------------|-------------------|----------------------|
| P/N: CPG151101D215 | DOC. No.: KH-PS1705-25 | Rev.: A | Page: 3/11 |
|------------------------------|----------------------------------|-------------------|----------------------|

1. Scope:

This Product Specification covers the requirement of Mechanical Keyboard switch on product performance, test methods and quality assurance provisions.

2. Product Application:

Mainly applied on computer keyboards, cash registers, industrial equipment and Man-Machine interface.

3. Technology Parameters:

Ambient Humidity: 45 ~ 85% RH

Operating Temperature Range: $-10^{\circ}\text{C} \sim +70^{\circ}\text{C}$

Storage Temperature Range: $-20^{\circ}\text{C} \sim +70^{\circ}\text{C}$

Suggested storage period: about 6 months

Require the tin part on the switch terminals should keep good after storage guarantee date

Normal Condition:

Ambient temperature: $20 \pm 2^{\circ}\text{C}$

Relative humidity: $65\% \pm 5\% \text{RH}$

Air pressure: 86~101KPa

4. Ratings

Rating: 12V AC/DC max. 2V DC min




10mA AC/DC max. 10 μA DC min

Insulation Resistance: $\geq 100\text{M}\Omega/\text{DC } 500\text{V}$


Withstand Voltage: 100 AC 1 Minute

Mechanical Life: 50,000,000 Cycles

5. Profile Dimensions





6. Electrical Performance

| Item | Description | Test Condition | Requirement |
|------|---------------------------------|---|--|
| 6.1 | Contact Resistance | <p>Static load: (Operation force)x2, which is applied on the center of Switch stem.</p> <p>Measurement tool: Contact resistance Meter. (1KHz,20mV,5~50mA)</p> <p>Measured at low current (100mA or less).</p> | 100mΩ Max |
| 6.2 | Insulation Resistance | <p>Apply a Voltage of DC 500 V for 1 minute, according to the below method.</p> <p>(1) Between terminals. (2) Between terminal and Body.</p> | 100mΩ Min |
| 6.3 | Dielectric withstanding voltage | <p>Apply a Voltage of AC100 V (50~60Hz) for 1 minute, according to the below method.</p> <p>(1) Between terminals. (2) Between terminal and Body.</p> | No evidence of breakdown |
| 6.4 | Bouncing | <p>Operation speed: 3~4 times/s</p> <p>Oscillo scope</p> <p>Switch Bouncing Test Circuit</p>  <p style="text-align: center;">Switch Bouncing Test Circuit</p> <p style="text-align: center;">"ON" "OFF"</p> | <p>Before Life cycle: On: 5ms MAX Off: 5ms MAX</p> <p>After Life cycle: On: 10ms MAX Off: 10ms MAX</p> |

7. Mechanical Performance

| Item | Description | Test Condition | Requirement |
|------|-------------------|---|-------------|
| 7.1 | Load Curve | <p>Place the vertical direction of switch operation and gradually increase the load applied to the center of the stem until it stop.</p> <div style="text-align: center;"> <p>Force.Travel-diagram</p> <p>Rose pink shaft</p> </div> | See page 11 |
| 7.2 | Loading parameter | <p>Place the vertical direction of switch operation and gradually increase the load applied to the center of the stem until it stop.</p> <div style="text-align: center;"> <p>Mounting Surface</p> </div> | See page 11 |

| | | | |
|-----|--------------------|---|--|
| 7.3 | Static Strength | <p>A static load of 3kgf shall be applied in the direction of button operation for a period of 60 seconds.</p>  | <p>No damage (Electrical) And mechanical</p> |
| 7.4 | Stem Pull Strength | <p>Break by a pull force applied opposite to the direction of stem operation.</p> | <p>5kgf Min</p> |
| 7.5 | Shock | <p>Measured by according to the below condition: (1) Acceleration: 80g (2) Cycles of test: 3 cycles each in 6 directions, for a total of 18 cycles.</p>  | <p>Shall meet No.6, 7.1, 7.2.</p> |
| 7.6 | Life Test | <ol style="list-style-type: none"> 1) D.C.12V 10mA resistance load 2) Operation speed: 5-6 times / s 3) Push force: 150gf 4) Push travel: 3.5mm 5) Operation number: 70,000,000 cycles | <p>Contact resistance: 1000mΩ Max Bouncing: 10ms Max Operation force: Variation rate within ±30%</p> |

8. Environmental Performance

| Item | Description | Test Condition | Requirement | | | | | | | | | | | | |
|---------|----------------------------|---|---|-------------|------------------|---------|---------------------------|----|----------------------------|----|---------------------------|----|---------------------------|----|---|
| 8.1 | Cold test | (1) Temperature: $-20\pm 2^{\circ}\text{C}$ (2) Duration of test: 48h (3) Take off a drop water (4) Standard conditions after test: 1h | Contact resistance: 200mΩ Max Shall meet: No. 6.2 to 6.4 No. 7.1 to 7.2 | | | | | | | | | | | | |
| 8.2 | Heat test | (1) Temperature: $70\pm 2^{\circ}\text{C}$ (2) Duration of test: 48h (3) Take off a drop water (4) Standard conditions after test: 1h | Contact resistance: 200mΩ Max Shall meet: No. 6.2 to 6.4 No. 7.1 to 7.2 | | | | | | | | | | | | |
| 8.3 | Temperature cycle | (1) Test cycles: 5 cycles (2) Standard condition after test: 1h <table border="1" style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <thead> <tr> <th style="width: 30%;"></th> <th style="width: 30%;">Temperature</th> <th style="width: 40%;">Duration of test</th> </tr> </thead> <tbody> <tr> <td rowspan="4" style="text-align: center;">1 cycle</td> <td style="text-align: center;">$20\pm 5^{\circ}\text{C}$</td> <td style="text-align: center;">1h</td> </tr> <tr> <td style="text-align: center;">$-20\pm 2^{\circ}\text{C}$</td> <td style="text-align: center;">1h</td> </tr> <tr> <td style="text-align: center;">$20\pm 5^{\circ}\text{C}$</td> <td style="text-align: center;">1h</td> </tr> <tr> <td style="text-align: center;">$70\pm 5^{\circ}\text{C}$</td> <td style="text-align: center;">1h</td> </tr> </tbody> </table> | | Temperature | Duration of test | 1 cycle | $20\pm 5^{\circ}\text{C}$ | 1h | $-20\pm 2^{\circ}\text{C}$ | 1h | $20\pm 5^{\circ}\text{C}$ | 1h | $70\pm 5^{\circ}\text{C}$ | 1h | Contact resistance: 200mΩ Max Shall meet: No. 6.2 to 6.4 No. 7.1 to 7.2 |
| | Temperature | Duration of test | | | | | | | | | | | | | |
| 1 cycle | $20\pm 5^{\circ}\text{C}$ | 1h | | | | | | | | | | | | | |
| | $-20\pm 2^{\circ}\text{C}$ | 1h | | | | | | | | | | | | | |
| | $20\pm 5^{\circ}\text{C}$ | 1h | | | | | | | | | | | | | |
| | $70\pm 5^{\circ}\text{C}$ | 1h | | | | | | | | | | | | | |

8.4

Soldering heat test

Soldering area: T/2 of PWB thickness.
(PWB: T=1.6mm)
Soldering temperature: $260 \pm 5^\circ\text{C}$
Soldering time: $5 \pm 0.5\text{s}$

Appearance:
No abnormality.

8.5


Solder ability

1. Hand soldering:
Please practice according to below condition:
(1) Soldering Temperature: $350 \pm 5^\circ\text{C}$
(2) Continual soldering time: $3 \pm 0.5\text{s}$
(3) Capacity of soldering iron: $\leq 20\text{w}$

2. Automatic PIP soldering:
For the product of T/H according to below condition:

At least 95% of surface area of immersed portion shall be covered by solder.

Wave Soldering Temperature Curve (Single Wave Peak)




| | | | |
|-----|--------------------------------|---|---|
| 8.6 | Humidity test | (1) Temperature: $60\pm 2^{\circ}\text{C}$ (2) relative humidity: 90~95% R.H. (3) Duration of test: 48h (4) Take off a drop water (5) Standard conditions after test: 1h | Contact resistance: 200m Ω Max Shall meet : No. 6.2 to 6.4 No. 7.1 to 7.2 |
| 8.7 | Salt Spray | Apply the following environment to test (1) Temperature: $35\pm 5^{\circ}\text{C}$ (2) Salt water density: $5\pm 1\%$ (3) Duration: 12hours (4) After test, the salt deposit shall be removed by running water. | Appearance: No corrosion spot, no crack, no base plate naked. Contact Resistance: 200 m Ω Max |
| 8.8 | Withstand K_2S | Apply the following environment to test: (1) Temperature: $35\pm 5^{\circ}\text{C}$ (2) K_2S Density: 2% (3) Duration: 2 minute. | Appearance: No corrosion spot, no crack, no base plate naked. Contact Resistance: 1000 m Ω Max |

| | | | |
|------------------------------|----------------------------------|-------------------|-----------------------|
| P/N: CPG151101D215 | DOC. No.: KH-PS1705-25 | Rev.: A | Page: 10/11 |
|------------------------------|----------------------------------|-------------------|-----------------------|

9. Recommended PCB Layout


Mounting Options




Circuit Board Layouts

Grid line spacing = 1.27mm


Keyswitch without fixation pins



Keyswitch with fixation pins



Metal Frame Cutout Dimensions



10. Loading Parameter (FP/OP/PT/OF / OT/TT) Specification

| Parameter | Unit | Specification | Remark |
|-----------|------|---------------|--------|
| FP | mm | 15.25 ± 0.2 | |
| OP | mm | 14.15 ± 0.6 | |
| PT | mm | 1.1 ± 0.4 | |
| OF | gf | 50 ± 10 | |
| OT | mm | 1.2 | Min |
| TT | mm | 3.5 ± 0.4 | |

11. Precaution

11.1 Immersion Soldering condition

| ITEM | CONDITION |
|-----------------------|---|
| Preheat temperature | 110°C Max (Ambient temperature of soldering surface of P.W.B) |
| Preheat time | 60s, Max |
| Area of flux | 1/2 Max of PWB Thickness |
| Temperature of solder | 260±5°C |
| Time of immersion | Within 5s |
| Number of soldering | 2time Max (But should down heat of the first soldering) |
| Printed wiring board | Single side copper-clad laminates |

- (1) After switches were soldered, please be careful not to clean switches with solvent.
- (2) Under the condition of using soldering iron, soldering temperature shall be 350°C max within 3 sec.

11.2 Notes

- (1) Please be cautious not to give excessive static load or shock to switches.
- (2) Please be careful not to stack up P. W. B. after switches were soldered.
- (3) Preservation under high temperature and high humidity or corrosive gas should be avoided Especially.
When you need to preserve for a long period, do not open the carton.
- (4) Products meet the ROHS & REACH environmental management substances control standards.