

# COLLECTION BARE COLOR PELLE 24X48

ITEM NUMBER **BARPE24X48M**

APPLICATION **FLOOR, WALL**

## PRODUCT INFO

NOMINAL SIZE	24" X 48"
ACTUAL SIZE	23.48" X 47.05"
RECTIFIED	YES
MATERIAL	COLOR BODY PORCELAIN
THICKNESS	8.5 MM
FINISH	MATTE
FACES	20
VARIATION	V3 MODERATE
COUNTRY OF ORIGIN	ITALY
CERTIFICATION	CERAMICS OF ITALY

## TESTING

DCOF	≥0.60
MOHS SCRATCH HARDNESS	≥6
BREAKING STRENGTH	> 1300 N; 35 N/mm <sup>2</sup>
UNI EN ISO 10545/4	
CHEMICAL RESISTANCE	GB MINIMUM
UNI EN ISO 10545/13	
STAIN RESISTANCE	CLASS 3 MINIMUM
UNI EN ISO 10545/14	
WATER ABSORPTION	<0.5%
ASTM C373	
VOC	NONE
FROST RESISTANT	YES
HEAT RESISTANT	YES
DIRECT SUNLIGHT	YES

## INSTALLATION

RECOMMENDED GROUT JOINT	1/16"
SEALING REQUIRED	NO
SEALING RECOMMENDED	YES
RECOMMENDED PATTERNS	STACKED BOND; NO MORE THAN 30% OFFSET FOR STAGGERED PATTERN

## PACKAGING

SOLD BY	BOX
PIECES/BOX	2
SQFT/BOX	15.50 SF
SQFT/PIECE	7.75 SF
WEIGHT/BOX	62.39 LBS



## USAGE

COMMERCIAL FLOORS	YES
RESIDENTIAL FLOORS	YES
RAMPS & INCLINES	NO
SHOWER WALL	YES
SHOWER FLOOR	YES
STEAM/SAUNA WALL	YES
STEAM/SAUNA FLOOR	YES
FIREPLACE	YES

## POOL USAGE

POOL DECK	YES
POOL WATERLINE	YES
POOL SUBMERGED	YES
SPA/HOT TUB	YES

EXTERIOR USAGE	FREEZING	NON-FREEZING
EXTERIOR COVERED WALL	YES	YES
EXTERIOR UNCOVERED WALL	YES	YES
EXTERIOR COVERED FLOOR	YES	YES
EXTERIOR UNCOVERED FLOOR	YES	YES

## ADDITIONAL INFORMATION

PLEASE VISIT [GLAZZIOSURFACES.COM](http://GLAZZIOSURFACES.COM) FOR ADDITIONAL PRODUCT INFORMATION INCLUDING INSTALLATION INSTRUCTIONS AND CARE & MAINTENANCE GUIDELINES.

ACTUAL COLOR, SIZE, AND TEXTURE MAY VARY. PLEASE REFER TO SAMPLE CHIP FOR VISUAL ACCURACY.

glazzio.  
**SURFACES**