

COLLECTION BARE

COLOR PELLE FORMED 24X48

ITEM NUMBER **BARPE24X48FOM**

APPLICATION **FLOOR, WALL**

PRODUCT INFO

NOMINAL SIZE	24" X 48"
ACTUAL SIZE	23.48" X 47.05"
RECTIFIED	YES
MATERIAL	COLOR BODY PORCELAIN
THICKNESS	8.5 MM
FINISH	MATTE
FACES	20
VARIATION	V3 MODERATE
COUNTRY OF ORIGIN	ITALY
CERTIFICATION	CERAMICS OF ITALY

TESTING

DCOF	≥0.60
MOHS SCRATCH HARDNESS	≥6
BREAKING STRENGTH	> 1300 N; 35 N/mm ²
UNI EN ISO 10545/4	
CHEMICAL RESISTANCE	GB MINIMUM
UNI EN ISO 10545/13	
STAIN RESISTANCE	CLASS 3 MINIMUM
UNI EN ISO 10545/14	
WATER ABSORPTION	<0.5%
ASTM C373	
VOC	NONE
FROST RESISTANT	YES
HEAT RESISTANT	YES
DIRECT SUNLIGHT	YES

INSTALLATION

RECOMMENDED GROUT JOINT	1/16"
SEALING REQUIRED	NO
SEALING RECOMMENDED	YES
RECOMMENDED PATTERNS	STACKED BOND; NO MORE THAN 30% OFFSET FOR STAGGERED PATTERN

PACKAGING

SOLD BY	BOX
PIECES/BOX	2
SQFT/BOX	15.50 SF
SQFT/PIECE	7.75 SF
WEIGHT/BOX	62.39 LBS



USAGE

COMMERCIAL FLOORS	YES
RESIDENTIAL FLOORS	YES
RAMPS & INCLINES	NO
SHOWER WALL	YES
SHOWER FLOOR	YES
STEAM/SAUNA WALL	YES
STEAM/SAUNA FLOOR	YES
FIREPLACE	YES

POOL USAGE

POOL DECK	YES
POOL WATERLINE	YES
POOL SUBMERGED	YES
SPA/HOT TUB	YES

EXTERIOR USAGE	FREEZING	NON-FREEZING
EXTERIOR COVERED WALL	YES	YES
EXTERIOR UNCOVERED WALL	YES	YES
EXTERIOR COVERED FLOOR	YES	YES
EXTERIOR UNCOVERED FLOOR	YES	YES

ADDITIONAL INFORMATION

PLEASE VISIT GLAZZIOSURFACES.COM FOR ADDITIONAL PRODUCT INFORMATION INCLUDING INSTALLATION INSTRUCTIONS AND CARE & MAINTENANCE GUIDELINES.

ACTUAL COLOR, SIZE, AND TEXTURE MAY VARY. PLEASE REFER TO SAMPLE CHIP FOR VISUAL ACCURACY.

glazzio.
SURFACES