

# COLLECTION CHI TOWN

## COLOR WRIGLEY

ITEM NUMBER **CHIWR12X24M**

APPLICATION **FLOOR, WALL**

### PRODUCT INFO

NOMINAL SIZE	12" X 24"
ACTUAL SIZE	11.92" X 23.62"
MATERIAL	COLORBODY PORCELAIN
FINISH	MATTE
THICKNESS	8.5 MM
RECTIFIED	YES
FACES	64
VARIATION	V2
COUNTRY OF ORIGIN	ITALY
CERTIFICATION	52% RECYCLED MATERIAL, CERAMICS OF ITALY

### TESTING

DCOF WET	≥ 0.42
BREAKING STRENGTH	> 40 N/MM <sup>2</sup>
ASTM C648	
CHEMICAL RESISTANCE	LA-HA-A
ASTM C650	
STAIN RESISTANCE	CLASS 5
ASTM C1378	
WATER ABSORPTION	< 0.15%
ASTM C373	
VOC	NONE
RECYCLED CONTENT	52%
FROST RESISTANT	YES
HEAT RESISTANT	YES
DIRECT SUNLIGHT	YES

### INSTALLATION

RECOMMENDED GROUT JOINT	3/16"
SEALING REQUIRED	NO
SEALING RECOMMENDED	YES
RECOMMENDED PATTERNS	NO MORE THAN 30% OFFSET FOR STAGGERED PATTERN

### PACKAGING

SOLD BY	BOX
PIECES/BOX	7
SQFT/BOX	13.56 SF
SQFT/PIECE	1.94 SF
WEIGHT/BOX	52.91 LBS



### USAGE

COMMERCIAL FLOORS	YES
RESIDENTIAL FLOORS	YES
RAMPS & INCLINES	NO
SHOWER WALL	YES
SHOWER FLOOR	YES
STEAM/SAUNA WALL	YES
STEAM/SAUNA FLOOR	NO
FIREPLACE	YES

### POOL USAGE

POOL DECK	NO
POOL WATERLINE	YES
POOL SUBMERGED	YES (WALL ONLY)
SPA/HOT TUB	YES

### EXTERIOR USAGE

	FREEZING	NON-FREEZING
EXTERIOR COVERED WALL	YES	YES
EXTERIOR UNCOVERED WALL	YES	YES
EXTERIOR COVERED FLOOR	NO	NO
EXTERIOR UNCOVERED FLOOR	NO	NO

### ADDITIONAL INFORMATION

PLEASE VISIT [GLAZZIOSURFACES.COM](http://GLAZZIOSURFACES.COM) FOR ADDITIONAL PRODUCT INFORMATION INCLUDING INSTALLATION INSTRUCTIONS AND CARE & MAINTENANCE GUIDELINES. ACTUAL COLOR, SIZE, AND TEXTURE MAY VARY. PLEASE REFER TO SAMPLE CHIP FOR VISUAL ACCURACY.

glazzio®  
**SURFACES**