COLLECTION **DECKO**COLOR **FRESH HAUS 2X5 PICKET MOSAIC**

ITEM NUMBER **DEK3505**APPLICATION **WALL**

| PRO | DUC | CT IN | VFO. |
|------------|-----|-------|------|
| | | | |

| THODOOT IN O | |
|-------------------------|-----------------------|
| NOMINAL SHEET SIZE | 11" X 12" |
| ACTUAL SHEET SIZE | 11"X 11.50" |
| INDIVIDUAL TILE SIZE | 2" X 5" |
| MATERIAL | PORCELAIN TILE |
| FINISH | CRACKLE FINISH |
| THICKNESS | 7 MM |
| VARIATION | V2 |
| CERTIFICATIONS | |
| TESTING | |
| DCOF WET | - |
| MOHS | 4 |
| PEI RATING | CLASS 4 |
| BREAKING STRENGTH | 1196 |
| ASTM C648 | |
| CHEMICAL RESISTANCE | Α |
| ASTM C650 | |
| STAIN RESISTANCE | Α |
| ASTM C1378 | |
| WATER ABSORPTION | < 0.5% |
| ASTM C373 | |
| VOC | VOC FREE |
| RECYCLED CONTENT | NO |
| FROST RESISTANT | YES |
| HEAT RESISTANT | YES |
| DIRECT SUNLIGHT | YES |
| INSTALLATION | |
| RECOMMENDED GROUT JOINT | PER MOSAIC SPACING |
| SEALING REQUIRED | YES |
| SEALING RECOMMENDED | YES |
| | |



USAGE

| COMMERCIAL FLOORS | NO |
|--------------------|----------|
| RESIDENTIAL FLOORS | NO |
| RAMPS & INCLINES | NO |
| SHOWER WALL | YES |
| SHOWER FLOOR | NO |
| STEAM/SAUNA WALL | YES |
| STEAM/SAUNA FLOOR | NO |
| FIREPLACE | SURROUND |
| POOL USAGE | |
| POOL DECK | NO |
| POOL WATERLINE | NO |
| POOL SUBMERGED | NO |
| SPA/HOT TUB | NO |
| | |

| EXTERIOR USAGE | FREEZING | NON-FREEZING |
|--------------------------|----------|--------------|
| EXTERIOR COVERED WALL | NO | YES |
| EXTERIOR UNCOVERED WALL | NO | YES |
| EXTERIOR COVERED FLOOR | NO | NO |
| EXTERIOR UNCOVERED FLOOR | NO | NO |

ADDITIONAL INFORMATION

SHEET

2.53 LBS

0.88

PLEASE VISIT GLAZZIOSURFACES.COM FOR ADDITIONAL PRODUCT INFORMATION INCLUDING INSTALLATION INSTRUCTIONS AND CARE & MAINTENANCE GUIDELINES. ACTUAL COLOR, SIZE, AND TEXTURE MAY VARY. PLEASE REFER TO SAMPLE CHIP FOR VISUAL ACCURACY.



PACKAGING SOLD BY

SQFT/SHEET

WEIGHT/SHEET