

COLLECTION EARLY DAWN COLOR GLORIOUS DAYLIGHT

ITEM NUMBER **ELD16052**
APPLICATION **FLOOR, WALL**

PRODUCT INFO

NOMINAL SIZE	4" X 12"
MATERIAL	CERAMIC
FINISH	GLOSSY
THICKNESS	8 MM
RECTIFIED	NO
FACES	29
VARIATION	V4
COUNTRY OF ORIGIN	PORTUGAL
CERTIFICATIONS	RECYCLED CONTENT

TESTING

DCOF WET	-
BREAKING STRENGTH	≥ 0.5 KN
UNI EN ISO 10545/4	
CHEMICAL RESISTANCE	GA + GLA
UNI EN ISO 10545/13	
STAIN RESISTANCE	CLASS 5
UNI EN ISO 10545/14	
WATER ABSORPTION	18-20%
UNI EN ISO 10545/3	
VOC	VOC FREE
RECYCLED CONTENT	7.5-10%
FROST RESISTANT	NO
HEAT RESISTANT	YES
DIRECT SUNLIGHT	YES

INSTALLATION

RECOMMENDED GROUT JOINT	3/16"
SEALING REQUIRED	NO
SEALING RECOMMENDED	YES
RECOMMENDED PATTERNS	STACK, BOND, DRY LAYOUT RECOMMENDED

PACKAGING

SOLD BY	BOX
PIECES/BOX	30
SQFT/BOX	9.69 SF
SQFT/PIECE	0.32 SF
WEIGHT/BOX	26.10 LBS



USAGE

COMMERCIAL FLOORS	NO
RESIDENTIAL FLOORS	NO
RAMPS & INCLINES	NO
SHOWER WALL	YES
SHOWER FLOOR	NO
STEAM/SAUNA WALL	YES
STEAM/SAUNA FLOOR	NO
FIREPLACE	NO

POOL USAGE

POOL DECK	NO
POOL WATERLINE	NO
POOL SUBMERGED	NO
SPA/HOT TUB	NO

EXTERIOR USAGE

	FREEZING	NON-FREEZING
EXTERIOR COVERED WALL	NO	NO
EXTERIOR UNCOVERED WALL	NO	NO
EXTERIOR COVERED FLOOR	NO	NO
EXTERIOR UNCOVERED FLOOR	NO	NO

ADDITIONAL INFORMATION

PLEASE VISIT GLAZZIOSURFACES.COM FOR ADDITIONAL PRODUCT INFORMATION INCLUDING INSTALLATION INSTRUCTIONS AND CARE & MAINTENANCE GUIDELINES.

ACTUAL COLOR, SIZE, AND TEXTURE MAY VARY. PLEASE REFER TO SAMPLE CHIP FOR VISUAL ACCURACY.

glazzio®
SURFACES