COLLECTION INGRAIN COLOR BAKED 12X24

ITEM NUMBER INGBA12X24M APPLICATION FLOOR, WALL

PRODUCT INFO

ACTUAL SIZE 11.81" X 23.62" MATERIAL COLORBODY PORCELAIN FINISH MATTE THICKNESS 8.5 MM RECTIFIED YES VARIATION V2 COUNTRY OF ORIGIN ITALY CERTIFICATION CERAMICS OF ITALY TESTING DCOF WET ≥ 0.42 BREAKING STRENGTH COMPLIANT UNI EN ISO 10545/4 CHEMICAL RESISTANCE COMPLIANT UNI EN ISO 10545/13 STAIN RESISTANCE COMPLIANT UNI EN ISO 10545/14 WATER ABSORPTION COMPLIANT UNI EN ISO 10545/3 VOC NONE RECYCLED CONTENT NONE FROST RESISTANT YES HEAT RESISTANT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING RECOMMENDED YES		
MATERIALCOLORBODY PORCELAINFINISHMATTETHICKNESS8.5 MMRECTIFIEDYESVARIATIONV2COUNTRY OF ORIGINITALYCERTIFICATIONCERAMICS OF ITALYTESTINGCERAMICS OF ITALYDCOF WET≥ 0.42BREAKING STRENGTHCOMPLIANTUNI EN ISO 10545/4COMPLIANTUNI EN ISO 10545/13COMPLIANTUNI EN ISO 10545/14COMPLIANTUNI EN ISO 10545/3COMPLIANTVOCNONERECYCLED CONTENTNONEFROST RESISTANTYESINSTALLATIONRECOMMENDED GROUT JOINT3/16"SEALING REQUIREDNOSEALING REQUIREDNORECOMMENDED PATTERNSSTACK, NO MORETHAN 30% OFFSETFOR STAGGERED	NOMINAL SIZE	12" X 24"
FINISHMATTETHICKNESS8.5 MMRECTIFIEDYESVARIATIONV2COUNTRY OF ORIGINITALYCERTIFICATIONCERAMICS OF ITALYTESTINGCERAMICS OF ITALYDCOF WET≥ 0.42BREAKING STRENGTHCOMPLIANTUNI EN ISO 10545/4COMPLIANTUNI EN ISO 10545/13COMPLIANTUNI EN ISO 10545/14COMPLIANTUNI EN ISO 10545/14COMPLIANTUNI EN ISO 10545/14COMPLIANTUNI EN ISO 10545/3COMPLIANTUNI EN ISO 10545/3COMPLIANTUNI EN ISO 10545/3COMPLIANTVOCNONERECYCLED CONTENTNONEFROST RESISTANTYESINSTALLATIONYESINSTALLATIONSTACK, NO MORERECOMMENDED GROUT JOINT3/16"SEALING REQUIREDNOSEALING REQUIREDNORECOMMENDED PATTERNSSTACK, NO MORETHAN 30% OFFSETFOR STAGGERED	ACTUAL SIZE	11.81" X 23.62"
THICKNESS 8.5 MM RECTIFIED YES VARIATION V2 COUNTRY OF ORIGIN ITALY CERTIFICATION CERAMICS OF ITALY TESTING CERAMICS OF ITALY TESTING 2 0.42 BREAKING STRENGTH COMPLIANT UNI EN ISO 10545/4 COMPLIANT UNI EN ISO 10545/13 COMPLIANT UNI EN ISO 10545/13 COMPLIANT UNI EN ISO 10545/14 COMPLIANT UNI EN ISO 10545/14 COMPLIANT UNI EN ISO 10545/3 COMPLIANT UNI EN ISO 10545/3 NONE RECYCLED CONTENT NONE FROST RESISTANT YES INEAT RESISTANT YES INEAT RESISTANT YES INSTALLATION NO RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	MATERIAL C	COLORBODY PORCELAIN
RECTIFIED YES VARIATION V2 COUNTRY OF ORIGIN ITALY CERTIFICATION CERAMICS OF ITALY TESTING DCOF WET ≥ 0.42 BREAKING STRENGTH COMPLIANT UNI EN ISO 10545/4 CHEMICAL RESISTANCE COMPLIANT UNI EN ISO 10545/13 STAIN RESISTANCE COMPLIANT UNI EN ISO 10545/14 WATER ABSORPTION COMPLIANT UNI EN ISO 10545/3 VOC NONE RECYCLED CONTENT NONE FROST RESISTANT YES HEAT RESISTANT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	FINISH	MATTE
VARIATION V2 COUNTRY OF ORIGIN ITALY CERTIFICATION CERAMICS OF ITALY TESTING CERAMICS OF ITALY TESTING 2 0.42 BREAKING STRENGTH COMPLIANT UNI EN ISO 10545/4 COMPLIANT UNI EN ISO 10545/4 COMPLIANT UNI EN ISO 10545/13 STAIN RESISTANCE STAIN RESISTANCE COMPLIANT UNI EN ISO 10545/14 COMPLIANT UNI EN ISO 10545/3 COMPLIANT VOC NONE RECYCLED CONTENT NONE FROST RESISTANT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	THICKNESS	8.5 MM
COUNTRY OF ORIGIN ITALY CERTIFICATION CERAMICS OF ITALY TESTING DCOF WET ≥ 0.42 BREAKING STRENGTH COMPLIANT UNI EN ISO 10545/4 COMPLIANT UNI EN ISO 10545/13 COMPLIANT UNI EN ISO 10545/13 COMPLIANT UNI EN ISO 10545/14 COMPLIANT UNI EN ISO 10545/14 COMPLIANT UNI EN ISO 10545/14 COMPLIANT UNI EN ISO 10545/3 VOC VOC NONE RECYCLED CONTENT NONE FROST RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION NO RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	RECTIFIED	YES
CERTIFICATION CERAMICS OF ITALY TESTING DCOF WET ≥ 0.42 BREAKING STRENGTH COMPLIANT UNI EN ISO 10545/4 CHEMICAL RESISTANCE COMPLIANT UNI EN ISO 10545/13 STAIN RESISTANCE COMPLIANT UNI EN ISO 10545/14 WATER ABSORPTION COMPLIANT UNI EN ISO 10545/3 VOC NONE RECYCLED CONTENT NONE FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16" SEALING RECUMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	VARIATION	V2
TESTING DCOF WET ≥ 0.42 BREAKING STRENGTH COMPLIANT UNI EN ISO 10545/4 CHEMICAL RESISTANCE COMPLIANT UNI EN ISO 10545/13 STAIN RESISTANCE COMPLIANT UNI EN ISO 10545/14 WATER ABSORPTION COMPLIANT UNI EN ISO 10545/3 VOC NONE RECYCLED CONTENT NONE FROST RESISTANT YES HEAT RESISTANT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	COUNTRY OF ORIGIN	ITALY
DCOF WET ≥ 0.42 BREAKING STRENGTH COMPLIANT UNI EN ISO 10545/4 COMPLIANT UNI EN ISO 10545/13 COMPLIANT UNI EN ISO 10545/13 STAIN RESISTANCE STAIN RESISTANCE COMPLIANT UNI EN ISO 10545/14 WATER ABSORPTION WATER ABSORPTION COMPLIANT UNI EN ISO 10545/3 COMPLIANT VOC NONE RECYCLED CONTENT NONE FROST RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	CERTIFICATION	CERAMICS OF ITALY
BREAKING STRENGTH COMPLIANT UNI EN ISO 10545/4 CHEMICAL RESISTANCE COMPLIANT UNI EN ISO 10545/13 STAIN RESISTANCE COMPLIANT UNI EN ISO 10545/14 WATER ABSORPTION COMPLIANT UNI EN ISO 10545/3 VOC NONE RECYCLED CONTENT NONE FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	TESTING	
UNI EN ISO 10545/4 CHEMICAL RESISTANCE COMPLIANT UNI EN ISO 10545/13 STAIN RESISTANCE COMPLIANT UNI EN ISO 10545/14 WATER ABSORPTION COMPLIANT UNI EN ISO 10545/3 VOC NONE RECYCLED CONTENT NONE FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	DCOF WET	≥ 0.42
CHEMICAL RESISTANCE COMPLIANT UNI EN ISO 10545/13 STAIN RESISTANCE COMPLIANT UNI EN ISO 10545/14 WATER ABSORPTION COMPLIANT UNI EN ISO 10545/3 VOC NONE RECYCLED CONTENT NONE FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING REQUIRED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	BREAKING STRENGTH	COMPLIANT
UNI EN ISO 10545/13 STAIN RESISTANCE COMPLIANT UNI EN ISO 10545/14 WATER ABSORPTION COMPLIANT UNI EN ISO 10545/3 VOC NONE RECYCLED CONTENT NONE FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	UNI EN ISO 10545/4	
STAIN RESISTANCE COMPLIANT UNI EN ISO 10545/14 WATER ABSORPTION COMPLIANT UNI EN ISO 10545/3 VOC NONE RECYCLED CONTENT NONE FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING REQUIRED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	CHEMICAL RESISTANCE	COMPLIANT
UNI EN ISO 10545/14 WATER ABSORPTION COMPLIANT UNI EN ISO 10545/3 VOC NONE RECYCLED CONTENT NONE FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	UNI EN ISO 10545/13	
WATER ABSORPTION COMPLIANT UNI EN ISO 10545/3 VOC NONE RECYCLED CONTENT NONE FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	STAIN RESISTANCE	COMPLIANT
UNI EN ISO 10545/3 VOC NONE RECYCLED CONTENT NONE FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	UNI EN ISO 10545/14	
VOC NONE RECYCLED CONTENT NONE FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	WATER ABSORPTION	COMPLIANT
RECYCLED CONTENT NONE FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	UNI EN ISO 10545/3	
FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION 3/16" RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	VOC	NONE
HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	RECYCLED CONTENT	NONE
DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	FROST RESISTANT	YES
INSTALLATION RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	HEAT RESISTANT	YES
RECOMMENDED GROUT JOINT 3/16" SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	DIRECT SUNLIGHT	YES
SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	INSTALLATION	
SEALING RECOMMENDED YES RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	RECOMMENDED GROUT JO	INT 3/16"
RECOMMENDED PATTERNS STACK, NO MORE THAN 30% OFFSET FOR STAGGERED	SEALING REQUIRED	NO
THAN 30% OFFSET FOR STAGGERED	SEALING RECOMMENDED	YES
	RECOMMENDED PATTERNS	THAN 30% OFFSET FOR STAGGERED

PACKAGING

SOLD BY	BOX
PIECES/BOX	7
SQFT/BOX	13.56 SF
SQFT/PIECE	1.94 SF
WEIGHT/BOX	54.59 LBS





USAGE

COMMERCIAL FLOORS	YES
RESIDENTIAL FLOORS	YES
RAMPS & INCLINES	NO
SHOWER WALL	YES
SHOWER FLOOR	YES
STEAM/SAUNA WALL	YES
STEAM/SAUNA FLOOR	NO
FIREPLACE	YES

POOL USAGE

POOL DECK	YES
POOL WATERLINE	YES
POOL SUBMERGED	YES (WALL ONLY)
SPA/HOT TUB	YES

EXTERIOR USAGE	FREEZING	NON-FREEZING
EXTERIOR COVERED WALL	YES	YES
EXTERIOR UNCOVERED WALL	YES	YES
EXTERIOR COVERED FLOOR	YES	YES
EXTERIOR UNCOVERED FLOOR	YES	YES

ADDITIONAL INFORMATION

PLEASE VISIT **GLAZZIOSURFACES.COM** FOR ADDITIONAL PRODUCT INFORMATION INCLUDING INSTALLATION INSTRUCTIONS AND CARE & MAINTENANCE GUIDELINES.

ACTUAL COLOR, SIZE, AND TEXTURE MAY VARY. PLEASE REFER TO SAMPLE CHIP FOR VISUAL ACCURACY.

