

# COLLECTION INGRAIN

## COLOR BAKED 24X48 PAVER

ITEM NUMBER **INGBA24X48PVM**  
APPLICATION **FLOOR, WALL**



### PRODUCT INFO

NOMINAL SIZE	24" X 48"
ACTUAL SIZE	23.62" X 47.24"
MATERIAL	COLORBODY PORCELAIN
FINISH	MATTE
THICKNESS	20 MM
RECTIFIED	YES
VARIATION	V2
COUNTRY OF ORIGIN	ITALY
CERTIFICATION	CERAMICS OF ITALY

### TESTING

DCOF WET	≥ 0.60
BREAKING STRENGTH	COMPLIANT
UNI EN ISO 10545/4	
CHEMICAL RESISTANCE	GA
UNI EN ISO 10545/13	
STAIN RESISTANCE	CLASS 5
UNI EN ISO 10545/14	
WATER ABSORPTION	COMPLIANT
UNI EN ISO 10545/3	
VOC	NONE
RECYCLED CONTENT	NONE
FROST RESISTANT	YES
HEAT RESISTANT	YES
DIRECT SUNLIGHT	YES

### INSTALLATION

RECOMMENDED GROUT JOINT	3/16"
SEALING REQUIRED	NO
SEALING RECOMMENDED	YES
RECOMMENDED PATTERNS	STACK, NO MORE THAN 30% OFFSET FOR STAGGERED PATTERN

### PACKAGING

SOLD BY	BOX
PIECES/BOX	1
SQFT/BOX	7.75 SF
SQFT/PIECE	7.75 SF
WEIGHT/BOX	74.63 LBS

### USAGE

COMMERCIAL FLOORS	YES
RESIDENTIAL FLOORS	YES
RAMPS & INCLINES	NO
SHOWER WALL	YES
SHOWER FLOOR	YES
STEAM/SAUNA WALL	YES
STEAM/SAUNA FLOOR	NO
FIREPLACE	YES

### POOL USAGE

POOL DECK	NO
POOL WATERLINE	YES
POOL SUBMERGED	YES (WALL ONLY)
SPA/HOT TUB	YES

### EXTERIOR USAGE

	FREEZING	NON-FREEZING
EXTERIOR COVERED WALL	YES	YES
EXTERIOR UNCOVERED WALL	YES	YES
EXTERIOR COVERED FLOOR	YES	YES
EXTERIOR UNCOVERED FLOOR	YES	YES

### ADDITIONAL INFORMATION

PLEASE VISIT [GLAZZIOSURFACES.COM](http://GLAZZIOSURFACES.COM) FOR ADDITIONAL PRODUCT INFORMATION INCLUDING INSTALLATION INSTRUCTIONS AND CARE & MAINTENANCE GUIDELINES.

ACTUAL COLOR, SIZE, AND TEXTURE MAY VARY. PLEASE REFER TO SAMPLE CHIP FOR VISUAL ACCURACY.

glazzio®  
**SURFACES**