

COLLECTION KESSEL

COLOR NOLLAN 3x12

ITEM NUMBER **KES6304**
APPLICATION **WALL**



PRODUCT INFO

TILE SIZE	3" X 12"
MATERIAL	CERAMIC
FINISH	GLOSSY
THICKNESS	7.8 MM
EDGE	PRESSED
FACES	1
VARIATION	V1 UNIFORM
COUNTRY OF ORIGIN	VIETNAM

CERTIFICATIONS

TESTING

DCOF WET	-
ABRASION ASTM C1027	3
BREAKING STRENGTH ASTM C648	0.86 KN
CHEMICAL RESISTANCE ASTM C650	CLASS A
STAIN RESISTANCE ASTM C1378	CLASS A
WATER ABSORPTION UNI EN ISO 10545/3	14% - 18%
VOC	VOC FREE
RECYCLED CONTENT	7%
FROST RESISTANT	NO
HEAT RESISTANT	YES (< 356° F)
DIRECT SUNLIGHT	NO

INSTALLATION

RECOMMENDED GROUT JOINT	1/8"
SEALING REQUIRED	NO
SEALING RECOMMENDED	YES
RECOMMENDED PATTERNS	STACKED, BOND, HERRINGBONE, BASKETWEAVE

PACKAGING

SOLD BY	BOX
PIECES/BOX	50
SQFT/BOX	12.16 SF
SQFT/PIECE	0.24 SF
WEIGHT/BOX	

USAGE

COMMERCIAL FLOORS	NO
RESIDENTIAL FLOORS	NO
RAMPS & INCLINES	NO
SHOWER WALL	YES
SHOWER FLOOR	NO
STEAM/SAUNA WALL	NO
STEAM/SAUNA FLOOR	NO
FIREPLACE SURROUND	NO

POOL USAGE

POOL DECK	NO
POOL WATERLINE	NO
POOL SUBMERGED	NO
SPA/HOT TUB	NO

EXTERIOR USAGE	FREEZING	NON-FREEZING
EXTERIOR COVERED WALL	NO	NO
EXTERIOR UNCOVERED WALL	NO	NO
EXTERIOR COVERED FLOOR	NO	NO
EXTERIOR UNCOVERED FLOOR	NO	NO

ADDITIONAL INFORMATION

PLEASE VISIT GLAZZIOSURFACES.COM FOR ADDITIONAL PRODUCT INFORMATION INCLUDING INSTALLATION INSTRUCTIONS AND CARE & MAINTENANCE GUIDELINES. ACTUAL COLOR, SIZE, AND TEXTURE MAY VARY. PLEASE REFER TO SAMPLE CHIP FOR VISUAL ACCURACY.

glazzio®
SURFACES