

# COLLECTION KESSEL

## COLOR OVO MUDCAP 2x6

ITEM NUMBER **KES6321**

APPLICATION **WALL**

### PRODUCT INFO

TILE SIZE	2" X 6" MUDCAP
MATERIAL	CERAMIC
FINISH	GLOSSY
THICKNESS	7.8 MM
EDGE	PRESSED
FACES	1
VARIATION	V1 UNIFORM
COUNTRY OF ORIGIN	VIETNAM
CERTIFICATIONS	

### TESTING

DCOF WET	-
ABRASION ASTM C1027	3
BREAKING STRENGTH ASTM C648	0.86 KN
CHEMICAL RESISTANCE ASTM C650	CLASS A
STAIN RESISTANCE ASTM C1378	CLASS A
WATER ABSORPTION UNI EN ISO 10545/3	14% - 18%
VOC	VOC FREE
RECYCLED CONTENT	7%
FROST RESISTANT	NO
HEAT RESISTANT	YES (< 356° F)
DIRECT SUNLIGHT	NO

### INSTALLATION

RECOMMENDED GROUT JOINT	1/8"
SEALING REQUIRED	NO
SEALING RECOMMENDED	YES
RECOMMENDED PATTERNS	STACKED, BOND, HERRINGBONE, BASKETWEAVE

### PACKAGING

SOLD BY	EA
PIECES/BOX	60
LINEAL FT/BOX	29.55 LF
LINEAL FT/PIECE	0.49 LF
WEIGHT/BOX	



### USAGE

COMMERCIAL FLOORS	NO
RESIDENTIAL FLOORS	NO
RAMPS & INCLINES	NO
SHOWER WALL	YES
SHOWER FLOOR	NO
STEAM/SAUNA WALL	NO
STEAM/SAUNA FLOOR	NO
FIREPLACE SURROUND	NO

### POOL USAGE

POOL DECK	NO
POOL WATERLINE	NO
POOL SUBMERGED	NO
SPA/HOT TUB	NO

### EXTERIOR USAGE

	FREEZING	NON-FREEZING
EXTERIOR COVERED WALL	NO	NO
EXTERIOR UNCOVERED WALL	NO	NO
EXTERIOR COVERED FLOOR	NO	NO
EXTERIOR UNCOVERED FLOOR	NO	NO

### ADDITIONAL INFORMATION

PLEASE VISIT [GLAZZIOSURFACES.COM](http://GLAZZIOSURFACES.COM) FOR ADDITIONAL PRODUCT INFORMATION INCLUDING INSTALLATION INSTRUCTIONS AND CARE & MAINTENANCE GUIDELINES.

ACTUAL COLOR, SIZE, AND TEXTURE MAY VARY. PLEASE REFER TO SAMPLE CHIP FOR VISUAL ACCURACY.

glazzio®  
**SURFACES**