COLLECTION SECRET SAUCE COLOR GRAYVY

ITEM NUMBER SECGR12X24M APPLICATION FLOOR, WALL

PRODUCT INFO

ACTUAL SIZE12" X 24MATERIALCOLORBODY PORCELAINFINISHMATTERTHICKNESS9 MMRECTIFIEDYESFACES3 GVARIATIONVCOUNTRY OF ORIGINUSACERTIFICATION20% RECYCLED MATERIALTESTING20% RECYCLED MATERIALDCOF WET≥ 0.42BREAKING STRENGTH> 40 N/MMASTM C648COMPLIANTCHEMICAL RESISTANCECLASS GASTM C650UNAFFECTEDWATER ABSORPTIONNONEASTM C373COMPLIANTVOCVOC FREERECYCLED CONTENT20%FROST RESISTANTYESINSTALLATIONNORECOMMENDED GROUT JOINT3/16SEALING REQUIREDNCSEALING RECOMMENDEDYESRECOMMENDED PATTERNSNO MORE THAN 30% OFFSET FOR STAGGERELPACKAGINGBODPIECES/BOX2	PRODUCT INFO	
MATERIALCOLORBODY PORCELAIMFINISHMATTERTHICKNESS9 MMRECTIFIEDYESFACES30VARIATIONVCOUNTRY OF ORIGINUSACERTIFICATION20% RECYCLED MATERIALTESTINGDCOF WETDCOF WET2 0.42BREAKING STRENGTH> 40 N/MMASTM C648COMPLIANTCHEMICAL RESISTANCECLASS 6ASTM C650UNAFFECTEDWATER ABSORPTIONNOMEASTM C373COMPLIANTVOCVOC FREERECYCLED CONTENT20%FROST RESISTANTYESINSTALLATIONNORECOMMENDED GROUT JOINT3/16SEALING REQUIREDNOSEALING RECOMMENDEDYESFROST RESISTANTYESPACKAGINGNO MORE THAN 30% OFFSET FOR STAGGERELPACKAGINGBOXPIECES/BOX2	NOMINAL SIZE	12" X 24"
FINISHMATTERTHICKNESS9 MMRECTIFIEDYESFACES3 GVARIATIONVCOUNTRY OF ORIGINUSACERTIFICATION20% RECYCLED MATERIALTESTINGDCOF WETDCOF WET2 0.42BREAKING STRENGTH> 40 N/MMASTM C648COMPLIANTCHEMICAL RESISTANCECLASS 6ASTM C650UNAFFECTEDWATER ABSORPTIONNONEASTM C373COMPLIANTVOCVOC FREERECYCLED CONTENT20%FROST RESISTANTYESINSTALLATIONNORECOMMENDED GROUT JOINT3/16SEALING REQUIREDNONO MORE THAN 30% OFFSET FOR STAGGERELNO MORE THAN 30% OFFSET FOR STAGGERELPACKAGINGBODPIECES/BOX7	ACTUAL SIZE	12" X 24"
THICKNESS9 MMRECTIFIEDYESFACES3 GVARIATIONVCOUNTRY OF ORIGINUSACERTIFICATION20% RECYCLED MATERIALTESTINGDCOF WETDCOF WET≥ 0.42BREAKING STRENGTH> 40 N/MMASTM C648COMPLIANTCHEMICAL RESISTANCECLASS SASTM C650UNAFFECTEDWATER ABSORPTIONNONEASTM C373COMPLIANTVOCVOC FREERECYCLED CONTENT20%FROST RESISTANTYESDIRECT SUNLIGHTYESINSTALLATIONNO MORE THAN 30% OFFSETRECOMMENDED GROUT JOINT3/16SEALING REQUIREDNONO MORE THAN 30% OFFSETPACKAGINGBOXPIECES/BOX7	MATERIAL	COLORBODY PORCELAIN
RECTIFIEDYESFACES30VARIATIONVCOUNTRY OF ORIGINUSACERTIFICATION20% RECYCLED MATERIALTESTINGDCOF WETDCOF WET≥ 0.42BREAKING STRENGTH> 40 N/MMASTM C648COMPLIANTCHEMICAL RESISTANCECLASS SASTM C650UNAFFECTEDWATER ABSORPTIONNONEASTM C373COMPLIANTVOCVOC FREERECYCLED CONTENT20%FROST RESISTANTYESINSTALLATIONNORECOMMENDED GROUT JOINT3/16SEALING REQUIREDNCSEALING REQUIREDNONO MORE THAN 30% OFFSET FOR STAGGERED PATTERNPACKAGINGBOXPIECES/BOX2	FINISH	MATTE
FACES30VARIATIONVCOUNTRY OF ORIGINUSACERTIFICATION20% RECYCLED MATERIALTESTINGDCOF WETDCOF WET≥ 0.42BREAKING STRENGTH> 40 N/MMASTM C648COMPLIANTCHEMICAL RESISTANCECLASS GASTM C650UNAFFECTEDWATER ABSORPTIONNONEASTM C373COMPLIANTVOCVOC FREERECYCLED CONTENT20%FROST RESISTANTYESINSTALLATIONNORECOMMENDED GROUT JOINT3/16SEALING REQUIREDNOSEALING REQUIREDNONO MORE THAN 30% OFFSET FOR STAGGEREL PATTERNPACKAGINGBOXPIECES/BOX2	THICKNESS	9 MM
VARIATIONVCOUNTRY OF ORIGINUSACERTIFICATION20% RECYCLED MATERIALTESTINGDCOF WET≥ 0.42BREAKING STRENGTH> 40 N/MMASTM C648COMPLIANTCHEMICAL RESISTANCECLASS 5ASTM C650UNAFFECTEDWATER ABSORPTIONNONEASTM C373COMPLIANTVOCVOC FREERECYCLED CONTENT20%FROST RESISTANTYESDIRECT SUNLIGHTYESINSTALLATIONNO MORE TIANRECOMMENDED GROUT JOINT3/16SEALING REQUIREDNO MORE THANSOLD BYBOXPIECES/BOX2	RECTIFIED	YES
COUNTRY OF ORIGINUSACERTIFICATION20% RECYCLED MATERIALTESTINGDCOF WETDCOF WET≥ 0.42BREAKING STRENGTH> 40 N/MMASTM C648COMPLIANTCHEMICAL RESISTANCECLASS 6ASTM C650UNAFFECTEDWATER ABSORPTIONNONEASTM C373COMPLIANTVOCVOC FREERECYCLED CONTENT20%FROST RESISTANTYESINSTALLATIONNORECOMMENDED GROUT JOINT3/16SEALING REQUIREDNOSEALING REQUIREDYESRECOMMENDED PATTERNSNO MORE THAN 30% OFFSET FOR STAGGEREDPACKAGINGSOLD BYPIECES/BOX2	FACES	30
CERTIFICATION20% RECYCLED MATERIALTESTINGDCOF WET ≥ 0.42 BREAKING STRENGTH > 40 N/MMASTM C648COMPLIANTCHEMICAL RESISTANCECLASS SASTM C650UNAFFECTEDWATER ABSORPTIONNONEASTM C373COMPLIANTVOCVOC FREERECYCLED CONTENT20%FROST RESISTANTYESHEAT RESISTANTYESDIRECT SUNLIGHTYESINSTALLATIONNO MORE THAN 30% OFFSET FOR STAGGEREDRECOMMENDED GROUT JOINT3/16SEALING REQUIREDNOSEALING RECOMMENDEDYESFOR STAGGEREDNO MORE THAN 30% OFFSET FOR STAGGEREDPACKAGINGBOXPIECES/BOX2	VARIATION	V1
TESTING DCOF WET ≥ 0.42 BREAKING STRENGTH > 40 N/MM ASTM C648 COMPLIANT CHEMICAL RESISTANCE CLASS 5 ASTM C650 UNAFFECTED WATER ABSORPTION NONE ASTM C373 COMPLIANT VOC VOC FREE RECYCLED CONTENT 20% FROST RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION NO RECOMMENDED GROUT JOINT 3/16 SEALING REQUIRED NO SEALING RECOMMENDED YES FOR STAGGERED NO MORE THAN SEALING RECOMMENDED YES FOR STAGGERED NO MORE THAN SEALING REQUIRED NO MORE THAN SEALING RECOMMENDED YES FOR STAGGERED PATTERN PACKAGING SOLD BY BOX PIECES/BOX 2	COUNTRY OF ORIGIN	USA
DCOF WET ≥ 0.42 BREAKING STRENGTH > 40 N/MM ASTM C648 COMPLIANT CHEMICAL RESISTANCE CLASS S ASTM C650 UNAFFECTED WATER ABSORPTION NONE ASTM C373 COMPLIANT VOC VOC FREE RECYCLED CONTENT 20% FROST RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION NO MORE THAN RECOMMENDED GROUT JOINT 3/16 SEALING REQUIRED NO SEALING REQUIRED NO MORE THAN SEALING REQUIRED NO MORE THAN SEALING REQUIRED NO MORE THAN SOLD BY BOX PIECES/BOX 2	CERTIFICATION	20% RECYCLED MATERIAL
BREAKING STRENGTH > 40 N/MM ASTM C648 COMPLIANT CHEMICAL RESISTANCE CLASS S ASTM C650 UNAFFECTED WATER ABSORPTION NOME ASTM C373 COMPLIANT VOC VOC FREE RECYCLED CONTENT 20% FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION NO RECOMMENDED GROUT JOINT 3/16 SEALING REQUIRED NC SEALING REQUIRED NC RECOMMENDED PATTERNS NO MORE THAN 30% OFFSET FOR STAGGERED PACKAGING SOLD BY BOX	TESTING	
ASTM C648 COMPLIANT CHEMICAL RESISTANCE CLASS 5 ASTM C650 UNAFFECTED WATER ABSORPTION NONE ASTM C373 COMPLIANT VOC VOC FREE RECYCLED CONTENT 20% FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16 SEALING REQUIRED NO SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS NO MORE THAM 30% OFFSET FOR STAGGEREL PATTERN PACKAGING SOLD BY BOX	DCOF WET	≥ 0.42
CHEMICAL RESISTANCECLASS SASTM C650UNAFFECTEDWATER ABSORPTIONNONEASTM C373COMPLIANTVOCVOC FREERECYCLED CONTENT20%FROST RESISTANTYESHEAT RESISTANTYESDIRECT SUNLIGHTYESINSTALLATIONNORE THAN 30% OFFSET FOR STAGEREDRECOMMENDED GROUT JOINT3/16SEALING REQUIREDNOSEALING RECOMMENDEDYESFOR STAGEREDNO MORE THAN 30% OFFSET FOR STAGERED PATTERNPACKAGINGSOLD BYPIECES/BOX7	BREAKING STRENGTH	> 40 N/MM ²
ASTM C650 UNAFFECTED WATER ABSORPTION NONE ASTM C373 COMPLIANT VOC VOC FREE RECYCLED CONTENT 20% FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16 SEALING REQUIRED NO SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS NO MORE THAM 30% OFFSET FOR STAGGERED PATTERN PACKAGING SOLD BY BOX	ASTM C648	COMPLIANT
WATER ABSORPTION NONE ASTM C373 COMPLIANT VOC VOC FREE RECYCLED CONTENT 20% FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION 3/16 SEALING REQUIRED NC SEALING REQUIRED NC SEALING RECOMMENDED YES FOR STAGGEREU PACKAGING SOLD BY BOX PIECES/BOX 7	CHEMICAL RESISTANCE	CLASS 5
ASTM C373 COMPLIANT VOC VOC FREE RECYCLED CONTENT 20% FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16 SEALING REQUIRED NO SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS NO MORE THAN 30% OFFSET FOR STAGGERED PATTERN PACKAGING SOLD BY BOX	ASTM C650	UNAFFECTED
VOC VOC FREE RECYCLED CONTENT 20% FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION 13/16 SEALING REQUIRED NO SEALING REQUIRED NO SEALING RECOMMENDED YES PACKAGING 20% SOLD BY BOX	WATER ABSORPTION	NONE
RECYCLED CONTENT 20% FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT SEALING REQUIRED NC SEALING RECOMMENDED YES RECOMMENDED PATTERNS NO MORE THAN 30% OFFSET FOR STAGGERED PACKAGING SOLD BY PIECES/BOX 7	ASTM C373	COMPLIANT
FROST RESISTANT YES HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION INSTALLATION RECOMMENDED GROUT JOINT 3/16 SEALING REQUIRED NC SEALING RECOMMENDED YES RECOMMENDED PATTERNS NO MORE THAN 30% OFFSET FOR STAGGERED PATTERN PACKAGING BOX PIECES/BOX 7	VOC	VOC FREE
HEAT RESISTANT YES DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT RECOMMENDED GROUT JOINT 3/16 SEALING REQUIRED NC SEALING RECOMMENDED YES RECOMMENDED PATTERNS NO MORE THAN 30% OFFSET FOR STAGGEREL PATTERN PACKAGING SOLD BY PIECES/BOX 7	RECYCLED CONTENT	20%
DIRECT SUNLIGHT YES INSTALLATION RECOMMENDED GROUT JOINT 3/16 SEALING REQUIRED NC SEALING RECOMMENDED YES RECOMMENDED PATTERNS NO MORE THAN 30% OFFSET FOR STAGGERED PATTERN PACKAGING SOLD BY PIECES/BOX 7	FROST RESISTANT	YES
INSTALLATION RECOMMENDED GROUT JOINT 3/16 SEALING REQUIRED NC SEALING RECOMMENDED YES RECOMMENDED PATTERNS NO MORE THAN 30% OFFSET FOR STAGGEREL PATTERN PACKAGING SOLD BY BOX	HEAT RESISTANT	YES
RECOMMENDED GROUT JOINT 3/16 SEALING REQUIRED NO SEALING RECOMMENDED YES RECOMMENDED PATTERNS NO MORE THAN 30% OFFSET FOR STAGGEREL PATTERN PACKAGING SOLD BY PIECES/BOX 7	DIRECT SUNLIGHT	YES
SEALING REQUIRED NC SEALING RECOMMENDED YES RECOMMENDED PATTERNS NO MORE THAN 30% OFFSET FOR STAGGERED PATTERN PACKAGING SOLD BY BOX	INSTALLATION	
SEALING RECOMMENDED YES RECOMMENDED PATTERNS NO MORE THAN 30% OFFSET FOR STAGGEREL PATTERN PACKAGING SOLD BY BOX PIECES/BOX 7	RECOMMENDED GROUT J	IOINT 3/16"
RECOMMENDED PATTERNS NO MORE THAN 30% OFFSET FOR STAGGEREL PATTERN PACKAGING SOLD BY BOX	SEALING REQUIRED	NO
30% OFFSET FOR STAGGERED PATTERN SOLD BY BOX PIECES/BOX	SEALING RECOMMENDED	YES
SOLD BY BOX	RECOMMENDED PATTERN	NS NO MORE THAN 30% OFFSET FOR STAGGERED PATTERN
PIECES/BOX 7	PACKAGING	
	SOLD BY	BOX
SQFT/BOX 13.56 SF	PIECES/BOX	7
	SQFT/BOX	13.56 SF



USAGE

COMMERCIAL FLOORS	YES
RESIDENTIAL FLOORS	YES
RAMPS & INCLINES	NO
SHOWER WALL	YES
SHOWER FLOOR	YES
STEAM/SAUNA WALL	YES
STEAM/SAUNA FLOOR	NO
FIREPLACE	YES

POOL USAGE

POOLUSAGE		
POOL DECK		NO
POOL WATERLINE		YES
POOL SUBMERGED	٢	YES (WALL ONLY)
SPA/HOT TUB		YES
EXTERIOR USAGE	FREEZING	NON-FREEZING
EXTERIOR COVERED WALL	YES	YES
EXTERIOR UNCOVERED	YES	YES
EXTERIOR COVERED FLOOR	NO	NO
EXTERIOR UNCOVERED FLOOR	NO	NO

ADDITIONAL INFORMATION

1.94 SF

53.5 LBS

PLEASE VISIT **GLAZZIOSURFACES.COM** FOR ADDITIONAL PRODUCT INFORMATION INCLUDING INSTALLATION INSTRUCTIONS AND CARE & MAINTENANCE GUIDELINES. ACTUAL COLOR, SIZE, AND TEXTURE MAY VARY. PLEASE REFER TO SAMPLE CHIP FOR VISUAL ACCURACY.

S Jazzic S

SQFT/PIECE

WEIGHT/BOX