

# COLLECTION SMOOTH OPERATOR

## COLOR BLUE ONYX

ITEM NUMBER **SMOBU48X110P**

APPLICATION **FLOOR, WALL**

### PRODUCT INFO

NOMINAL SIZE	48" X 110"
ACTUAL SIZE	47.25" X 109.44"
MATERIAL	PORCELAIN SLAB
FINISH	POLISHED
THICKNESS	6.5 MM
RECTIFIED	YES
FACES	6
VARIATION	V4
COUNTRY OF ORIGIN	ITALY (STOCKED IN U.S.)

### CERTIFICATION

### TESTING

DCOF WET	-
BREAKING STRENGTH	> 2000 N
UNI EN ISO 10545/4	≥ 45 N/MM <sup>2</sup>
CHEMICAL RESISTANCE	A - LA - HA UNAFFECTED
UNI EN ISO 10545/13	
STAIN RESISTANCE	CLASS 5
UNI EN ISO 10545/14	
WATER ABSORPTION	COMPLIANT
ASTM C373	
ABRASION	3
ASTM C1027	
VOC	NONE
RECYCLED CONTENT	NO
FROST RESISTANT	YES
HEAT RESISTANT	NO
DIRECT SUNLIGHT	YES

### INSTALLATION

RECOMMENDED GROUT JOINT	3/16"
SEALING REQUIRED	NO
SEALING RECOMMENDED	YES
RECOMMENDED PATTERNS	STACKED; BOND; NO MORE THAN 30% OFFSET FOR STAGGERED PATTERN

### PACKAGING

SOLD BY	SLAB
DELIVERY	A-FRAME
A-FRAME CAPACITY	13-14 SLABS

2361 NOSTRAND AVE #301  
BROOKLYN, NY 11210  
INFO@GLAZZIOSURFACES.COM  
(718) 663-4747



### USAGE

COMMERCIAL FLOORS	LIGHT COMMERCIAL
RESIDENTIAL FLOORS	YES
RAMPS & INCLINES	NO
SHOWER WALL	YES
SHOWER FLOOR	NO
STEAM/SAUNA WALL	YES
STEAM/SAUNA FLOOR	NO
FIREPLACE	YES

### POOL USAGE

POOL DECK	NO
POOL WATERLINE	YES
POOL SUBMERGED	YES
SPA/HOT TUB	YES

### EXTERIOR USAGE

	FREEZING	NON-FREEZING
EXTERIOR COVERED WALL	YES	YES
EXTERIOR UNCOVERED WALL	YES	YES
EXTERIOR COVERED FLOOR	NO	NO
EXTERIOR UNCOVERED FLOOR	NO	NO

### ADDITIONAL INFORMATION

PLEASE VISIT [GLAZZIOSURFACES.COM](http://GLAZZIOSURFACES.COM) FOR ADDITIONAL PRODUCT INFORMATION INCLUDING INSTALLATION INSTRUCTIONS AND CARE & MAINTENANCE GUIDELINES.

ACTUAL COLOR, SIZE, AND TEXTURE MAY VARY. PLEASE REFER TO SAMPLE CHIP FOR VISUAL ACCURACY.

glazzio®  
**SURFACES**