

# COLLECTION TWIGGY

## COLOR MELLOW PAVER

ITEM NUMBER **TWIME16X48PVN**  
APPLICATION **FLOOR**



### PRODUCT INFO

NOMINAL SIZE	16" X 48"
ACTUAL SIZE	15.75" X 47.24"
MATERIAL	COLOR BODY PORCELAIN
FINISH	NATURAL
THICKNESS	20 MM
VARIATION	V3 MODERATE
COUNTRY OF ORIGIN	ITALY
CERTIFICATIONS	CERAMICS OF ITALY

### TESTING

DCOF WET	≥ 0.60
BREAKING STRENGTH	-50 N/mm <sup>2</sup>
UNI EN ISO 10545/4	
CHEMICAL RESISTANCE	GA
UNI EN ISO 10545/13	
STAIN RESISTANCE	CLASS 5
UNI EN ISO 10545/14	
WATER ABSORPTION	- 0.1%
UNI EN ISO 10545/3	
VOC	NONE
RECYCLED CONTENT	NO
FROST RESISTANT	YES
HEAT RESISTANT	YES
DIRECT SUNLIGHT	YES

### INSTALLATION

RECOMMENDED GROUT JOINT	3/16"
SEALING REQUIRED	NO
SEALING RECOMMENDED	YES
RECOMMENDED PATTERNS	STACKED, BOND, NO MORE THAN 30% OFFSET FOR STAGGERED PATTERN

### PACKAGING

SOLD BY	BOX
PIECES/BOX	1
SQFT/BOX	5.17 SF
SQFT/PIECE	5.17 SF
WEIGHT/BOX	47.36 LBS

### USAGE

COMMERCIAL FLOORS	YES
RESIDENTIAL FLOORS	YES
RAMPS & INCLINES	NO
SHOWER WALL	YES
SHOWER FLOOR	YES
STEAM/SAUNA WALL	YES
STEAM/SAUNA FLOOR	YES
FIREPLACE	YES

### POOL USAGE

POOL DECK	YES
POOL WATERLINE	YES
POOL SUBMERGED	YES
SPA/HOT TUB	YES

EXTERIOR USAGE	FREEZING	NON-FREEZING
EXTERIOR COVERED WALL	YES	YES
EXTERIOR UNCOVERED WALL	YES	YES
EXTERIOR COVERED FLOOR	YES	YES
EXTERIOR UNCOVERED FLOOR	YES	YES

### ADDITIONAL INFORMATION

PLEASE VISIT [GLAZZIOSURFACES.COM](http://GLAZZIOSURFACES.COM) FOR ADDITIONAL PRODUCT INFORMATION INCLUDING INSTALLATION INSTRUCTIONS AND CARE & MAINTENANCE GUIDELINES. ACTUAL COLOR, SIZE, AND TEXTURE MAY VARY. PLEASE REFER TO SAMPLE CHIP FOR VISUAL ACCURACY.

glazzio®  
**SURFACES**