Attention Please Read If Your RV Came Prewired ~

Guidance for MV-BC1 Wireless RV Camera System Setup in Prewired RVs

If your recreational vehicle (RV) is pre-wired for the MV-BC1 Wireless RV Camera System, please carefully review the following instructions to ensure a smooth setup and pairing process.

Please note that the camera within this system operates by utilizing the power supplied by your RV's exterior lights. These lights are commonly energized by the tow vehicle. The power source for the camera can be derived from various lighting functions, such as parking lights, reverse lights, running lights, or head lights.

Pairing Procedure for Pre-Wired Systems:

Please take note that before starting the pairing procedure, it is imperative to ensure that the exterior lights are switched off. This step ensures that the camera is not receiving power at the initiation of the pairing process.

Follow the steps listed below to pair your camera with the monitor:

- 1. Hold the menu button on your monitor.
- 2. Select 'Cam 1' from the available options.
- 3. Tap the screen selection button, located to the left of the power button.
- 4. After the pairing countdown begins, turn on your RV's exterior lights.
- 5. Once the exterior lights power up the camera, the pairing process will conclude successfully.

In case you encounter any difficulties during this process, do not hesitate to reach out to our Technical Support Department for assistance. We are readily available to provide you with the necessary help and guidance.

You can reach to us via:

Telephone: 1-800-735-2000

Email: TechSupport@Magnadyne.com

Thank you for choosing Magnadyne for your RV needs. We look forward to serving you.