



.6 HP Chiller

WIFI APP

Max/Min Temperature Exposure
Recommended Max: 90F
Recommended Min: 32F

20 Micron Filtration

Chills Down to 37°F / 3°C
Heats Up to 85°F / 30°C

Cooling Speed
(Pending on Ambient Temperature)
(80 to 120 Gallon of Water)
1-3°F every 40 min

Automated Ozone Sanitation

GFCI Protection

Includes:
Hose Kit, Filter Wrench, & 2 Filter Cartridge Replacement

Dimensions (WxDxH)
17"x12"x19"

Shipping Dimensions (WxDxH)
23"x17"x24"

Weight: 75 lbs
Shipping Weight: 80 lbs
Model: DCT-SY-06-HC



.8 HP Chiller

WIFI APP

Max/Min Temperature Exposure
Recommended Max: 95F
Recommended Min: 32F

20 Micron Filtration

Chills Down to 37°F / 3°C
Heats Up to 85°F / 30°C

Cooling Speed (Estimated)
(Pending on Ambient Temperature)
(80 to 120 Gallon of Water)
1-3°F every 30 min

Automated Ozone Sanitation

GFCI Protection

Includes:
Hose Kit, Filter Wrench, & 2 Filter Cartridge Replacement

Dimensions (WxDxH)
19"x14"x22"

Shipping Dimensions (WxDxH)
23"x17"x24"

Weight: 80 lbs
Shipping Weight: 85 lbs
Model: DCT-SY-08-HC



1.0 HP Chiller

WIFI APP

Max/Min Temperature Exposure
Recommended Max: 100F
Recommended Min: 32F

20 Micron Filtration

Chills Down to 37°F / 3°C
Heats Up to 85°F / 30°C

Cooling Speed (Estimated)
(Pending on Ambient Temperature)
(80 to 120 Gallon of Water)
1-3°F every 20 min

Automated Ozone Sanitation

GFCI Protection

Includes:
Hose Kit, Filter Wrench, & 2 Filter Cartridge Replacement

Dimensions (WxDxH)
21"x15"x22"

Shipping Dimensions (WxDxH)
25"x18"x24"

Weight: 89 lbs
Shipping Weight: 94 lbs
Model: DCT-SY-10-HC