

FAZE Series Component Sets

FC6


General Features:


- * Heavy Gauge Steel Powder Coated Basket With MASSIVE Punched Logo
- * High-Energy Y30 Magnets Assures Sufficient Magnet Force Needed For High Sensitivity And Accurate Sound Reproduction
- * Two Piece Custom Paintable Metal Grills
- * Woven Fibre Paper Cone With Butyl Rubber Surround
- * High Quality Cloth Spider With Polyester Fibre
- * 1" High Temperature ASV Voice Coil
- * 25mm Silk Diaphragm Tweeter With Ferro Fluid Cooled V.C.
- * Custom Competition Grade 12 dB Crossover With MASSIVE Logo (Kit)


Specifications:

Model	FC6
Woofer Size	6.5"
Tweeter Size	25mm
Frequency Range	50-20KHz
SPL@2.83V/1m	93dB
Watts RMS	150W
Maximum Power	300W
Peak Power	600W
Impedance	40HM
Frame Diamter	6.5"
Mounting Depth	2.4"
Mounting Diameter	5.65"

FC6














P.O. BOX 252004 LOS ANGELES, CA 90025 U.S.A.




FAZE Series Coaxial Speakers

FC6X

General Features:

- * Heavy Gauge Steel Basket With Thick Powder Coating, MASSIVE Punched Logo
- * Custom Made Massive Logo 2 Way Tweeter Plate
- * High-Energy Y35 Magnets Assure Sufficient Magnet Force Needed
- * Two Piece Custom Paintable Metal Grills
- * Rugged Construction To Withstand Harsh Mobile Environment
- * Woven Fibre Paper Cone With Butyl Rubber Surround
- * High Quality Cloth Spider With Polyester Fiber
- * 1" High Temperature ASV Voice Coil
- * 20mm Silk Diaphragm Tweeter With Ferro Fluid Cooled V.C.
- * Built-In 6dB Crossover
- * Fully Isolated Tinsel Leads To Eliminate Crosstalk
- * Custom Designed Pole Piece For Low Distortion And Sound Quality

FC6X









MADDIVE
P.O. Box 252004 Los Angeles, CA 90025 U.S.A.

Specifications:

Model	FC6X
Woofer Size	6.5"
Tweeter Size	20mm
Frequency Range	58Hz-10KHz
SPL@2.83V/1m	91dB
Watts RMS	75W
Maximum Power	150W
Peak Power	300W
Impedance	40HM
Frame Diamter	6.5"
Mounting Depth	2.4"
Mounting Diameter	5.65"
missiming Diamoloi	0.00