



# GORDO SERIES

3000 Watt RMS / 6000 Watt Max Subwoofers

All GORDO Series model subs use enormous 4" quadruple layered, dual 1 Ohm flat wound aluminum voice coils with Kevlar fiber dust caps and non-pressed paper cones that have stylish red stitching.



MSRP: \$1,199.95 ~ \$1,679.95



## Overview:

The 'MASSIVE MAN' GORDO Series Subwoofers are CEA 2031 compliant and built to be Big, Bad, Beautiful and just perhaps a danger to all mankind.

All three GORDO Series model subs use enormous 4" quadruple layered, dual 1 Ohm flat wound aluminum voice coils with Kevlar fiber dust caps and non-pressed paper cones that have stylish red stitching. They are powered with triple stacked 450oz Hi-Flux Ferrite Magnets that bolt to its heavy die-cast aluminum alloy basket.

GORDO can shake the world and do it while holding 6000 watts. These subwoofers can really pound out some serious pain so you might need to stop and ask yourself; can I really take it?

## Features and Benefits

- Die cast alloy baskets with black textured finish
- Kevlar fiber non-pressed paper cone
- EROM foam surround with red stitching
- 4" 4-layer dual high temp aluminum flat wound voice coils
- Fiberglass woven dust cap
- Direct cooling design T-yoke with black anodized finish
- Triple stacked 450oz high energy magnet
- Triple black poly cotton spiders with mirror image layout
- Customized rubber gasket and magnet boot
- 10 gauge pure copper direct lead connection
- Dual 1 Ohm impedance





# GORDO SERIES

3000 Watt RMS / 6000 Watt Max Subwoofers

All GORDO Series model subs use enormous 4" quadruple layered, dual 1 Ohm flat wound aluminum voice coils with Kevlar fiber dust caps and non-pressed paper cones that have stylish red stitching.



MSRP: \$1,199.95 ~ \$1,679.95

## Specifications

### RMS WATTAGE

- 3000 Watts RMS
- 6000 Watts MAX

### SENSITIVITY

- 101.1dB (12") / 102.2dB (15") / 104.3dB (18")

### FREQUENCY RESPONSE - Fs

- 37.2Hz (12") / 35.87Hz (15") / 34.36Hz (18")

### WOOFER MOUNTING CUT DIAMETER

- 7.11.22" (12") / 13.77" (15") / 16.61" (18")

### WOOFER DISPLACEMENT - ft3

- 0.11 (12") / 0.19 (15") / 0.22 (18")

### MOUNTING DEPTH

- 7.71" (12") / 8.18" (15") / 9.69" (18")

### WOOFER X-MAX

- 15mm

### WOOFER MAGNET

- Triple Stacked 450oz High Energy Ferrite Magnet

### VOICE COIL CONFIGURATION

- Dual 1 Ohm

### QTS - Parallel

- 0.368 (12") / 0.422 (15") / 0.462 (18")

### VAS - Liters

- 18.718 (12") / 49.794 (15") / 88.618 (18")

### WEIGHT - Lbs.

- 26.8 (12") / 27.6 (15") / 28.3 (18")

### WARRANTY

- 90 day limited warranty
- 1-year limited warranty when installed by authorized reseller