



# MK SERIES

## 140 - 300 Watts Component Speakers

**MK Series speakers are the result of pushing the limits of our engineer's imagination. Incredible sound quality is achieved in the form of rich lows, powerful mid ranges and smooth highs**

MSRP: \$74.95 ~ \$249.95



## Overview:

MK Series speakers are the result of pushing the limits of our engineer's imagination. Incredible sound quality is achieved in the form of rich lows, powerful mid ranges and smooth highs.

The compact and efficient MK6 & MK5 Bass/Mid-Range speaker utilizes an ultra-high grade ferrite magnet that allows the design to be as much smaller than standard ferrite-driven motors.

The MK5 & MK6 Series use smooth sounding silk dome tweeters that use an external threaded nut & bolt" mounting system which hold the 1" / 25mm Copper VC and powerful neodymium magnets. The external crossover network is built with high-grade components commonly found in systems costing more than twice as much.

Need more SPL? **MK6R** is a solo 6 inch driver that is perfect for custom installations.

## Features and Benefits

- Heavy gauge steel shallow mount baskets
- High energy Y30 magnets
- Custom competition grade 12dB crossovers
- 1" High temp KSV voice coils
- Custom designed pole piece for low distortion and sound quality
- Woven fiber paper cone with butyl rubber surround
- High sensitivity for efficiency
- 25mm silk diaphragm ferro fluid cooled tweeters
- High quality cloth spider with polyester fiber
- Two piece custom paintable grills





# MK SERIES

## 140 - 300 Watts Component Speakers

**MK Series speakers are the result of pushing the limits of our engineer's imagination. Incredible sound quality is achieved in the form of rich lows, powerful mid ranges and smooth highs**

MSRP: \$74.95 ~ \$249.95



## Specifications

### RMS WATTAGE

- 130w / 260w (MK5) • 150w / 300w (MK6)

### SENSITIVITY

- 83dB (MK5, MK6)

### FREQUENCY RESPONSE

- 60-20Khz (MK5) • 50-20KHz (MK6)

### WOOFER SIZE

- 5.25" (MK5) • 6.5" (MK6)

### TWEETER SIZE

- 25mm

### CROSSOVER POINT

- 2.5KHz

### WOOFER VOICE COIL

- 1 Inch KSV

### TWEETER MAGNET

- Neodymium

### FRAME DIAMETER - INCHES

- 5.08" (MK5) • 6.54" (MK6)

### MOUNTING HOLE DIAMETER - INCHES

- 4.41" (MK5) • 5.59" (MK6)

### MOUNTING DEPTH - INCHES

- 1.85" (MK5) • 2.48" (MK6)

### IMPEDANCE

- 4 OHM

### WARRANTY

- 90 Day limited
- 1-year limited warranty when installed by authorized reseller