



PKS SERIES

250 Watt RMS / 500 Watt Max Pro Component Speakers

Massive takes the guesswork out of designing a professional audio system by providing all the necessary components for you. This ensures that out of the box your new beats will be crisp, clean and loud!



MSRP: \$249.95

Overview:

Bass/Mid-range Unit

The Ultra High Grade Ferrite Magnets used in the PK6S are mounted into a cast aluminum low resonance basket to product a crisp, clean, open playback while offering all this in less that a 2" mounting depth. The custom cloth surrounds with UV treaded paper cones give a "Sonic Signature" that delivers big sound from a small shallow driver.

Component Tweeter

The matched pair of flush mountable 25mm aluminum bullet milled tweeters mounted into high powerful Neodymium magnets that are designed to take "Heat from the Beat" while delivering extended highs.

2-Way Crossover

The 2 external crossover networks are built with high grade film capacitors, large-gage inductors and 6 dB filters that assign what frequencies are to be reproduced for each driver. The result is a well balanced, clean, precise project sound.

Features and Benefits

- Low resonate cast aluminum basket
- 1" / 25-mm copper voice coils
- High grade ferrite magnets (midrange)
- High powered neodymium magnets (tweeters)
- UV treaded paper cones with custom cloth surrounds
- Center mounted "Phase Plug" midrange for better dispersion
- Ultra Shallow Mounting at Less that 2 inches
- SPL @ 1W-100dB
- Phase optimized high grade 6 dB per octave crossovers
- Small footprint of crossover for tight installation requirements
- Included protective, paintable grills





PKS SERIES

250 Watt RMS / 500 Watt Max Pro Component Speakers

Massive takes the guesswork out of designing a professional audio system by providing all the necessary components for you. This ensures that out of the box your new beats will be crisp, clean and loud!



MSRP: \$249.95

Specifications

RMS WATTAGE

- 250 Watts RMS
- 500 Watts Max

SENSITIVITY

- 100dB

FREQUENCY RESPONSE

100Hz - 20KHz

WOOFER SIZE

- 6.5" Paper Cone

TWEETER SIZE

- 25mm Aluminum Pro Driver

CROSSOVER POINT

- 2.5K @ 12dB/Octive

WOOFER VOICE COIL

- 25mm / Copper

TWEETER MAGNET

- Neodymium

FRAME DIAMETER

- 6.57" / 16.7cm

MOUNTING HOLE DIAMETER

- 5.63" / 14.30cm

MOUNTING DEPTH

- 1.99" / 5.05cm

WEIGHT

- 10 Lbs / 4.53 Kg

WARRANTY

- 90 day limited warranty
- 1-year limited warranty when installed by authorized reseller