



TOROX SERIES

1000 Watt RMS / 2000 Watt Max Subwoofers

These beasts weigh in at 2000 Watts MAX Power!
The TORO X Series Subwoofer collection includes:
TOROX 104, TOROX 122, TOROX 124 & TOROX 154.
All models are dual voice coils for multiple impedance wiring options.



MSRP: \$299.95 ~ \$474.95

Overview:

Massive Audio thinks that everyone should “Run with the Bulls”! All ToroX subwoofers were designed to be the “Alpha” breeder of the sonic highway.

Just take a look at the 10 gauge hard wired speaker cables that come with every dual 4 ohm or dual 2 ohm TOROX subwoofer. Black textured finished cast aluminum baskets suspend “Red” double stitched Kevlar Fiber non-pressed paper cones with woven fiberglass dust caps into the deep long throw EROM foam surrounds.

The low mechanical resonant and sonic warmth of ToroX is due to mirrored image triple black poly cotton spiders with customized rubber gaskets and low resonance magnet boots.

The combinations of materials like black anodized enhanced Cooling T-Yokes and Triple Stacked 180oz Magnets that house a 3 inch 4-layer voice coil that can hold up to 2,000 Watts of Peak power makes any Bull See Red!

Features and Benefits

- Die cast basket with black textured finish
- Kevlar fiber non-pressed paper cone
- EROM foam surround with red stitching
- 3” 4-layer hi-temp voice coils
- Fiberglass woven dustcap
- Enhanced cooling T-Yoke design with black anodized finish
- Triple stacked 180oz high energy magnets
- Triple black poly cotton spiders with mirror image layout
- Customized rubber gasket and magnet boot
- 10 gauge power cable direct lead connection
- Dual 4 ohm or Dual 2 ohm impedance





TOROX SERIES

1000 Watt RMS / 2000 Watt Max Subwoofers

These beasts weigh in at 2000 Watts MAX Power!
The TOROX Series Subwoofer collection includes:
TOROX 104, TOROX 122, TOROX 124 & TOROX 154.
All models are dual voice coils for multiple
impedance wiring options.



MSRP: \$299.95 ~ \$474.95

Specifications

RMS WATTAGE

- 1000 Watts RMS
- 2000 Watts MAX

SENSITIVITY

- 86.5dB (104) / 87.3dB (122) / 86.8dB (124) / 88.7dB (154)

FREQUENCY RESPONSE - Fs

- 40.2Hz (104) / 37.2Hz (122) / 36.4Hz (124) / 36Hz (154)

WOOFER MOUNTING CUT DIAMETER

- 9.21" (104) / 11.14" (122) / 11.14" (124) / 13.86" (154)

WOOFER DISPLACEMENT - ft3

- 0.058 (104) / 0.087 (122) / 0.087 (124) / 0.158 (154)

MOUNTING DEPTH

- 6.10" (104) / 6.77" (122) / 6.77" (124) / 7.91" (154)

WOOFER X-MAX

- 14mm

WOOFER MAGNET

- Triple Stacked 180oz High Energy Ferrite Magnets

VOICE COIL CONFIGURATION

- Dual 4 (104) / Dual 2 (122) / Dual 4 (124) / Dual 4 (154)

QTS - Parallel

- 0.64 (104) / 0.55 (122) / 0.67 (124) / 0.71 (154)

VAS - Liters

- 10.2 (104) / 22.2 (122) / 23.5 (124) / 46.9 (154)

WEIGHT - Lbs.

- 27.85 (104) / 29.30 (122) / 29.00 (124) / 31.00 (154)

WARRANTY

- 90 day limited warranty
- 1-year limited warranty when installed by authorized reseller