

ANETA LIGHTING

LIGHTS FOR HOME AND WORK SINCE 1947

EKETORP

19815

www.aneta.se

www.aneta.no

SE: Rengöring: Torkas med torr trasa.
 NO: Rengjøring: Tørkes av med tørr klut.
 FI: Puhdistus: Pyyhi kuivalla liinalla.
 EN: Cleaning: Wipe with a dry cloth.

SE: Denna produkt innehåller en ljuskälla med energieffektivitetsklass F. Lysdioden i armaturen är inte utbyttbar, när ljuskällans livstid är slut ska hela armaturen bytas. 50000 tim ≈ 20 år (6 tim/dag)

NO: Dette produktet inneholder en lyskilde med energieffektivitetsklasse F. Diodelyskilden i armaturen er ikke utskiftbar, når lyskildens levetid er slutt skal hele armaturen byttes. 50000 tim ≈ 20 år (6 tim/dag)

FI: Tämä tuote sisältää valonlähteen, jonka energiatehokkuusluokka on F. Valaisimen valolähde ei ole vaihdettavissa. Kun valonlähteen elinkaari on loppu niin koko valaisin on vaihdettava. 50 000 tuntia ≈ 20 vuotta (6 t/päivä)

EN: This product contains a light source of energy efficiency class F. The diode lamp of vthis luminaire is not replaceable; when the light source reaches its end of life the whole luminaire shall be replaced. 50000 h ≈ 20 years (6 h/day)

Light Source :

Lighting technology used: LED	CCT colour temperature:.....3000 K
Mains or non-mains: non-mains	On-mode power: 2,85 W
Directional or non-directional: non-directional	Stand-by power: 0 W
Connected L.S.: no	Networked standby power: .. 0 W
Color-tuneable: no	CRI: ≥ 80
Envelope:no	R9 color rendering index: 0
High luminance:no	Chromaticity coordinates: x:0.446, y:0.410
Anti-glare shield:no	SDCM: < 6
Dimmable:yes	Lifetime L ₇₀ ,B ₅₀ : 50 000 hours
Energy consumption in on-mode: 3 kWh / 1000 h	Lumen maintenance factor: 0,96
Energy efficiency class (A-G): F	Survival factor: 0,90
Useful luminous flux:..... 285 lm	Measures LxBxH: mm
CCT colour temperature:..... 2700 K	Supply current: 300 mA CC

* The luminous flux stated here is the value for the light source itself in accordance with Regulation (EU) 2019/2015. On the box the luminous flux for the lighting fitting is stated, where the light is partly absorbed by glass/glare shield/shade and parts of the fitting, why it is lower than for the light source.

