



# SAFETY DATA SHEET

According to GHS

Page 1 of 8

Date Issued: 04/12/2023  
Date of Revision: 04/12/2023  
Date of Printing: 04/12/2023

Doc No: PTN-2  
Version: 1

## OXYPLAST PR12/1000/C; PR28/1000/C

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

#### 1.1. Product Details

Product Code : PR12/1000/C; PR28/1000/C  
Trade Name : Oxyplast Powder Coating  
Chemical Family : Polyester  
Use : Powder coating material for professional use

#### 1.2. Company Identification

Manufacturer's Name : Lea Hin Co. (Powder Manufacturers ) Pte Ltd  
Address : 293, Alexandra Road, Singapore 159940  
Telephone Number : 65-4756198  
Emergency Number : 65-96348098

#### 1.3. Contact Point

Designation : Technical Department  
Telephone Number : 65-4756198

### SECTION 2: HAZARDS IDENTIFICATION

*GHS Classification* : Acute Toxicity (Inhalation) - Category 4  
Acute Toxicity (Oral) - Category 4  
Serious Eye Damage / Eye Irritation - Category 2  
Skin Sensitization - Category 1  
Germ Cell Mutagenicity - Category 2

*Hazard Pictogram* :



GHS08

*Signal Word* : Danger

*Hazard Statements* : Harmful if inhaled  
Harmful if swallowed  
Causes serious eye irritation  
May cause an allergic skin reaction  
May cause genetic defects



# SAFETY DATA SHEET

According to GHS



## OXYPLAST PR12/1000/C; PR28/1000/C

### Precautionary Statements:

#### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves and eye/face protection. Avoid breathing dust. Contaminated work clothing shall not be allowed out of the workplace.

#### Response

- Inhaled : Remove victim to fresh air and keep at rest position comfortable for breathing.
- Swallowed : Call a doctor/physician if feeling unwell.
- Eyes : Rinse cautiously with water for several minutes. If irritation persists, get medical advice/attention.
- Skin : Wash with plenty of soap and water. If skin irritation occurs, get medical advice/attention. Wash contaminated clothing before reuse.

### Other Hazards:

Accumulation of fine powder may pose the risk of a dust explosion in the presence of air. By excessive exposure to dust, eye and respiratory tract irritation is possible.

## SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

<u>Component Name</u>	<u>CAS Number</u>	<u>Percentage by Weight</u>
1,3,5-tris(oxiranylmethyl)-	2451-62-9	< 7 %
1,3,5-triazine-2,4,6 (1H,3H,5H)-trione		

## SECTION 4: FIRST-AID MEASURES

### General Advice

In all cases of doubt, or when symptoms persist, seek medical attention.

### Inhalation

Remove to fresh air, keep the patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth.

If unconscious, place in the recovery position and seek medical advice.

### Skin Contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners. Obtain medical attention.

### Eye Contact

Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart, and seek medical advice.

### Ingestion

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do not induce vomiting.



## SAFETY DATA SHEET

According to GHS



Page 3 of 8

**OXYPLAST PR12/1000/C; PR28/1000/C**

### SECTION 5: FIRE-FIGHTING MEASURES

#### *Suitable Extinguishing Media*

Extinguishing powder, alcohol-resistant foam, water spray, carbon dioxide (CO<sub>2</sub>).

#### *Extinguishing Media Which Must NOT Be Used For Safety Reasons*

Do not use water jet.

#### *Specific Fire Hazards*

Fire will produce dense black smoke.

Decomposition products may be a hazard to health.

#### *Specific Fire Fighting Procedures*

Cool closed containers exposed to fire with water spray.

Do not allow run-off from fire fighting to enter drains or watercourses.

#### *Protective Equipment*

Appropriate self-contained breathing apparatus may be required.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### *Personal Precaution(s)*

Exclude sources of ignition and ventilate the area. Exclude non-essential personnel. Avoid breathing vapours.

Refer to Section 8 for appropriate personal protective equipment.

#### *Environmental Precaution(s)*

Do not allow to enter drains or watercourses.

#### *Method(s) For Cleaning Up*

Remove all sources of ignition. Sweep up, shovel or vacuum. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

Clean preferably with a detergent. Avoid the use of solvents.

### SECTION 7: HANDLING AND STORAGE

#### *Handling*

##### Precaution(s)

Smoking, eating and drinking should be prohibited in areas of storage and use. For personal protection, see Section 8.

##### Technical Condition(s)

Never use pressure to empty: the container is not a pressure vessel. Always keep in containers made of the same material as the supply container.

Electrical equipment and lighting should be protected to appropriate standards and to prevent dust coming into contact with hot surfaces, sparks or other ignition surfaces.

##### Safe Handling Advice

Keep the container tightly closed. Exclude sources of heat, sparks and open flame. Non-sparking tools should be used. Avoid skin and eye contact. Avoid inhalation of vapour and spray mist.



# SAFETY DATA SHEET

According to GHS



## OXYPLAST PR12/1000/C; PR28/1000/C

### Storage

- Precaution(s)  
No smoking. Prevent unauthorised access.
- Storage Condition(s)  
Store in a dry, well-ventilated place away from sources of heat, ignition and direct sunlight. Store at temperatures below 30°C.  
Containers which are opened should be properly resealed and kept upright to prevent leakage.
- Separation of Incompatible Product(s)  
Store separately from oxidising agents and strongly alkaline and strongly acidic materials.
- Packaging / Tank Material  
Made of the same material as the supply container.

## SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

### a) Exposure Limit

Preparation	CAS Number	Standard	Reference
Powder coating dust	Not Applicable	5 mg/m <sup>3</sup>	ACGIH TLV

One or more of the following substances may be present in the powder:

Substance	CAS No.	PEL (Long Term) * mg/m <sup>3</sup>
Carbon black	1333-86-4	3.5
Aluminium metal dust	7429-90-5	10
Iron oxide dust	1) 20344-49-4 2) 1309-37-1	1) 5 (as Fe) 2) 5 (as Fe)
Titanium dioxide	13463-67-7	10
Manganese compound	Not available	5 (as Mn)
Barium sulphate	7727-43-7	10
Amorphous silica dust	1) 112926-00 2) 112945-52-5	1) 2 2) 2
Aluminium oxide	1344-28-1	10
Chromium (III) compound	1308-38-9	0.5 (as Cr)
Mica dust	Not available	3
Tin oxide	Not available	2 (as Sn)
1,3,5-tris(oxiranylmethyl)- 1,3,5-triazine-2,4,6 (1H,3H,5H)-trione	2451-62-9	AGCIH: 0.05 mg/m <sup>3</sup> TWA

\* Means the permissible exposure level over an 8-hour working day and a 40-hour work week, as defined in the Factories (Permissible Exposure Levels of Toxic Substances) Order, 1997 Edition (Singapore)

### b) Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.



## SAFETY DATA SHEET

According to GHS



Page 5 of 8

### OXYPLAST PR12/1000/C; PR28/1000/C

#### c) Personal Protection

- Respiratory Protection : Wear appropriate breathing apparatus if air renewal is not sufficient to maintain dust/vapour under TLV.
- Eye Protection : Eye protection eg. splash-proof goggles designed to protect against powder splashes should be worn.
- Hand Protection : Barrier creams may help to protect exposed areas of the skin but are not substitutes for full physical protection. They should not be applied once exposure has occurred.  
When skin exposure may occur, advice should be sought from glove suppliers on appropriate types. Wear impermeable gloves.
- Skin And Body Protection : Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at the neck and wrists through contact with the powder is avoided.

#### d) Hygiene Measure(s)

When using, do not eat, drink or smoke. Wash hands and face with soap before break and at the end of works. Keep away from food and drink. Take a shower at the end of the working day.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

- Physical State : Powder
- Colour : One of various colours
- Odour : None to slightly characteristic
- Water Solubility : Insoluble
- Fat Solubility : Insoluble
- Solvent Solubility : Soluble in some specific organic solvents
- Boiling Point : Not Applicable
- Melting Point (°C) : >70°C
- Percentage Volatile : Not Applicable
- Evaporation Rate : Not Applicable
- Vapour Density : Not Applicable
- Specific Gravity : 1.2 – 1.9
- Flash Point : Not Applicable
- Explosion limits : 40 – 70 g/m<sup>3</sup>
- pH : Not Applicable

### SECTION 10: STABILITY AND REACTIVITY

- Stability : Stable under the recommended storage and handling conditions (see Section 7).
- Incompatibility (Materials To Avoid) : Keep away from oxidising agents and strongly alkaline and strongly acidic materials to prevent the possibility of exothermic reaction.
- Hazardous Decomposition Products : When exposed to high temperatures, may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, N<sub>x</sub>O<sub>y</sub>.



# SAFETY DATA SHEET

According to GHS



**OXYPLAST PR12/1000/C; PR28/1000/C**

## SECTION 11: TOXICOLOGICAL INFORMATION

### General Information

There is no data available on the product itself.

### Acute Toxicity

- Inhalation*  
Cough, difficult breathing or other symptoms of poisoning may occur within some hours.
- Skin Contact*  
Dust may cause irritation in skin folds or by contact in combination with tight clothing.
- Eyes contact*  
Splashes in the eyes may cause irritation and reversible local damage.
- Ingestion*  
May cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

### Sensitisation

May cause sensitisation of susceptible persons by skin contact.

### Toxicity of Repeated or Prolonged Exposure

Repeated or prolonged exposure may cause irritation of eyes and skin.

*Respiratory Sensitization* : May cause allergy or asthma symptoms or breathing difficulties if inhaled

*Germ Cell Mutagenicity* : Available data characterizes this material as mutagenic (in vivo/in vitro)

*Carcinogenicity* : Not classified

*Reproductive Toxicity* : Not classified

*Specific Target Organ Toxicity (Single Exposure)* : Not classified

*Specific Target Organ Toxicity (Repeated Exposures)* : Not classified

*Aspiration Hazard* : Not classified

## SECTION 12: ECOLOGICAL INFORMATION

### General Information

This material is not classified as dangerous for the environment. The ecological assessment for this material is based on the evaluation of its components. There are no data available on the material itself.

- Ecotoxicity: : Not available
- Persistence and Degradability : Not available
- Bioaccumulative Potential : Not available
- Mobility in Soil : Not available

### Environmental Toxicity

Ecological problems are not known or expected under normal use.

### Other Adverse Effects

Hazard to the Ozone Layer : Not available



# SAFETY DATA SHEET

According to GHS



Page 7 of 8

**OXYPLAST PR12/1000/C; PR28/1000/C**

## SECTION 13: DISPOSAL CONSIDERATIONS

### Disposal Method

The generation of waste should be avoided or minimised wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product and any by-products should at all times comply with the requirements of an environmental protection and waste disposal legislation and any regional and local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

## SECTION 14: TRANSPORT INFORMATION

### General Information

Not regulated

- UN Number* : Not regulated
- UN Proper Shipping Name* : Not applicable
- Transport Hazard Class(es)* : Not applicable
- Packing Group* : Not applicable
- Environmental Hazards* : None
- Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code* : Not applicable
- Special Precautions for User* : Always transport in closed packagings that are upright and secure

### IMDG

Not restricted / Not regulated

### Air Transport

IATA: Not restricted / Not regulated

This material is not in violation of IATA regulations concerning dangerous goods

## SECTION 15: REGULATORY INFORMATION

### Labelling

Not subject to labelling according to OSH (Classification, Packaging and Labelling of Hazardous Chemicals - 1997)

### Risk Phrases

None according to OSH (Classification, Packaging and Labelling of Hazardous Chemicals -1997)

### Safety Phrases

None according to OSH (Classification, Packaging and Labelling of Hazardous Chemicals -1997)

### REACH Status

This product is not in compliance with the current requirements of REACH Regulation



## SAFETY DATA SHEET

According to GHS



Page 8 of 8

**OXYPLAST PR12/1000/C; PR28/1000/C**

### SECTION 16: OTHER INFORMATION

#### *Important remarks*

- As the specific conditions of use of the product are outside the supplier's control, the user is always responsible for ensuring that the requirements of relevant legislations are complied with.
- The information contained in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Date Issued: 04/12/2023

Date of Revision: 04/12/2023