

		FIRETDOEK.NL																						
		getest volgens																						
kleur	Zwart		X	X			X	X	X	X	X	X	X	X	X	Ketinger	LANTOR	FREUDENBERG			X	X	X	
	Grijs		X															beige			X	X	X	
materiaal	Wit		X															X			X	X	X	
	RAL kleuren					X																		
extra	Pantone kleuren																							
	Printable Picture																							
materiaal	Cellulose+glass		X	X	X													X						
	Glasfibre																	X						
extra	PET																						X	
	Bonding		acryl	acryl	acryl																			
extra	Row material																							
	Synthetic																							
extra	Supply material																							
	kleur																							
extra	Hotmelt				X				X			X												
	FormaldeHyde emissions	EN 717-1	E1	E1	E1												E1	E1					E1	
extra	Density g/m2	DIN EN 29073-1	50 +/- 3	50 +/- 3	50 +/- 3	50 +/- 3	100 +/- 3										130	150 +/- 3	100 +/- 3			200	245	250
	Thickness mm	DIN ISO 9073-2	0,23	0,27	0,27	0,27	1										0,17		0,35	50 +/- 3	0,23	0,15	0,3	0,3
extra	Tensile strength Longitudinal N/5cm	DIN EN 29073-3	>60	>60	>60	45													>120	>60				
	Tensile strength transversal N/5cm	DIN EN 29073-3	>40	>40	>40	60													>100	>40				
extra	Elongation Longitudinal %	DIN EN 29073-3	>1,5	>1,5	>1,5	30													>2	>1,5	2%			
	Elongation transversal %	DIN EN 29073-3	>1,5	>1,5	>1,5	55													>1,5	>1,5	5%			
extra	VOC Emissie	ISO 16000/16017	A+	A+	A+														A+					
	Air Permeability l/m2 x sec	EN ISO 9237	950				4800											500	450	950	950			
extra	Flow resistance PA s/m	DIN 29053	190	190															300		267			
	reaction to fire on 0.8mm alu	DIN EN 13501	A1-S1,d0	A1-S1,d0															A1-S1,d0	A1-S1,d0				
extra	reaction to fire	DIN EN 13501																						
	reaction to fire	DIN 4102	B1	B1		B2	B2										B-S1,d0	B-S1,d0	B-S1,d0	B-S1,d0	B-S1,d0	B-S1,d0	B-S1,d0	
extra	Bouwbesluit 2012																							
	sound absorption classe	DIN EN 11654	C	C	C	X	X	X										X	C	X	X	A	D	A
extra	Scheurbaar																							
	hutterproof																X							
extra	geen stof																							
	geurloos																X	X						
extra	recyclebaar																X	X	X	X	X	X	X	
	UV bestendig																X	X	X	X	X	X	X	
extra	naaibaar																X	X	X	X	X	X	X	
	plakbaar SPUITLIJM		X	X		X	X	X	X	X	X	X						X						
extra	nietbaar		X	X	X	X	X	X	X	X	X	X					X	X	X	X	X	X	X	
	Anti Bacterien																X	X	X	X	X	X	X	
extra	Vochtbestendig																X							
extra																	X							
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra																								
extra						</																		



TOEPASSING

FA 450 C

X
X
X
X

X

100%
Akoestical

E1
450 +/- 3
2,5

A+

B-S1,d0

X
A
X
X
X
X
X
X
X
X
X
X
X
X
X
X

roll

FA450 C

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X

X