



Contact Us

- www.rainwater-terrace.com
- **O** 01937 845176

isit Website

☑ rainwater-terrace@design4plastics.com






- Hosepipe Connector ①
- 10 Adjustable "Shrubbler Spikes" (2)
- Connector 3/4" BSP to 4mm barb 3
- 10 Metres of 4mm micro hose 4
- 4 End bungs (5)
- 2 Tee-connectors. 6
- 1 Filter ⑦



Each "Shrubbler Spike" has its own adjustable valve on top which can be used to control the flow of water to each plant. This is done by turning the round knob on top of each spike.

- 1) Position the "Shrubbler Spikes" in planters or directly into the ground.
- 2) Starting furthest away, cut lengths of the 4mm micro hose to "daisy-chain" them together, leaving a little slack in case you need to move them in the future.
- 3) Supplied are 2 tee connectors so that you can take tubing to both sides of the Rainwater Terrace.





- **6)** Fit the hosepipe adapter to the highest container to get the maximum pressure (refer to other side for fitting instructions) then fit the micro-hose onto the spigot.
- **7)** Turn on the tap on the hosepipe adapter and adjust the individual drippers to the desired flow rate. It is best to start with them all fully closed and unscrew the top on each one until the desired flow rate is achieved.
- 8) Close the tap when you feel the plants have had enough water.















