





CUTTING SYSTEMS

ETR 350 P / ETR 400 P (wet/dry)
Powerful with big cutting depth up to 152 mm

The cutting systems for dust reduced cutting ETR 350 P / ETR 400 P (wet/dry)

Big cutting depth up to 152 mm (ETR 400 P)



performance optimized & more powerful special motor with power electronics









SPECIFICATIONS	ETR 350 P	ETR 400 P
Power input	2700 W	2850 W
Rated voltage	230 V ~	230 V ~
Rated speed	2200 rpm	1950 rpm
Max. disc diameter	350 mm	400 mm
Max. cutting depth	130 mm	152 mm
Spindle connection	Ø 25.4 mm	Ø 25.4 mm
Weight	12.9 kg	13.4 kg
Order no.	06818000	06825000

Supplied

in a box incl. diamond cutting disc, dust guard and assembly tools



integrated water supply with flow regulator

easy adjustment of the watervolume



dry cut for renovation

where no wet cut is possible - e.g. Living room renovation

APPLICATION:

- Cutting of mineral materials, f. e. concrete, brick and natural stone
- Breakthroughs into brickwork
- Wall cuttings for installations
- Slitting of expansion joints
- Civil engineering, drilling and sawing operators, gardening and landscaping

Simple, safe guidance through innovative drive concept







FEATURES:

- Special oil bath gearbox with optimal adjusted speed for fast working
- Electronic soft start, constant speed, temperature control and over current cut-off, overload indication
- Best results in system with the EE premium diamond cutting disc
- Immersion function
- Adjustable cutting depth limitation without any tools f. e. for the cutting of screed (accessory)
- Adapter and diamond cutting disc for working near to the edge (accessory)
- Exact wall cuttings by using a guide rail (accessory) easy mounting, easy feed, low vibration
- Wide supporting rolls exact guiding
- Spindle lock easy tool change
- Robust metal suction hood
- Handle and hood adjustable ergonomic handling in different working positions
- Nozzle diameter 35 mm direct connection of industrial vacuum cleaner of EIBENSTOCK DSS series–
- Cut-off carbon brushes protection of the motor









IΩΩ 1919/







Safe, precise and energy-saving with crank feed for relaxed working

FEATURES:

- Quick mounting
- Easy transport by only person
- Robust carriage mounted on roller bearings – easy feed
- Easy modular possibility of extension for long straight cuts

 fast mounting of the machine without any tools



Accessories	Order no.	Order no.
	ETR 350 P	ETR 400 P
Set of Guide rails 200 cm		
2x Guide rail 100 cm incl. machine holder, connection and mounting	3744N000	3744N000
Choose and order also the fastening set!		
Guide rail 100 cm incl. connection and		
mounting	3744P000	3744P000
Choose and order also the fastening set!		
Fastening set for Guide rails	35729000	35729000
For assembly required!		
Diamond cutting disc Premium	3744G000	3744T000
Diamond cutting disc near to the edge Premium	3744H000	3744V000
Set of Adapter for cutting near		
to the edge	3744K000	3744W000
Adjustment and limitation for cutting depth	3744L000	3744U000





Hazardous dust (e. g. silica dust) has to be suctioned by a Dust Class M Vacuum Cleaner! For our electric power tools we are recommending to use a Vacuum Cleaner of our Eibenstock DSS range!



Elektrowerkzeuge GmbH Eibenstock Auersbergstraße 10 08309 Eibenstock, Germany

Phone: +49 (0) 3 77 52 - 50 30 Fax: +49 (0) 3 77 52 - 20 19 Internet: www.eibenstock.com E-Mail: office@eibenstock.com

Certified according to DIN EN ISO 9001:2015
Technical changes excepted! Illustrations may vary!

Your dealer: