

FIREMANS POLE (ADD-ON) - OPTION 'A' AND 'B' POSITIONS ASSEMBLY INSTRUCTIONS

CONTENTS

Warnings	21
Assembly Tips	3
Inventory and Tools	24
Assembly Instructions	25
Firemans Pole Add-on Orientation	25
Firemans Pole Assembly	96
Existing Frame Preparation	27
Position Option 'A' Installation	98
Position Option 'B' Installation	e 10
Maintenance	213

WARNING

PLEASE CAREFULLY READ ALL INFORMATION CONTAINED IN THIS ASSEMBLY MANUAL BEFORE YOU INSTALL AND USE YOUR FUNKY MONKEY BARS®.


SAFETY NOTICE


- 1. Any person handling or using the Funky Monkey Bars® products must follow the instructions as described in this document. The person in charge of assembling and using the equipment must ensure that the recommendations for use given in this document are seen by all users.
- 2. Only use the Funky Monkey Bars® after they have been fully assembled and after checking that the fittings are tightened properly (refer to page 3 Correct Tightening Method).
- 3. DO NOT install your Funky Monkey Bars® over concrete, asphalt, packed earth, wood decking or any other hard surface. A fall onto a hard surface can result in serious injury or death.
- 4. Inspect all grub screws, bolts and nuts at the beginning of each play session to ensure your Funky Monkey Bars® are tight and secure.
- 5. Ensure all tubes are fully inserted into fittings until you hear the magic "CLUNK" sound.
- 6. Ensure your Funky Monkey Bars® are properly secure at ALL times. Pegs are in place and inserted fully into the ground.
- 7. DO NOT exceed the maximum load/weight limit as recommended by Funky Monkey Bars®.
- 8. Children should be supervised by an adult at all times.
- Installing a gym/crash mat under the fall zone area of your Funky Monkey Bars® would be recommended for children learning this new skill. This will reduce the chance of injury and build the child's confidence while they build strength and master the skill.
- 10. Ensure you have thoroughly read your assembly and installation instructions and viewed our on-line installation videos at https://www.funkymonkeybars.com/blogs/installation-maintenance-videos
- 11. DO NOT climb, sit or stand on top of the monkey bar (horizontal ladder) section.
- 12. DO NOT jump from the top of any section of the monkey bar.
- 13. DO NOT use your Funky Monkey Bars® when wet as the steel will be slippery.
- 14. DO NOT attach items to your frame that are not designed specifically to be used with Funky Monkey Bars®, especially lower quality products that have not been approved by Funky Monkey Bars®.
- 15. Ensure the height of your Funky Monkey Bars® (horizontal ladder) are set at a level that is age appropriate.
- 16. DO NOT install your Funky Monkey Bars® over or near objects that could interfere with users in an unsafe way. Maintain a clear area around your Funky Monkey Bars®.
- 17. DO NOT use your Funky Monkey Bars® while under the influence of drugs and alcohol.
- 18. Wear clothing free of drawstrings, hooks, loops or anything that could get caught while using your Funky Monkey Bars® and result in entanglement and/or strangulation.


ASSEMBLY

- 1. Keep small children away from the Funky Monkey Bars® during assembly.
- 2. Do not attempt to use the Funky Monkey Bars® until it is completely assembled and every fitting is tight and secured.
- 3. Installation typically takes 1-2 hours to complete. Two people are recommended for assembly.
- 4. Ensure all fittings are tightened to the correct tightening method as described on page 3.
- 5. Assembly should be carried out on clean, dry, level surface

Please refer to the video section on the Funky Monkey Bars® website for more handy tips and assembly instructions at http://www.funkymonkeybars.com/pages/videos







Assembly requires 2 adults.

Heavy items !

Work on flat level surface.

LOCATION

- 1. A safe fall zone around your Funky Monkey Bars® is essential. A minimum distance of 1.5m to 2m (5 ft to 6.5ft) is recommended around the elevated hanging points of your Funky Monkey Bars®.
- 2. Place your Funky Monkey Bars® on level ground, away from any structure or obstruction such as a fence, garage, house, overhanging branches, laundry lines or electrical wires and remove any obstructions beneath your Funky Monkey Bars®.
- 3. Ensure your Funky Monkey Bars® are positioned away from retaining walls, pool fences, structures and other play equipment. Maintain a clear space around the whole perimeter of your Funky Monkey Bars®.
- 4. Place your Funky Monkey Bars® on the most level surface available.


MAINTENANCE

- 1. At the beginning of each heavy play session we recommend the following maintenance processes be performed on your Funky Monkey Bars®:
 - Tighten all bolts, grub screws and applicable hardware (as per page 3)
 - Lubricate all metallic moving parts as per instructions (flying fox, swing hooks etc)
 - Check all protective coverings on bolts, pipes, edges and corners. Replace if they are loose, cracked or missing.
 - Check all moving parts including swing seats, shackels, snap hooks, chains and trolleys for wear, rust, or other deterioration. Replace as needed.
- 2. Twice a month during play season we would recommend the following maintenance processes be performed on your Funky Monkey Bars®:
 - Tighten all connections and hardware
 - Check all protective coverings on bolts, pipes, edges and corners. Replace if they are loose, cracked or missing.
- 3. Once a month during play season we would recommend the following maintenance processes be performed on your Funky Monkey Bars®:
 - Lubricate all metallic moving parts as per instructions (flying fox, swing hooks etc). If swings start to squeek then lubricate swing hooks.
 - Check all moving parts including swing seats, ropes, chains and trolleys for wear, rust, or other deterioration. Replace as needed.
 - Owners shall be responsible for maintaining the legibility of any warning labels.


For additional information concerning your Funky Monkey Bars®, please contact our customer service team or check our website for any important updates. Phone - 1300 912 198 or www.funkymonkeybars.com

CORRECT INSERTION INTO FITTINGS - (INDICATIVE DIAGRAM SHOWN)


All tubes must be fully inserted until contact is made with adjoining tube.




CORRECT TIGHTENING METHOD OF GRUB SCREWS - (INDICATIVE DIAGRAM SHOWN)



TOOLS REQUIRED FOR INSTALLATION



FITTINGS



Elbow D-125 Long Tee D-104

4 hole Base Plate D-131

> **4**x Peg


SELECT DESIRED ORIENTATION OF FIREMANS POLE ADD-ON.

(Assembly for Gorilla shown in example)

1

FIREMANS POLE ADD-ON POSITION OPTION B.

Long tee added as extension to swing leg. **REFER TO STEPS 2-5 THEN STEPS 13 ONWARDS**



NOTE: Both position A & B require slightly different assembly methods. Please refer to the applicable steps as follows.


2 ASSEMBLE FIREMANS POLE AND EXTENDER TUBE




1. On flat level ground, slide fittings onto firemans pole and extender tube, ensure fittings are fully engaged.

> **1x** 4 hole Base Plate D-131

2. Fully tighten all grub screws





SX2


2x Elbow

D-125


 δ

3 ATTACH TOP TUBE

ľ0,




ASSEMBLY INSTRUCTIONS - EXISTING FRAME PREPARATION



5 LOWER LEG TO GROUND



Lower loosened leg and twirly whirly to the ground



NOTE: If you are installing with a cargo net in place simply leave the leg and twirly whirly loose in position. Refer to cargo net instructions.

6


THE FOLLOWING STEPS 7-10 ARE FOR THE FIREMANS POLE **POSITION OPTION 'A'.**

Please refer to page 10 for position option 'B'.


7 ATTACH LONG TEE



- 1. With grub screws facing outwards slide the long tee onto the swing bar to the desired location for the firemans pole.
- 2. Fully tighten grub screws





8 REATTACH LEG TO SWING BAR



Lift the lowered swing leg assembly from step 5 back into position and fully insert the swing bar into the leg elbow.


Fully tighten grub screws.





12 THE FOLLOWING STEPS 13-17 ARE FOR THE FIREMANS POLE **POSITION OPTION 'B'**.

Please refer to page 8 for position option 'A'. For drawing clarity the selected install location shown is the same as position A.











Slide long tee onto lowered swing leg from step 13, and tighten grub screws.


Ensure leg is not over inserted - & is level with side hole.











18 THE FOLLOWING STEPS APPLY TO BOTH POSITION OPTIONS 'A' ABD 'B'.

19 **FINAL CHECKS**



1. Ensure frame is square and level.

- Firmly tighten all grub screws and bolts.
 All base plates are pegged down.



MAINTENANCE.



At the beginning of each heavy play session (especially a party) and twice a month during play season ensure;

1. Tighten all hardware - grub screws, nuts and bolts.

- 2. Pegs are in place and fully secure.
- 3. Lubricate all metallic moving parts with WD40 or Vasaline (trolley and swing hooks.)
- 4. Ensure your frame is level and square.

FAILURE TO DO SO COULD RESULT IN SERIOUS INJURY OR DEATH.

FOR MORE INFORMATION AND ASSEMBLY TIPS PLEASE REFER TO OUR WEBSITE VIDEO INSTRUCTION SECTION AT HTTP://WWW.FUNKYMONKEYBARS.COM/PAGES/VIDEOS

21 HAVE FUN



NOTES.



ABN 72 164 496 520

 \bigcirc

1300 912 198

info@funkymonkeybars.com

www.**funkymonkeybars**.com

9 Cutting Way, **Yangebup** WA 6164





All Funky Monkey Bars® designs are registered and protected under IP Australian certification.