


# Test Verification of Conformity

## Verification Number: 210901907SHA-V1

On the basis of the referenced test report(s), sample(s) tested of the below product have been found to comply with the standards harmonized with the directives listed on this verification at the time the tests were carried out. Other standards and Directives may be relevant to the product. This verification is part of the full test report(s) and should be read in conjunction with it <them>.

Once compliance with all product relevant  mark directives are verified, including any relevant e.g. risk assessment and production control, the manufacturer may indicate compliance by signing a Declaration of Conformity themselves and applying the mark to products identical to the tested sample(s).

Applicant Name & Address:	Afore New Energy Technology (Shanghai) Co., Ltd Build No.7, 333 Wanfang Road, Minhang District, Shanghai. China. 201112
Product Description: Ratings & Principle Characteristics:	PV Grid interactive inverter See Appendix
Models/Type References:	BNT003KTL, BNT004KTL, BNT005KTL, BNT006KTL, BNT008KTL, BNT010KTL, BNT012KTL, BNT013KTL, BNT015KTL, BNT017KTL, BNT020KTL, BNT025KTL
Brand Name:	Afore
Relevant Standards/Directives:	EN IEC 61000-6-1:2019; EN 61000-6-3:2007/+A1:2011; the EMC Directive 2014/30/EU
Verification Issuing Office Name & Address:	Intertek Testing Services Shanghai Building No.86, 1198 Qinzhou Road (North), Shanghai 200233, China
Date of Tests:	2021-08-25 to 2021-12-05
Test Report Number(s):	210901907SHA-001

### Signature



**Name: Jonny Jing**  
**Position: Manager**  
**Date: 2021-12-24**

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## APPENDIX: Test Verification of Conformity

This is an Appendix to Test Verification of Conformity Number: 210901907SHA-V1

Ratings:

Specifications table				
Model	BNT003KTL	BNT004KTL	BNT005KTL	BNT006KTL
<b>Input:</b>				
Vmax PV (Vdc)	1100	1100	1100	1100
Isc PV (absolute Max.) (A)	25 x 2	25 x 2	25 x 2	25 x 2
Number MPP trackers	2	2	2	2
Number input strings	1/1	1/1	1/1	1/1
Max. PV input current(A)	15 x 2	15 x 2	15 x 2	15 x 2
MPPT voltage range (Vdc)	150-1000	150-1000	150-1000	150-1000
Vdc range @ full power (Vdc)	200-850	200-850	200-850	250-850
<b>Output</b>				
Normal Voltage(V)	3P+N+PE/3P+PE 230/400			
Frequency (Hz)	50			
Current (normal) (A)	4.4	5.8	7.3	8.7
Current (Max. continuous) (A)	5.3	7	8.5	10.5
Power rating (W)	3000	4000	5000	6000
Power Rating (VA)	3000	4000	5000	6000
Power factor /rated	1 (-0.8~+0.8 adjustable)	1 (-0.8~+0.8 adjustable)	1 (-0.8~+0.8 adjustable)	1 (-0.8~+0.8 adjustable)
<b>others</b>				
Protective class	Class I			
Ingress protection (IP)	IP 65			
Temperature (°C)	-25°C to +60°C (Derating 45°C)			
A	Non-isolated			
Overvoltage category	OVC III (AC Main), OVC II (PV)			
Weight (kg)	16			
Dimensions (WxHxD) (mm)	510 x 370 x 167			

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

<b>Specifications table</b>				
<b>Model</b>	<b>BNT008KTL</b>	<b>BNT010KTL</b>	<b>BNT012KTL</b>	<b>BNT013KTL</b>
<b>Input:</b>				
Vmax PV (Vdc)	1100	1100	1100	1100
Isc PV (absolute Max.) (A)	25 x 2	25 x 2	25 x 2	25 x 2
Number MPP trackers	2	2	2	2
Number input strings	1/1	1/1	1/1	1/1
Max. PV input current(A)	15 x 2	15 x 2	15 x 2	15 x 2
MPPT voltage range (Vdc)	150-1000	150-1000	150-1000	150-1000
Vdc range @ full power (Vdc)	300-850	500-850	500-850	500-850
<b>Output</b>				
Normal Voltage(V)	3P+N+PE/3P+PE 230/400			
Frequency (Hz)	50			
Current (normal) (A)	11.6	14.5	17.4	18.9
Current (Max. continuous) (A)	13.5	17	21.5	22
Power rating (W)	8000	10000	12000	13000
Power Rating (VA)	8000	10000	12000	13000
Power factor /rated	1 (-0.8~+0.8 adjustable)	1 (-0.8~+0.8 adjustable)	1 (-0.8~+0.8 adjustable)	1 (-0.8~+0.8 adjustable)
<b>others</b>				
Protective class	Class I			
Ingress protection (IP)	IP 65			
Temperature (°C)	-25°C to +60°C (Derating 45°C)			
Inverter Isolation	Non-isolated			
Overvoltage category	OVC III (AC Main), OVC II (PV)			
Weight (kg)	16			17
Dimensions (WxHxD) (mm)	510 x 370 x 192			

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Specifications table				
Model	BNT015KTL	BNT017KTL	BNT020KTL	BNT025KTL
<b>Input:</b>				
Vmax PV (Vdc)	1100	1100	1100	1100
Isc PV (absolute Max.) (A)	30 + 48	48 x 2	48 x 2	48 x 2
Number MPP trackers	2	2	2	2
Number input strings	1/2	2/2	2/2	2/2
Max. PV input current(A)	20 + 32	32 x 2	32 x 2	32 x 2
MPPT voltage range (Vdc)	150-1000	150-1000	150-1000	150-1000
Vdc range @ full power (Vdc)	500-850	500-850	500-850	500-850
<b>Output</b>				
Normal Voltage(V)	3P+N+PE/3P+PE 230/400			
Frequency (Hz)	50			
Current (normal) (A)	21.8	24.7	29	36.3
Current (Max. continuous) (A)	27	30	32	40
Power rating (W)	15000	17000	20000	25000
Power Rating (VA)	15000	17000	20000	25000
Power factor /rated	1 (-0.8~+0.8 adjustable)	1 (-0.8~+0.8 adjustable)	1 (-0.8~+0.8 adjustable)	1 (-0.8~+0.8 adjustable)
<b>others</b>				
Protective class	Class I			
Ingress protection (IP)	IP 65			
Temperature (°C)	-25°C to +60°C (Derating 45°C)			
Inverter Isolation	Non-isolated			
Overvoltage category	OVC III (AC Main), OVC II (PV)			
Weight (kg)	17	19		
Dimensions (WxHxD) (mm)	510 x 370 x 192	535 x 370 x 192		

**Signature**



**Name: Jonny Jing**  
**Position: Manager**  
**Date: 2021-12-24**

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.